
PRIL 1959

MACHINE AND TOOL

blue book













Interview with Motorola's

ROBERT W. GALVIN

"Production engineers . . . their status is higher."

Complete Contents Pages 5 and 6

5 Basic Reasons why MARVEL HACK SAWS CUT-OFF MORE ACCURATELY...

The consistently accurate performance of MARVEL Heavy Duty Hack Saws is no accident. MARVEL engineers knew, many years ago, that to produce and maintain accurate cutting-off, a hack saw must be designed and built like a fine machine tool.

Some of the basic design principles built into the modern MARVEL Hack Sawing System that makes it the most accurate cutting-off method you can use are:

1. V-Way Design... Greater Rigidity

Upright and Saddle are precision machined and fitted to form a rigid, integral unit capable of withstanding any cutting load with no deflection or side movement.

2. Anti-Friction Bearing Construction


Anti-friction ball or roller bearings are used at all load carrying points. Even the strongly braced saw frame reciprocales on heavy duty, fully enclosed preloaded ball bearings which provide permanent, frictionless rigidity and true-running, straight line cutting strokes.

3. Minimum Blade Frame Reach

Cless-coupled design and crank lever action of MANVE Saws keeps the saw frame and blade reach very short in relation to the vertical V-ways on which the unit is mounted. This insures optimum rigidity, even under the most severe operating conditions.

4. Positive Relief Blade Lift

On the return stroke, positive relief lift raises the blade to provide proper and "cushioned" lead-in on the next cutting stroke. This prolongs blade sharpness, life and accuracy.



5. Rigid Cutting Tool

Cutting-off accuracy requires a rigidly held, relatively short cutting tool. MARVEL Unbreakable High-Speed-Edge Hack Saw Blades, which combine a narrow high speed steel cutting edge permanently weided to a tough alloy steel body, can be tensioned from 200% to 300% more taut than ordinary blades. This provides a most rigid cuttine edge.

Catalog C85 has complete details, facts and figures on both Marvel metal cutting Hack Saws and Band Saws. Write for it today.



PL-1305



ARMSTRONG-BLUM MFG. CO. 5700 W. BLOOMINGDALE AVE., CHICAGO 39, ILL.

HEADS for DRILLING, REAMING and TAPPING


Any Number of Holes, in Any Pattern, in Any Material, on All Centers



Round, rectangular, and diamond shaped housings standard. Special, heavy duty heads available. All the spindles the jobs need.



Zagar "66" holds up to 6 spindles; 31/2" spread; maximum drill dia. 5/16". Low price, quick delivery.



Varying size holes, of varying depths on all centers are drilled in one pass. Hole patterns can be changed with a minimum of expense and delay.

Standard Zagar gearless drill heads can be installed on your drill press or in complete machining units. The gearless principle permits larger number of spindles for holes to be drilled, reamed or tapped simultaneously. Exclusive chip breaker action provides additional economies.

المنالة:

Write for Manual "B-4" for engineering data.

Zagar's answer to increasing hole production is in more spindles and fewer machines. Send in your drilling problem to Zagar or contact the nearest representative whose listing appears in the telephone book.

ZAGAR, INCORPORATED 23900 LAKELAND BLVD.
CLEVELAND 23, OHIO
TOOLS FOR INDUSTRY and SPECIAL MACHINERY

1872 1959

LATHES have always met the standards of the times

There's a real plus-factor for the user, in the long life and business continuity of the builder of a machine tool. The tool always has the original manufacturer behind it . . . to fulfill a guarantee, to supply parts and accessories, to see that it continues to operate and make money for the owner.


If you're interested in knowing more about this well-designed, modern lathe, with more than 86 years of integrity behind it, write for our new brochure on the Wade No. 94 Lathe.



SOFT BLANK TOP JAWS

immediate delivery

STANDARDS



Soft Blank Top Jaws may be used on any chuck having master jaws. Both medium and heavy duty styles are carried in stock and made from 1020 steel.

> SAVE **OVER** 50%

Write today for prices

HURON MACHINE PRODUCTS, INC.

P.O. Box No. 2274

DEARBORN, MICHIGAN



Reader's Guide



	April, 1959	Vol. 54 - No. 4	
	FEATURES IN THIS ISSUE	79	
	LETTERS TO THE EDITO	R 82	
	ROUNDUP OF WASHING	ron news 89	
	AS THE EDITOR SEES I	т 93	
Interview	An Interview with Rob Motorola, Inc.	ert W. Galvin, President,	95
	By PAUL A. MELIN	IE	
Mist Cooling	Mist Cooling Up-to-I By Paul A. MELIN		105
Labor Arbitration	Simplification, Part Standards Hold Up	in Arbitration?	110
	By HAROLD R. NIS	SLEY	
Carbide Tool Cutting	Long Range Outlook for Man-Made Diamonds 118 By Chester A. Nisula		
Gear Shaping	Gear Shaper Chamfer By J. SIEGFRIED SI		128
Maintenance	Proper Care of Oil	Seals	133



Accepted as Controlled Circulation Publication at Pontiac, Illinois

Copyrighted, 1959, by the Hitchcock Publishing Company,
Wheaton, Ill.



News of Automation	Tape Controlled Combination Machine for Small Lot Manufacturer		
Field Reports	Grease Gun Barrel Production Upped 200% 146 Unique Locating and Clamping 149 Belt Guard is Made of Glass Reinforced Plastic 150		
Shop Hints	Indicator Holder for Milling Machine		
Departments	Meetings 86 Free Literature 159 News of the Industry 171 The Market Place 278 Products Index 285 Index to Advertisers 291		
Editorial Staff	WILLIAM F. SCHLEICHER, vice president and editorial director; Paul A. Meline, managing editor; Darrell Ward, engineering editor; D. M. Carlson, assistant editor; Joyce Richardt and Lois Newman, readers' service.		
Editorial Advisory Board	M. John Ahlstromer, asst. factory mgr., Chicago Screw Co.; Ronnie Burritt, factory mgr., J. J. Tourek Mfg. Co.; Ed Fluskey, consulting eng., Revere Camera Co.; Homer F. Griffith, works mgr, Construction Equipment Div., International Harvester Co.; Joe Kosinski, works mgr., Scully-Jones & Co.; Paul Prikos, vice pres., Prikos & Becker Tool Co.		
Business Staff	ROBERT C. VAN KAMPEN, president; VINCENT C. HOGREN, executive vice president; J. E. HITCHCOCK, vice president; M. L. YONTS, secretary and advertising production manager; OLIVER S. PEPPER, business manager; JOHN S. TODD, production manager; ROBERT L. SPRECKELS, circulation manager; GENE WEST, fulfillment manager; RAY SIETSEMA, director of research; BRUCE B. HOWAT, director of marketing; L. M. SCHROEDER, advertising art director.		
	Hitchcock District Managers are listed on Page 64.		
Subscription rates:	\$5.00 per year in U.S.A. \$6.00 per year elsewhere		



produces
lapping machines
for any piece part...
any production speed

The option of selection is particularly important when it comes to precision lapping machines. Apply your own standards of economy, machine size, production line output, piece part size and shape . . . and select a Spitfire flat or cylindrical lapping machine for your own specifications! Spitfire engineers and manufactures the most complete line of lapping machines in the industry to produce flatness to 1 light band, microinch finishes to 2 RMS or less. Result: your selection means maximum efficiency and economy—whatever the lapping and/or finishing job!





free!

get full details about the complete Spitfire line of lapping machines. Write, phone today.

NEW!

Spitfire 24" Precision Flat Lapping machine with pneumatic lifting and pressure arms. Nth degree flat lapping operation coupled with unparalleled unloading and loading facilities. Newest addition to the complete Spitfire line.

SPITFIRE TOOL AND MACHINE COMPANY

2931 N. PULASKI ROAD / CHICAGO 41, ILLINOIS / Phone: PAlisade 5-1610

CINCINNAT gives you positive correctio

Gage-Line unit mounted on the footstock housing of a CINCINNATI FILMATIC 14" x 36" Heavy Duty Universal Grinding Machine. MARE-UNE

CINCINNATI°

CENTERTYPE GRINDING MACHINES . CENTERLES MICRO-CENTRIC GRINDING MACHINES . CHUCKIN

GAGE-LINE UNIT

of taper ... quickly; accurately

Taper is an elusive factor in centertype grinding. The cut and try method of eliminating or correcting it is expensive and quite often wasteful of nearly-finished parts. Gage-Line is Cincinnati's answer to precise taper control. It is an electronic taper correcting unit which eliminates trial and error with amazing sureness and accuracy. There's the way it works. A gage head is mounted on each end of the table, and an electronic control unit is mounted on the right-hand end of the machine. When the swivel table is adjusted, the control unit

electronically translates the signal from each gage head to a graduated meter, reading direct for amount of movement and length of workpiece.

Gage-Line unit is another forward step by Cincinnati in their continuing efforts to improve the accuracy and reduce the cost of precision centertype grinding. Gage-Line is available for all cincinnati filmatic 4" to 14"L Plain Grinding Machines and 10" to 18" Universal Grinding Machines having between-center lengths up to 48" inclusive. Want more information? Ask for brochure G-687.




Gage-Line unit mounted on the bed of a CINCINNATI FILMATIC $18'' \times 48''$ Universal Grinding Machine. Detailed information on these fine precision grinders in catalog No. G-663-2.



RINDING MACHINES • ROLL GRINDING MACHINES RINDERS • CENTERLESS LAPPING MACHINES GRINDING MACHINE DIVISION
The Cincinnati Milling Machine Co.
Cincinnati 9, Ohio

A MOUNTAIN & POWER



POWER FOR BIG JOBS — Here a Rodgers 600-Ton Inclined Forcing Press is forcing a large gear and sprocket from a mine machine shaft.

or a touch

The heavy machines and equipment used in the great iron mining industry present a variety of problems when repair or maintenance is necessary. For this work the accurately controlled action of Rodgers Hydraulic Forcing Presses is a real time and work saver.

A Rodgers Forcing Press puts a

A Rodgers Forcing Press puts a mountain of power at your fingertips to force wheels, sprockets or gears from their shafts and for straightening, assembling, swedging or upsetting jobs. Operators also use the versatility, speed, power and positive control of a Rodgers Forcing Press to efficiently perform small pressing and forcing jobs with just a touch of pressure—tasks once done only on vertical shop presses!

you get both with RODGERS FORCING PRESSES

Rodgers vertical, horizontal and inclined forcing presses offer capacities from 100 to 600 tons... up to 9 feet between tension bars... up to 16 feet between ram and abutment... single or double acting cylinders with 13 or 26-inch ram travel (72-inch travel available)... electrically powered hydraulic pumps with selective, positive pressure adjustment and remote control... removable press cylinders that

can be used in special jacking or pulling jobs...and many more features that assure you of dependable, long life operation — all fully described in Rodgers Catalog Number 315A.

Write for it today!



LIGHT TOUCH FOR SMALL JOBS—This Rodgers 300-Ton Inclined Forcing Press is used on small as well as large equipment repairs. Here, a pin is being pressed out of a tractor idler support bracket.

7453 WALKER STREET

MINNEAPOLIS 26, MINNESOTA

Rodgers Hydraulic Inc.



EMBOSSING












OWN ACTING

C PRAME PRESSE

HYDRAUUC CKING UNITS



Your need demanded it!

VERSIZE

Flat Ground Die Stock

SELECT B FM A-2 Type Air Hardening

OVERSIZE: .010" to .012" on thickness

BADGER 0-1 Type Oil Hardening

OVERSIZE: 014" to .016" on 1/4" thickness and above (Standard tolerances on 1564" thickness and under)

Made by LATROBE



to cut

costsi

Fully-uniform

DESEGATIZED®

SELECT B FM

(A-2 Type, Air Hardening)

BADGER

(0-1 Type, Oil Hardening)

Cuts die costs . . . speeds die making!

Latrobe's OVERSIZE Flat Ground Die Stock facilitates die production by permitting design and layout to nominal dimensions-with "extra thousandths" for grinding to nominal size after heat treatment.

Latrobe's OVERSIZE Flat Ground Stock is. furnished with precision-ground surfaces in 18 and 36 inch lengths. Grade is identified over entire length of bar. Over 750 sizes of O-1 type Badger and 125 sizes of A-2 type Select B FM!

Call Latrobe today-

Or, send for Bulletin P-8-9-243

LATROBE STEEL COMPANY

MAIN OFFICE and PLANT: LATROBE, PENNSYLVANIA

BRANCH OFFICES and WAREHOUSES: BOSTON . BUFFALO . CHICAGO . CLEVELAND . DAYTON

DETROIT . HARTFORD . INDIANAPOLIS . LOS ANGELES

MIAMI . MILWAUKEE . NEW YORK . PHILADELPHIA


PITTSBURGH . TOLEDO . SAN LEANDRO

UNBELIEVABLE VALUES!...

IMPERIAL RADIAL DRILLS

	Model	Col. Diam. Inches	Arm	Base Price
	L-26	71/2	26"	\$1995.
	L-21/2	81/2	21/2'	\$2085.
	L-3	81/4	3'	\$2195.
THE PARTY OF THE P	M-3PE	10	3'	\$3995.
TT "	M-4PE	12 %	4'	\$4985.
3	M-5PE	14	5'	\$6295.
	M-6PE	14	6'	\$6985.
		AGENTS \	WANTED	

IMPERIAL WIEGER Guillotine **Shears**



- ALL STEEL CONSTRUCTION SINGLE STROKE CONTROL
 - - · PERMANENT ACCURACY

8" gaps on all models. Cuts thin and heavy gauge accurately.

Length	Capacity	Price
6'	10 gauge	\$3595.
8'	12 gauge	\$4395.
10'	12 gauge	\$5195.
6'	3/16 inch	\$5190.
8'	10 gauge	\$5495.
10'	10 gauge	\$5795.
6'	⅓₂ inch	\$6190.
8'	3/16 inch	\$6495.
10'	% inch	\$6795.

AARON MACHINERY CO., Inc.

DEPT. B 45 CROSBY ST., N. Y. 12 . WA 5-8300

BRANCHES AT:

BUFFALO, N. Y. RICHMOND, CA MINEOLA, N. Y. LOS ANGELES. HOUSTON, TEXAS TULSA, OKLAHO SEE OTHER AD PAGE - 24



CUT-OFF BLADES

CAST-TO-FORM

TIPPED TOOLS

"Where and How to use TANTUNG" — Facts about all types of TANTUNG tools . . . how to grind and

braze . . . examples of production cost-savings,

etc. Ask for Booklet No. 573. V-R TANTUNG bridges the gap between maximum cutting speeds of high speed steel and practical minumum speeds of cemented carbides . . . and it's easy to grind with aluminum oxide wheels.

High red-hardness; high transverse rupture strength; low coefficient of friction and high shock resistance are a few of the characteristics which make TANTUNG cast alloy the ideal tool material for intermediate cutting speeds.

Ask your V-R representative to show you how TANTUNG can cut costs on many of your machining operations.






PRIME MANUFACTURERS OF REFRACTORY METALS ENGINEERED FOR THE JOB

838 Market Street . Waukegan, Illinois





based on a setup used to cut a slot in a plastic key case, but the basic idea can be adapted to perform a host of operations in metal fabrication.

It's a simple, inexpensive device. A Bellows Rotary Feed Table, mounted vertically, feeds the part to the tool attached to the piston rod of the Bellows Air Motor. The two are electrically interlocked. Bellows Rotary Feed Tables can be provided to index almost any number of positions. The unit can be equipped with a "timed dwell"; additional work stations can be set up to perform other operations on the same part: automatic feeding or ejecting devices could be installed. Whatever you make, however vou make it. Bellows "Controlled-

Air-Power" Devices can help you make it at lower cost.

THIS SPOT-A-MATION IDEA FILE IS YOURS ON REQUEST

Complete wiring diagrams, installation data and equipment list on the "ferris-wheel" shown, and on a score of other applications where Bellows air-powered work units are used to convert existing equipment to lower cost operation. Write for it today. Address: Dept. MTB-459, The Bellows Co., Akron 9, Ohio. 1341-B


OTHER INDUSTRIAL DIVISIONS OF IBEC: Sinclair-Collins Valve Co... Valvair, Akron, Ohio Anderson Co., Cleveland, Ohio

The Bellows Co.

AKRON 9, OHIO

NEW! WARNER & SPINDLE

...enables profitable small-lot production of even your most complex and precision demanding bar jobs on a fast, automatic basis





Now, the shop-proven, cost-cutting features which have made Warner & Swasey Automatic Chuckers so outstanding in their field are available in a new Single Spindle Bar Automatic. Most important among the profit-producing features of this new Warner & Swasey 2 AB are:

- FASTER SETUPS—With no cams to change, timeconsuming setup procedures, usually encountered with automatic bar machines, are eliminated. Even your smallest lot bar jobs can now be produced on an automatic basis economically.
- GREATER ACCURACY—only two wide—and widelyspaced—bearing surfaces support the turret. Thus, cumulative tolerance problems in conventional "multi-

ple bearing" turret location designs are eliminated.

- EASIER TOOLING FOR COMPLEX WORK Flexibility and accessibility of the 2 AB's cross slides and pentagon turret enable the use of a wide variety of machining methods. One operation usually handles even the most complex workpieces.
- POWER FOR TOMORROW'S JOBS-TODAY
 The 2AB's 25 horsepower, reversible motor more than
 meets today's rugged metal removing requirements and,
 coupled with a wide range of spindle speeds, permits
 the efficient application of the latest cutting tool materials.
- "FREE" CUT-OFF TIME—An independently-operated cut-off slide allows full utilization of both front and rear cross slides. The cut-off cycle may be started during

SWASEY 2 AB SINGLE AUTOMATIC BAR MACHINE



any one of the pentagon turret stations. Thus cut-off can be progressing during subsequent machining providing a cut-off cycle which is virtually "free".

■ AUTOMATIC RESTOCKING INDICATOR—This ingenious device in the hydraulic bar feed mechanism automatically stops the 2 AB and lights an indicator light on the operator's control panel before the bar being machined runs out—prevents tool damage from improperly-gripped stock.

Why not call your nearest Warner & Swasey Field Representative and get the complete story on the new 2 AB. It can help increase both production and overall profits so important in today's highly competitive picture. WARNER
SWASEY
Cleveland
PRECISION
MACHINERY
SINCE 1880

NO MATTER WHICH WAY YOU TURN
... WARNER & SWASEY CUTS COSTS

Symbols of Service

to all metal-working industries

The Morse "house emblem" and the NIDA seal are double warranty of the best you can get in quality and service.

For Morse-Franchised Distributors are like the tools they sell... tested and proven on their jobs... men of experience and responsibility who know how to get you top value for every dollar you spend on cutting tools.

So call him in today . . . your Morse-Franchised Distributor. You'll find him more and more of a business asset, the longer you do business with him.

MORSE TWIST DRILL & MACHINE COMPANY NEW BEDFORD, MASSACHUSETTS

WAREHOUSES IN NEW YORK CHICAGO DETROIT DALLAS SAN FRANCISCO

A Direct of VAN NORMAN INDUSTRIES. INC



Morse CUTTING TOOLS





Now

NING with the

horizontal optical-jig-borer offers you increased ACCURACY VERSATILITY PRODUCTIVITY

Made in Switzerland Measurement in inches



 Projected optical setting—direct reading to .00005" for linear motions and I sec. of arc for built-in rotary table. Linear optics provided with adjustable zero reference

· Simplified controls functionally arranged for greater operating speed and efficiency

3" diameter boring spindle
Increased capacity: table size 39% x 32"; 29% cross travel; 23% longitudinal travel; 25% vertical travel

Hydraulic feeds and infinitely variable spindle speeds

Rear support optional

MBI has engineers available for consultation, guarantees service by factory trained staff, and stocks spare parts in New York.

> Demonstrations upon request at our conveniently located demonstration centers.

M. B. I. EXPORT & IMPORT LTD.



A DIVISION OF MACHINERY BUILDERS, INC. 475 Grand Concourse, Bronx 51, N. Y.

"Over 25 years' experience in designing and building machinery."

22½ hours per day... 7 days a week...



and no maintenance problems

"We have encountered no maintenance problems," says a spokesman for a major New York appliance plant which has operated these 2 BAKER AUTOMATIC BAR MACHINES continuously since installation 6 months ago.

Change-over time has been cut from 16 hours to 4 hours, A separate washing step and hand burring operation have also been eliminated. Baker electronic speed control is another reason "... why we have ordered the third machine for use here ..." says this Baker customer. For additional details, write to Baker Brothers, INC., Dept. TB-459, 1000 Post Street, Toledo 10, Ohio.



Each BAKER cuts, threads and burrs 720 Heater Motor Shafts per hour, eliminating the need for manual finishing steps.

BAKER

AUTOMATIC Bar machines

STANDARD AND SPECIAL DRILLING AND TAPPING MACHINES . COMPRESSION MOLDING MACHINES



Discover The Broad, New Applications of TIME-SAVING, MODERN ABRASIVES!

Brightboy, the only complete stock line of rubberbonded abrasives, will perform many types of work previously unrelated to abrasive uses. Replaces many older, costlier metal working methods. Gives you a broad, new, refreshing concept of abrasive applications! Fast, prompt delivery from distributors on factory stock.

Brightboy is a different finishing medium, which burrs, cleans, finishes, polishes, in a single-step, time-saving operation. Its unique working action results from rubber and Aluminum Oxide or Silicon Carbide

abrasive grains, working simultaneously. You have wide choice of stock grains and textures, grades extra fine to extra coarse, in soft, firm and tough rubber binders, JOB-MATCHED to your work. No fuss. No muss. Wheels, sticks, rods and blocks for machine and manual operations.

WRITE us NOW for:

- . SAMPLE BRIGHTBOY HAND TABLET
- CATALOG LISTING GRAINS, TEXTURES, MACHINE SPEEDS
- NEW METHOD RECOMMENDATIONS and name of nearest Brightboy distributor

TIME SAVING FEATURES

Works to close tolerances
Can be shaped to contour
Produces conventional and
special finishes and patterns,
frequently the final polish
No before-use preparation or dressing
No skilled labor required

GENERAL USES

Removing light digs, tool and heat marks Cleaning welded and soldered joints Burring and finishing castings, stampings, machined and molded parts Maintenance of tools and machinery

BRIGHTBOY INDUSTRIAL DIVISION WELDON ROBERTS RUBBER CO. 95 North 13th Street Newark 7, N.J.

America's Pioneer Manufacturer of Rubber-Bonded Abrasives





INGENIOUS

NEW... UNIVERSAL RER DEBURRING TOOL



with spring loaded retractable blade eliminates chatter gives precision-cut edge or chamfer at high speed



The cutting action of Model 955 Universal 8.8.R chatterless Deburring Tool (on the left) is effected by spring tension against the blade. On Model 956, right, the spring tension is against the bady. This is adjustable to regulate the deepth of cut. The blade is free-flooting to allow self-olignment and uniform stock removals.



The new Universal R&R Tool makes a hencyl herizantial deburrer when used with a perturble drill held in a vise. With proper adjustment, the R&R Deburring Tool is CMATTERESS. A new design cliews the bearing angle of the tool bady oned the blade to be in continuous contact with the work piece at all times.



R&R Deburring Tool used in electric drill as a portable unit for heavy plote or other objects too heavy to handle. Blades of the R&R Deburring Tool are replaceable at naminal cost from stock. They are made of high speed steel, precision hardened and ground to close tolerances for interchangeability.



Used in any standard drill press at the high operatling speeds recommended by the molers of high speed steels, the R&B Deburring Tool performs most efficiently. High operating speeds mean more production, lower costs. Both tool is made in a full range of sizes to 1½" diameter.

UNIVERSAL ENGINEERING COMPANY

209

Use postpaid card. Circle No. 218

FRANKENMUTH 10,


Exceptional Values! Available from stock! PRECISION MILLING MACHINES

ABENE
VERTICAL HORIZONTAL
MILLING MACHINE
\$3990.

THOUSANDS SOLD TO SATISFIED CUSTOMERS!

PEDERSEN HORIZONTAL, VERTICAL

and combination
MILLING MACHINES




75x16

VPF-4



LIBERAL TERMS . RENTALS

WESTBURY Universal Dial-Type Horizontal Milling Machines




WESTBURY
I-S
VERTICAL TURRET
MILLING MACHINE
\$15.95
Incl. Motor
& Controls

Via H.P. 9"x32"
Table
Available With:
9"x42" Table
\$95. extra
Coulant
\$155. extra

AARON MACHINERY CO., Inc.
DEPT. B 45 CROSBY ST., N. Y. 12 . WA 5-8300

BRANCHES AT:
BUFFALO, N. Y. RICHMOND, CAL.
MINEOLA, N. Y. LOS ANGELES, CAL
HOUSTON, TEXAS TULSA, OKLAHOMA

SEE OTHER AD PAGE - 12



BOYAR-SCHULTZ BIR SURFACE GRINDERS


Available in Hydraulic and Hand Feed models.

These machine tools are of the most advance design, fully proved and enthusiastically endorsed by users who must have accuracy as well as production performance.

Exclusive features include heavy duty precision spindle; vertical column assembly supported by horizontal cylindrical ways; closely grained nickel alloy table with longitudinal ways of hardened and ground tool steel; vertical feed assembly with precision ground worm gear perfectly fitted to bronze gear for easy operation.

Hydraulic operation is accomplished by controls A and B above. These controls automatically disengage longically disengage longically

tudinal and cross feed hand wheels.





Precision screw on vertical feed assembly turns through a perfectly fitted steel worm and bronze gear, operating in grease packed, sealed gear box. Unique column assembly combines vertical and cross feed travel. Sturdy vertical column has oversize bearing surfaces. Hardened and ground cylindrical WOVS provide occurate long wearing surface for cross feed travel.

Write, wire or call.
We'll be glad to
SHOW you what this
fine grinder will do.

BOYAR-SCHULTZ

2008 So. 25th Ave.

Broadview, III.

Now Boice-Crane Brings You

AMAZING DRILL PRESS VALUES!

An 18" Which Rivals a 20" in Capacity and H.P. at the Price of a 17"

24" Hand or Power Feed Models Offering Equally Sensational Value

You buy Scotch from Scotland, optical goods from Germany, perfume from France, lace from Ireland, and woolens from England because you consider them superior.

Now get the fine unhurried workmanship of Swedish machinery, in drill presses made especially for Boice-Crane, U.S.A.

FIRST IN MEDIUM SIZES WITH POWERFUL GEAR-DRIVES AND GEAR SHIFT SPEED SELECTION



NO UNHANDY GUARDS . NO PULLEYS OR BELTS . NO BELT CHANGING

Instant speed selection is by gear shift on 4-speed models, supplemented by 2-speed motors on 8-speed models. Reversing switch for tapping is standard on 24-inch, optional on 18-inch. Feed speeds (power feed only .004" and .007".



EXCLUSIVE & NEW! POSITIVE, MULTIPLE AUTOMATIC DEPTH CONTROL

provides 3 stops for hand-feed step or interrupted stroke drilling and counterboring.

SPINDLE - QUILL - COLUMN Stocky, oversized and super accurate spindle centains No. 3 MT socket WITHIN IT and BETWEEN bearings, not just a No. 2 pretruding BELOW the bottom bearings. All bearings SRF, the bettum most a relier type for heavier thrust and radial loads. Columns 4" dia. on 18": 4-5/16" on 24" hand feed; 5" on 24" power feed model. All quills 2-3/8". Head raiser and table raiser are standard.


UNBELIEVABLY LOW PRICES! 18-inch, 1" cap. (cast iron) complete Just \$369.50! with motor.

*3-phase with plain table.

24-inch, $11/4^{\prime\prime}$ cap. (cast iron) Power Feed — 11/2 H.P. 2-speed Motor, Only 795.00** (As shown ready to run)

**\$575.00 hand feed only.

FULLY GUARANTEED—Inspection ticket certifies in .000's and .000's the built in accuracy and critical alignments.



POSITIVE ALL-GEAR DRIVE—MOI POWER THAN V-BELTS. Fully enclor precision steel and fiber gears. 9 to ball bearings. I H.P. geared drive mes I H.P. at ALL speeds. Contrast with ' terrific power lesses of V-belts and shear at the low spindle speeds best suited large twist drills.

REPLACEMENT PARTS STOCK!
TO MEET ALL FUTURE DEMAND

Write Today for Additional Information.

BOICE-CRANE COMPAN'

936 W. Central Avenue

Use postpaid card. Circle No. 221

Toledo 6, Oh



TOOLMAKERS OVERARM

Here's the way to add new "firepower" to toolroom milling operations! Install in your toolroom a GREAVES MILL equipped with this new Toolmakers Overarm.

You'll discover new versatility for milling intricate jig and fixture work, for keywaying, slotting and angular milling. Two graduated swivels permit mounting the spindle head in almost any angle for milling, drilling, spot facing and related operations.

Powered by an independent 2 HP motor, the unit is driven through helical gears. Eight speeds may be selected with convenient controls operating speed change clutches. A hand-fed quill attachment provides 4° tool travel to the spindle. Arbor support fits overarm, permits arbor type milling without changing overarm.

Write for Complete Specifications and Prices

GREAVES MACHINE TOOL DIVISION
J. A. FAY & EGAN COMPANY
2600 Eastern Avenue, Cincinnati 2, Ohio

- Swivels permit any angular setting of spindle head.
- 2 HP Independent motor drive.
- 8 speeds from 175
 to 1750 RPM.
- Quill has 4" hand feed.
- Spindle equipped with No. 50 N. S. taper; reduced to No. 2 Morse taper when Quill Attachment is used.
- Geors run in oil bath,
- Full vision oil level gauge.
- RACK FEED. The overarm is equipped with rack feed for positioning over work.

Manufacturers of GREAVES MILLS "the MOST Mill for the LEAST Maney!"





This 24-ft. boring mill is facing a disc of 300 stainless . . . a difficult machining operation . . . but this 3-man team quickly found the answer.

This 3-Man Team makes expensive machines pay off

Every time some new alloy must be machined, new problems arise as to the best tool, grade of carbide, feeds, speeds and depth of cut to use. Modern mills and machines are too costly to permit a lot of experimenting with resultant downtime.

The only sure and economical way is by pooling the know-how of a 3-man "tooling team." The Tool Engineer knows the job requirements; the Machine Operator contributes his machining skill; and your Kennametal Carbide Engineer provides information on the latest developments in carbide tooling.

Such a 3-man team can best determine the proper tools required for the job . . . then fill those requirements from the extensive line of Kennametal* tooling. Spearheaded by the Kendex*

(patented) line of "throw-away" insert tooling with more than 50 standard styles, plus many adaptations for special needs, Kennametal offers a selection that will provide the right tool for every job . . . for every shop, whether large or small.

Call in your Kennametal Carbide Engineer today to help you get the best tooling for every machine and material . . . applying Kennametal and helping to solve tough machining problems is his full-time job. Or write Kennametal Inc., Latrobe, Pennsylvania.

"Trademark"





Aram Kalenian, writer of the letter reproduced above, and president of Vee-Arc Corp., is shown with Raiph Rastad, superintendent, and Paul Daoust, operator, examining a chucking job run on their 3" Model AB Cleveland Dialmatic.

The parts shown (some are blanked out, others are machined complete) are typical of those produced on the Model AB 3" Cleveland Single Spindle Automatic at the Vee-Arc Corp. Diameters of these parts range from \%" to 4\%", and materials include aluminum, type 303 stainless, and tough, oold hobbing steel.

By making use of the Cleveland's chucking attachment, which is quickly substituted for the bar stock feed assembly, the part shown at right is machined from blanks of 4½" round aluminum bar stock in 98 seconds cycle time.

What the Cleveland Dialmatic does for Vee-Arc, it can do for you! Choose Clevelands to increase the production efficiency in your plant.

THE CLEVELAND AUTOMATIC MACHINE COMPANY

4930 Beech Street Cincinnati 12, Ohio SALES OFFICES: CHICAGO CLEVELAND - DETROIT

HARTFORD . S. ORANGE

Manufacturers of a Complete Line of Single Spindle Automatic Screw Machines and High Pressure Hydraulic Die Costing Machines

Use postpoid card. Circle No. 224

FOR BIG, WEAVY PRECISION SPINDLES

that produce BIG savings in production cost

SPECIFY POPE



POPE P-18670 Heavy Duty, High Speed Milling Spindle, 4 ft. long, 10 in. dia.; weight about 1000 lbs.



POPE P-18842 Deep Hole Internal Grinding Spindle, 10 HP, 7 ft. long, 12 in. dia. barrel; weight 4000 lbs.



POPE P-5794B Motorized Deep Hole Grinding Spindle, 10 HP, 36 in. long, 6 in. dia. barrel, for use in horizontal or vertical position on boring mills or planers; weight about 800 lbs.



POPE P-18844 Vertical Bearing Grinder Spindle, 20 HP, 6 ft. long, 12 in. dia. barrel; weight approx. 4000 lbs.



POPE P-1098 Heavy Dury Internal and External Grinding Spindle, 50 HP, for wheel of 30 in. dia. and 12 in. width; weight approx. 6000 lbs.



POPE P-10009E Motorized Deep Hole Grinding Spindle, 5 HP, 36 in. long, 5 in. dia. barrel; weight 600 lbs.



POPE P-1076 Cylindrical Grinding Spindle, designed for crush dressing and form grinding; 5 ft. long, 10 in. dia. barrel, for 24 in. dia.; 4 in. wide wheel; weight about 1250 lbs.



POPE P-A1 Deep Hole, Rum Type Grinding Spindle attached to boring machine, 10 HP, 10 ft. long, 10 in. dia. barrel; weight 2000 lbs. (For purposes of comparison, a Pope P-32 6" x 18" Surface Grinder Spindle is shown in the foreground.)

Send us your specifications and get prompt quotations on the one best Spindle for your work, out of the 20,000 different Precision Spindles that bear the name "POPE".

No. 125



ENGINEERS AND BUILDS STANDARD AND SPECIAL PRECISION ANTI-FRICTION BEARING SPINDLES FOR EVERY PURPOSE

POPE MACHINERY CORPORATION . 261 RIVER STREET . HAVERHILL, MASS.

Established 1920

Save Hours in tool rooms and die shops with CONTOUR SAWING AND FILING

You can save real time and money in the production of parts for jigs and fixtures, dies, gages, templates and special machine production by using an Oliver of Adrian contour sawing and filing machine.

The Oliver is so simple to operate that all sawing, filing and lapping can be handled by an ordinary mechanic—saving a skilled die maker's costly time. Parts can be shaped to dimension faster, more accurately with no hand filing or semi-finishing operations. Available in five types — bench or pedestal. Write today.

OLIVER OF ADRIAN OLIVER INSTRUMENT COMPANY 1408 E. Maumee St. • Adrian, Michigan





SOLID POWER

of a Remington drill

Chips fly when Remington power tools bite into steel. They're tough to wear out, too, because of the solid way Remington builds them. Remington manufactures a broad and versatile line. In drills alone, choose from 21 electric-powered or 11 air-powered models. Each is serviced for parts or repairs from a nationwide network of Remington Service Stations. It makes sense any way you look at it to specify Remington for all your portable power tool needs. Write for free descriptive catalogs—there's no obligation.

CHOOSE THE POWER MOST
EFFICIENT FOR YOU. REMINGTON
POWER TOOLS ARE AVAILABLE IN
AIR • ELECTRIC • GASOLINE
AND POWDER-ACTUATED
MODELS

Remington

Remington Arms Company, Inc., Bridgeport 2, Conn. IN CANADA: Remington Arms of Canada, Limited, 36 Queen Elizabeth Blvd., Toronto 18, Ont.



CIMCOOL PRESENTS . .

CIMPERIAL

Here is what we believe to be the most advanced, the most effective cutting fluid in the history of the industry.

CIMPERIAL is an entirely new chemical concentrate especially designed for heavy duty applications. It is the only water-miscible fluid capable of performing the tough, low clearance, low speed operations previously limited to cutting oils.

CIMPERIAL is a chemical solution—not an emulsion—which effectively covers 95% of all metal cutting jobs.

CIMPERIAL increases tool life because it defeats both heat and pressure. Forming a chemical solution in water, CIMPERIAL rapidly dissipates heat. Won't "hold" the heat as an oil will. CIMPERIAL contains newly discovered EP (Extreme Pressure) additives which give you more cutting action with less force. Result: production equal to, or better than, oil; and working conditions vastly improved.

Note these important advantages:

CIMPERIAL lasts longer. It won't turn rancid: it contains no food for bacteria and has a remarkable bactericide to control those bacteria that do enter the mix from outside sources. No more Monday morning odor. Less frequent coolant changes mean lower costs, less down time for machines. CIMPERIAL is productive and clean. The new EP chemicals reduce the cutting forces and friction on the tool: in one case CIMPERIAL has already increased tool life 70%. It also has high film strength for lubricity characteristics better than oil. And there is no smoke or vapor around your machines.

You get two types of chemical rust inhibitors in CIMPERIAL ... which form both polar and passivating films over metal surfaces. This gives you, even at lean dilutions, double protection against corrosion.



FOR 100% OF ALL METAL CUTTING JOBS

Production-proved products of The Cincinneti Milling Machine Co-

CIMPERIAL—newest in the famous, industry-proven line of CIMCOOL. Cutting Fluids! CIMCOOL 52 Concentrate—The pink fluid which covers 85% of all metal cutting jobs. CIMPLUS—The transparent grinding fluid which provides exceptional rust control. CIMCUT Concentrates (AA, NC, SS)—For every job requiring an oil-base cutting fluid. ALSO—CIMCOOL Taipping Compound—CIMCOOL Bactericide—CIMCOOL Machine Cleener.

For full information on great new CIMPERIAL and the complete family of CIMCOOL Cutting Fluids, call your CIMCOOL Distributor today. Or contact Cincinnati Milling Products Division. Cincinnati 9, Ohio.

"Trade Mark Reg. U. S. Pat. Off.

A DC's

of SHORT RUN SHEET METAL PRODUCTION



A TEMPLATE MAKING
with the WIEDEMANN COORDINATOR

B TEMPLATE INSPECTION
WITH the WIEDEMANN INSPECTOR



SAVE 60%-90% ON YOUR WORK

Send typical drawings of your work, and let us show you how the WIEDEMANN METHOD can cut your production costs 60% to 90%.

From producing precision templates . . . to fast accurate hole inspection . . . to high speed production of panels, chassis and other pierced parts, you can do the entire job in 60% to 90% less time with the Wiedemann Team—Coordinator, Inspector and Turret Punch Press.

Layout and setup are completely eliminated. Template holes are located on the Coordinator to X and Y dimensions using optical scanners, and drilled in rapid sequence. To assure optimum accuracy, template hole locations can be checked quickly on the Wiedemann Inspector. Then, working to the template, parts are pierced at amazing speed—30 to 100 holes a minute—with a Wiedemann Turret Punch Press. Complete flexibility of hole size, shape and location is assured. Even extensive engineering changes can be made on-the-spot at minimum cost.

Job shops and manufacturers alike are discovering the profitable difference the Wiedemann Team makes. Write today for full information.



HIGH SPEED PIERCING
with the WIEDEMANN RA-41P
TURRET PUNCH PRESS

WIEDEMANN MACHINE COMPANY TURRET PUNCH PRESSES

DEPT. MT-4 . GULPH ROAD . KING OF PRUSSIA, PA.

from your Heller distributor. the IMPROVED AISI-01 flat ground die steel Combining the MOST WANTED ANALYSIS ... with the MOST NEEDED FEATURES!

 EASY MACHINABILITY! The special spheroidized annealing of Heller's Die Steel assures you of the finest grain structure, the easiest machinability, and the most uniform hardening.

 SMOOTHER PHNISH Surface finished to 25-35 micro inches, with all decarburization and surface defects removed, the new Heller "01" is ready for scribing, shaping and heat treating on arrival.

3. COST CUTTING CONVENIENCE! The wide range of standard stock sizes locally available allow you to avoid the hidden costs of machining, grinding and

cutting to size. No interruption of your regular work load, all you do is call your Heller distributor.

4. BETTER PACKAGNED All sizes of this improved "01" are individually wrapped in protective packages. Dimensions you can trust and heat-treating directions anybody can follow are printed on every package!


YOU CAN EASILY SELL NEW HELLER "01" by telling big users of flat ground die steel that you can supply the analysis they prefer with those outstanding features. Once they try it, they'll always buy it.

HELLER TOOL CO.



America's Oldest File Manufacturer
NEWCOMERSTOWN, OHIO
Subsidiary of Simonds Saw and Steel Co.

Branch Offices and Warehouses Boston • Newark, N. J. • Detroit • Chicago • Shreveport • Los Angeles • San Francisco • Partland, Ore



Typical Cincinnati® Shears: blg series 15012, capacity 1½", 12'; small series 1004, capacity 3/6", 4'; in between series 1810, capacity 3/4", 10'.



All steel, interlocked construction no welds used as load supports



Hydraulic holddowns exert tons of pressure, insure accuracy



Non-float inclined ram maintains extremely accurate knife clearance




Front controlled power ba gage is standard, accurate



small

or in between



Cincinnati[®] Shears
give you every advantage

Simple operation, micrometer accuracy, cost-cutting speed, all-steel construction, and versatility—these are the advantages which make Cincinnati Shears earn their way in your plant.

And, whether you're shearing steel or plastics, nonferrous metals or asbestos, wire mesh, clad metals, or even radioactive material, the Cincinnati Shear line gives you a range of choices to fit your own requirements. Cincinnati Shears are in service cutting all of these materials.

Cincinnati ruggedness enables you to use one knife

clearance for all thicknesses up to machine capacity.

Power operated back gages which are standard equipment, reduce non-productive time. Hydraulic holddowns provide tons of pressure, insure accuracy. The inclined ram permits the economy of four-edged knives, keeps work from binding between back gage and lower knife.

Since gap frames are standard, you can do notching, slitting or shearing work longer than the machine on any Cincinnati[®] Shear to the limit of its gap.

Be sure to get the full Cincinnati story before you buy your next shear. Write Dept. H for Catalog S-7R.



Cincinnati 11, Ohio, U.S.A.

Shapers / Shears / Press Brakes

THE CINCINNATI
SHAPER co.



MANHATTAN MOLDISCS CUT FASTER...LAST LONGER

Manhattan Moldiscs are made in types to meet specific job requirements for use with mild steels, stainless alloys, aluminum or copper. Tests prove they're the most economical portable wheels you can use on right angle grinders . . . smoothing weldments, removing burrs, beveling edges. Manhattan Moldiscs cut cleanly and freely on the toughest roughing and finishing—without loading or glazing. They're safer to use, too, because they're light in weight, easy to handle . . . and reinforced with special super-strength synthetic fabric for greater safety. Manhattan Moldiscs do a better grinding job, and they last longer!

Ask a Manhattan abrasive wheel engineer to demonstrate the advantages of Manhattan Moldiscs...available in a wide range of types from harder, stiff bonds for roughing—to resilient, flexible bonds for fine finishing.

To get "More Use per Dollar" also on other grinding or cutting jobs . . . specify Manhattan custom made, high speed, heavy duty abrasive wheels.

- REINFORCED FOR
 GREATER SAFETY
- WILL NOT LOAD
 OR GLAZE
- LIGHTWEIGHT,
 EASY TO CONTROL
- SPECIAL BONDS FOR ROUGHING AND FINISHING

"More Use Per Dollar"



WRITE TO THE ABRASIVE WHEEL DEPARTMENT

MANHATTAN RUBBER DIVISION - PASSAIC, NEW JERSEY RAYBESTOS - MANHATTAN, INC.

Belts * Hose * Roll Covering * Jank Linings * Industrial Rubber Specialties * Abrasive and Diamond Wheels * Brake Blocks and Linings * Clutch Focings * Asbestos Testiles * Mechanical Packings * Engineered Plastics * Sintered Metal Products * Industrial Adhesives * Laundry Pads and Covers * Bowling Balls

Another great
W-T "Light-Heavyweight"...

New

ALKER- URNER

17"

DRILL PRESS

Like the well-known 15" and 20" Walker-Turner drill presses, this new 17" unit is every inch a "Light-Heavyweight"—fast, accurate, dependable, and low in cost. It has the ruggedness and stamina to handle continuous heavy-duty production drilling—yet it's easy to move if you want to "take the tool to the work."

To suit a wide range of job requirements, this new big-capacity 17" drill press is available in 76 models—floor, bench or multiple spindle units with either hand or power feed. Also, it's a natural for building low-cost automated set-ups.

Your W-T distributor can show you the many outstanding features of this new "Light-Heavyweight." He's listed under "Tools" in the Yellow Pages.



FREE CATALOG

Write today for free catalog to Walker-Turner Division of Rockwell Manufacturing Co., Dept. WD-23,400 N. Lexington Ave., Pittsburgh 8, Pa.


WALKER-TURNER

another fine product by

ROCKWELL







Courtesy Combustion Engineering, Inc.

Combustion Engineering uses Gilberts for precision boring on atomic reactors

It takes an unusual boring mill (specifically, a Cincinnati Gilbert) to meet the specifications on this job:

- (a) diameters within .001°,
- (b) parallelism of center line of holes to center line of plate within .0001" per inch.
 - (c) parallelism of flat surfaces within .010",
 - (d) 32 R.M.S. surface finishes.

These are some of the machining requirements on this part for a fast breeder reactor built in the Chattanooga plant of Combustion Engineering, Inc., pioneer manufacturer in the nuclear field. They are typical of the quality of work assigned to this Cincinnati Gilbert table type horizontal boring mill. Automatic positioning makes work-handling fast and precise.

A number of other Gilbert boring mills are producing similar close-tolerance work for Combustion Engineering—proof that "those who buy Gilbert buy Gilbert again."


New Bulletin 1157 will show you why Gilbert boring mills do so many things so well.

The Cincinnati Gilbert Machine Tool Co 3352 Beekman Street, Cincinnati 23, Ohio.

those who buy GILBERT buy Gilbert again

SYNTRON Vertical Vibratory

PARTS FEEDERS



Orienting and feeding small parts to automatic assembly machines. SYNTRON Parts Feeders cut production cost in the metalworking field by efficient, accurate, dependable, controlled handling of small parts. They orient and feed parts of almost every size, shape and material at controlled rates to automatic equipment, as shown in the assembly application above.

SYNTRON Parts Feeders are easily adaptable to such operations by means of specially designed gravity feed tracks that deposit parts at a predetermined point.

Let SYNTRON help you reduce costs-

SYNTRON COMPANY

300 Lexington Avenue

Homer City, Penna.

NEW RANGE OF SIZES

DiaTest

HIGH PRECISION

SMALL BORE GAGE

- RANGE: .043" to 1.130"
- 4 SETS, fully equipped with rings and measuring heads.
- READINGS IN .0001"
- ACCURACY TO .00008"

DiaTest checks out-of-round, tapers, incomplete bores and all other variations. All sets overlap in size for complete range.

All parts available separately.

EACH SET complete with dial indicator.

NEW ACCESSORIES

• RIGHT ANGLE ATTACHMENT

Permits gaging without removing work-piece from under bore spindle.

- EXTENSION RODS may be used to length of 30" without loss of accuracy
- DEPTH ADJUSTER used in conjunction with extension rods, permits gaging to any defined depth.

Write today, or call NEwcastle 1-8888 for full information!

SET RANGE E-1 .057" - .170" E-2 .165" - .390" E-3 .372" - .828"

E-4

ALSO: 3 new measuring heads with range of .043" to .067". (Require special contact needles.)

.820"-1.130

.372"828"		
_		
١		

*For measuring to the bottom of closed holes. (Require special contact needles.)



FOSTER SUPPLIES CO.

6122 Milwaukee Ave., Dept. MTBB, Chicago 46, Illinois Use postpaid card. Circle No. 239



BUNTING BEARING ALUMINUM is the newest metal offered in bar form as a thoroughly good bearing material. Available in 138 sizes of 13" tubular and solid bars, Bunting Bearing Aluminum Bars are in stock now on shelves of Bunting distributors all over America.

If you are using a low priced bronze bar, this new Bunting Aluminum Bar will meet your need for high quality at low cost. Thus the high quality Bunting Precision Cast Bronze Bar is augmented by the high quality Bunting Aluminum Bar. providing dependable bearing materials covering the entire range of requirements.

Ask your local Bunting distributor or write for catalog and literature.

Other Products Available from your Bunting Distributor

866 steck sizes of Bunting Cast Bronze Bearings and 267 sizes of Bunting Cast Bronze 13" Bors. 667 sizes of Bunting Sintered Oil Filled Bronze Plain, Flange and Thrust Bearings and 84 sizes of Sintered Bronze 6½" Bars. Ask for Catalog 58.

343 sizes of Bunting Cast Branze Electric Mater Bearings for all meters. Ask for Cotalog 258.

BEARINGS, BUSHINGS AND SPECIAL PARTS OF CAST BRONZE OR SINTERED METALS. ALCOA! ALUMINUM BARS. THE BUNTING BRASS AND BRONZE COMPANY, TOLEDO 1, OHIO

Conversely 1958 by The Bunting Bross and Brosse Co., Toledo, Ohio



tributor is listed in the classified section of your telephone directory usually under Bars — Bronze and Bearings-Bronze.

ASK HIM



Procision ball bearing workhead SE mounted on compound Stide for setting outler to correct position when cirillading end editing flutes and radii. Other two workheads available

THE UNIVERSAL

RADIAL

CUTTER

GRINDING

FIXTURE

Radia: Grinding Attachment D combines with Unit 1A for sharpening end mills with source conical or ball ness shapes

UNIT IA. Universal Cuffer Grinding Fixture fits any universal too. or surface grinder



UNIT 24 Pedict Grinding Fixture for sharpening futer and mills with source eaties, or better has the index disc accordes for multi-fluty culture.



NEW FINE-ADJUSTMENT SLIDING SWIVEL GIVES SMOOTH, PRECISE INDI-CATOR SETTING.

Smooth, positive positioning of finest dial indicator in readily accomplished by the fine-adjustment Sirang Swive Fino precise positioning is accumately made by slight movement of convenient lever A



WRITE FOR

ROCHELEAU TOOL AND DIE CO.INC.

850 NO MAIN STREET SECURIORSED MASS



S

Motch & Merryweather's


Quality, Service and Availability add up to lower production costs

Triple Chip cut-off blades and slitting saws—characterized by a specially-developed tooth form—cut faster and last longer.

M&M's factory repair, resharpening and resegmenting service, the fastest in the industry, helps you avoid excessive inventories . . . minimizes costly downtime.

The complete line of M&M cutting tools, stocked by M&M distributors strategically located in every important industrial area, enables you to get immediate delivery on the tools you need, when you need them. Sawing and cutting tool specialists are always available to help you solve tough or unusual sawing problems.

Always specify Motch & Merryweather . . . first in quality . . . first in service . . . first in availability.






FREE — Send today for your copy of M&M's Circular Sawing Handbook, a pocket-sized guide to sawing operations.

THE MOTCH & MERRYWEATHER MACHINERY CO.

Cutting Tool Manufacturing Division

Cleveland 17, Ohio Use postpaid card. Circle No. 242



Precision ball bearing workhead 6B mounted on compound Slide for setting cutter to correct position when grinding end cutting flutes and radii. Other type workheads available. THE UNIVERSAL

RADIAL

CUTTER
GRINDING
FIXTURE

Radial Grinding Attachment D combines with Unit 1A for sharpening end mills with square, conical, or ball nose shapes.

> UNIT 1A. Universal Cutter Grinding Fixture fits any universal tool or surface grinder.



UNIT 4A. Radial Grinding Fixture for sharpening fluted end mills with square, conical, or ballnose mills. The index disc provides for multi-flute cutters.



900

NEW FINE-ADJUSTMENT SLIDING SWIVEL GIVES SMOOTH, PRECISE INDI-CATOR SETTING.

Smooth, positive positioning of finest dial indicator is readily accomplished by the fine-adjustment Sliding Swivel. Final precise positioning is accurately made by slight movement of convenient lever "A"



ROCHELEAU TOOL AND DIE CO.INC.

650 NO. MAIN STREET, LEOMINSTER, MASS.

WRITE FOR: SLIDING SWIVEL FOLDER



Motch & Merryweather's


Quality, Service and Availability add up to lower production costs

Triple Chip cut-off blades and slitting saws—characterized by a specially-developed tooth form—cut faster and last longer.

M&M's factory repair, resharpening and resegmenting service, the fastest in the industry, helps you avoid excessive inventories . . . minimizes costly downtime.

The complete line of M&M cutting tools, stocked by M&M distributors strategically located in every important industrial area, enables you to get immediate delivery on the tools you need, when you need them. Sawing and cutting tool specialists are always available to help you solve tough or unusual sawing problems.

Always specify Motch & Merryweather . . . first in quality . . . first in service . . . first in availability.






FREE — Send today for your copy of M&M's Circular Sawing Handbook, a pocket-sized guide to sawing operations.

THE MOTCH & MERRYWEATHER MACHINERY CO.

Cutting Tool Manufacturing Division

Cleveland 17, Ohio



get more production at lower cost with HANNIFIN "FD" PRESSES

A COMPLETELY NEW LINE OF HIGH-SPEED HYDRAULIC BENCH PRESSES

FAST DELIVERY—ALL THESE SIZES! 2, 3, 4, 5, 6, 8, 10 and 12 TONS

HEAVY-DUTY OPEN-GAP PRODUCTION PRESSES

Our quantity production gives you highest quality at lowest cost.

THEY HAVE "EVERYTHING"...

Dual Safety Hand Lever Controls
Dual Electric Push-Button Controls
Adjustable Stroke Control
Reverse on Pressure or Distance
Full Automatic Cycling
Hannifin High Speed Hydraulic Index Tables
Reciprocating Hydraulic Slide Feeds

USE THEM FOR ...

Assembly Operations
Riveting — Staking
Forming — Stamping
Trimming Die Castings
Trimming Plastics
Molding Semi-Conductors
Preforming — Compacting

MAY BE FLOOR MOUNTED-OPTIONAL, LOW-COST BASES AVAILABLE

Call in your nearby Hannifin man—he's a trained production analyst—to prove how you can do more at lower cost with Hannifin presses. Or, write for our new Bulletin 132A. It tells the whole story.

HANNIFIN COMPANY

529 South Wolf Road . Des Plaines, Illinois

A DIVISION OF PARKER-HANNIFIN CORPORATION .



IT'S GRATIFYING TO KNOW YOU MAKE THE BEST!

The man who makes Ace Drill Bushings is no Johnny-come-lately. He's not a novice. His bushings last a long, long time. That makes them cost you less.

He cares about quality. Some say it doesn't pay to build stuff too good . . . just get by . . . imply that engineers don't know the difference, but they're wrong. The man who makes Ace Drill Bushings doesn't buy that line,

He makes the best. Doesn't have to offer excuses or alibis. Doesn't have to dodge his customers; they're his friends. He saves them lots of money. He backs every claim with controlled quality . . . His Drill Bushings are consistent — every one the same — you can depend on them,

He sleeps well at night, too — every night — year after year. His customers are happy. He doesn't worry about competition — just goes right on making the very best drill bushings — rolling up bigger and bigger sales.

We're talking about ACE - the DRILL BUSHINGS that are superior. Try them. You'll see.

STOCKED, FOR IMMEDIATE DELIVERY BY LEADING TOOLING SPECIALISTS IN YOUR COMMUNITY.

ACE DRILL BUSHINGS

NEW JERSEY
611 McCarter Highway
EWARK 2 Mitchell 2-3006



CALIFORNIA
5407 Fountain Ave.
LOS ANGELES 29 HO 9-8253



MICHIGAN
10620 West Nine Mile Road
DETROIT 37 Lincoln 8-0777

JONES & LAMSON OPTICAL COMPARATORS

the man who needs

a new machine tool is



This is what you should demand in an Optical Comparator

Optical inspection and measuring equipment offers fast operation, extreme accuracy and tremendous versatility. When buying a comparator, be sure you get these benefits:

- Specifically designed projection lens system (not just an adaptation of other types of lenses).
 Ball and roll type supported measuring
- tables (they offer top speed and accuracy).

 3. Table assemblies so designed that simple changes can be made in your own plant.

(You can change a basic comparison machine over to one for universal measuring applications, at low cost.)

- Measuring facilities that offer direct readings without computation.
- (You save a lot of time, minimize human error, assure accuracy.)
- 5. Solid mechanical design throughout.

(You can't inspect anything very accurately if it's moving.)

Jones & Lamson Optical Comparators and Measuring Machines give you all these features, plus many more. They are explained in detail in our new catalog. Write for a copy today. Jones & Lamson Machine Company, 520 Clinton Street, Springfield, Vermont.



The you machining when you should be swaging?

There's no profit in chips, especially when you can save material, time, investment and labor costs by swaging. Rotary swaging has become the modern production method for reducing, pointing, tapering, sizing, assembling, bonding and forming ID contours with production tolerances to within \pm .001. Swaging improves physical characteristics, permits control of wall thickness, and eliminates finish grinding in many cases. Write today for the new Fenn Swaging Catalog. It may prove an eye-opener toward doing a better job on your product.



FENN MANUFACTURING CO.

903 FENN ROAD

NEWINGTON, CONN.

extra!

ALL ABOUT THE LATEST BENDING METHODS

Let Pedrick show you how the latest methods of bending pipe, tube and structural metal-on a job or production basis-can save you money.

For full information on Pedrick Production Benders, write Pedrick Tool AND MACHINE Co., 3640 N. Lawrence St., Phila. 40, Pa. Dept. 3,





FREE "PEDRICK LINE" BULLETIN. WRITE TODAY.

EDRICK production benders



Specify Ex-Cell-O standard power units and cut your machine tool lead time

Today's demand for increased productivity, lower per-unit cost, even on relatively short runs, is being met economically by automatic, single-purpose, high-production machines—consisting essentially of a plain base and one or more Ex-Cell-O Quill-Type Hydraulic Power Units.

These standard, self-contained Ex-Cell-O Hydraulic Power Units are now being

EX-CELL-O PRECISION PRODUCTS INCLUDE: MACHINE TOOLS • GRINDING AND BORING SPINDLES • CUTTING TOOLS • RAILROAD PINS AND BUSHINGS • DRILL JIG BUSHINGS • TORQUE ACTUATORS • THREAD AND GROOVE GAGES • GRANITE SURFACE PLATES • AIRCRAFT AND MISCELLANEOUS PRODUCTION PARTS • DAIRY EQUIPMENT

used for: drilling, counterboring, spot facing, reaming, as well as prime movers for milling equipment. Multiple operations may also be performed.

For the full story on the cost-saving advantages get in touch with your local Ex-Cell-O Representative. Or, if you prefer, write direct to Ex-Cell-O, Detroit.


* Style 22-8-inch Strake; Style 22-L-12-inch Strake.

58-21R



FIRST IN HIGH-SPEED METAL CUTTING

STONE



STRUCTURALS • SHEET

PLATE • EXTRUSIONS

Ferrous and Non-ferrous Metals • Non-metallic Materials

With one stroke, Stone metal cutting machinery outmodes hacksaws and bandsaws in the metal cutting field. Any material, regardless of hardness, can now be cut with machine tolerances in less than 4 seconds per square inch, leaving a mill-like finish that requires little or no machining.

Stone offers a complete line of metal cutting machines ranging from manual or automatic chop-stroke cut-off machines to traverse-type units that cut sheet and plate up to 12 feet in length. Illustrated is the Model M-750, typi-

cal of Stone Machinery's dependable construction. The fully enclosed, 7½ H.P. geared-in-head motor delivers full power to the cutting edge. The fast-acting, self-centering vise quickly adjusts for angle cutting (up to 46°). The heavy, cast, table-surface is finely machined for use of jigs and fixtures. Precision-cast frame gives maximum rigidity and support for fast, accurate cutting.

Other Stone Metal-Cutting Machines available with 3½ to 15 H.P. motors. Stone machines may be equipped for manual, semi-, or fully automatic operation. Optional Oil Mist Spray is easily attached—doubles or triples the life of the blade for non-

ferrous cutting.

STONE MACHINERY COMPANY, INC.

11 Fayette St., Manlius, New York

"...represented in every major industry throughout the world."

SEND FOR FREE FOLDER

For full details of the modern, faster, less expensive method of cutting, plus the details of other Stone cutting machinery, write today.

LOOK for improvements in industrial handcleaners



A NEW WAY to clean working hands

There has never been such a combination of plus features to keep workers' hands healthy—and therefore on the job day after day!

It's a brand new scientific formulation — non-depleting Lan-O-Kleen PLUS.

It's WEST'S famous Lan-O-Kleen handcleaner plus a softer scrubbing action plus a gentler sudsing action . . plus a soothing lanolin action!

All of which combine to combat the depletion of natural skin oils while hands are being washed clean.

Highly important is the exclusive process that keeps the rich lanolin content of Lan-O-Kleen PLUS "free" to soothe and soften. Lanolin is impregnated into a corn meal base, instead of being "held" in the soap by conventional methods. In this way, it is instantly released for more positive, beneficial action.

Lan-O-Kleen PLUS is dispensed from a patented, precision-action unit A clog-proof measuring valve with a mechanical agitator delivers a thrifty, yet adequate individual portion. More than 435 pairs of hands can be washed with each dispenser filling.

FREE TRIAL OFFER. We'd be glad to send five pounds of Lan-O-Kleen PLUS and loan a dispenser for free trial. Or we'll send a smaller sample for evaluation. Just call your local WEST office. Or mail the coupon to our Long Island City Headquarters, Dept. 18.

- $\hfill \square$ Supply a dispenser and 5 lbs. of Lan-O-Kleen PLUS.
- ☐ Send a small sample of Lan-O-Kleen PLUS.


Name__

Position_

PROGRAMS AND SPECIALTIES
FOR PROTECTIVE SANITATION
AND PREVENTIVE MAINTENANCE



WEST CHEMICAL PRODUCTS INC.
42 16 West Street. Long Island City 1. New York
Branches In principal cities
CANADA: 5621-23 Casgrain Avenue, Montreal



Oscillation Improves Abrasive Cutting 4 Ways

On an oscillating-type abrasive cut-off machine, the cutting wheel is rocked back and forth across the cut while the wheel is fed downward. This horizontal movement produces some remarkable results.

- 1 Greater cutting capacity is one big advantage of oscillation. Because oscillation reduces the arc of contact between the wheel and the work, it is possible to cut solid steel bars up to 12" square. Without oscillation, 2" to 3" would be the practicable limit.
- 2 Faster cutting is another benefit of oscillation. Because the reduced arc of contact offers less resistance to the cutting wheel on large sections, the same wheel cuts faster, straighter, and with less feed pressure. Cutting rates of 4 to 8 seconds per square inch are maintained on even the largest cross-sections.
- 3 Better quality cuts are obtained with oscillation. Less heat is generated because of the small arc of contact, and the rocking action permits coolant to enter the cut more easily and prevent any heat build-up.

Burn-free cuts are produced with negligible burr, and there is little or no need for further finishing.

4 Longer wheel life is an important economy factor. The lower cutting temperature resulting from oscillation adds extra cuts to the life of every wheel.

The better flow of coolant within the cut washes away metal chips and loose abrasive, helping wheel efficiency.

HOW ALLISON-CAMPBELL CAN HELP

A complete selection of machines and wheels for any cut-off application is offered by ALLISON-CAMPBELL. Four types of CAMPBELL machines—chop stroke, oscillating, horizontal, and rotary—in capacities from the smallest stock to 14" rounds . . billets up to 12" square . . plate up to 6" thick and 20 ft. long. ALLISON wheels—more than 150 different specifications—rubber or resinoid bond—3" to 34" diameters—0.06" to 3/16" thick.

Expert recommendations from your ALLISON-CAMPBELL Field Engineer can solve your cut-off problems for you. He'll be glad to show you how to get the faster, cleaner cuts you can expect from modern abrasive cutting techniques. Ask him.

WRITE FOR NEW BULLETIN

 Individual analysis of your cutting problems can be made in the new ALLISON-CAMPBELL Demonstration Laboratory. Write for a copy of DH-20, a new bulletin which describes how you can use these facilities. Complete details on ALLISON wheels and CAMPBELL machines are also available.

ALLISON-CAMPBELL DIVISION AMERICAN CHAIN & CABLE

937 Connecticut Avenue, Bridgeport 2, Conn.



SSILE MANUFACTURER

THE CONSTRUCTION OF STREET

a savings in time . .

THE TENED WITH A DISTURBANCE OF THE ECIAL EQUIPMENT MA

FOUNDRY EQUIPMENT MAKER torode

Above \$4000 yearly savings... excellent accuracy, duplicating to ease of conversion to regular or Copymatic operation are outstanding removing 15 to 30% more metal than our best (lathes) - twice that of some.

CHINE TOOL BUILDER

% time saved . . .

BCO

cell

5.92

CHINING SUBCONTRACTOR

The set of the second set of the second second

ving us

RCRAFT SUBCONTRACTOR

lps make deliveries and money.

TED BOAT BUILDER

000 annual saving . . .

ECTRONICS MANUFACTURER

oduction increased 200%

on is 90° COPYMATIC Lathe with 4-Way Power Rapid Traverse, anal extra). 45° COPYMATIC and Powershift Preselector Istock also available.

BOURSE FRANCES CONTRACTOR

HOW TO JUSTIFY YOUR LATHE REPLACEMENT

LOOK AT LODGE & SHIPLEY FIRSTI

> More production at lower cost is the answer to constant upward pressure on prices. Savings proved in Lodge & Shipley case histories* show the wisdom of


investigating and buying a Lodge & Shipley POWERTURN Lathe as a profitable replacement.

Production requirements change. The lathe purchased just a short time ago may not be adequate . . . judged by today's production, accuracy and economic standards. Details in Sweet's Machine Tool File; contact local representative through Yellow Pages or write direct for case histories and Bulletin No. L-103:

The Lodge & Shipley Co., 3074 Colerain Avenue, Cincinnati 25, Ohio.

*Names and details on request.

odge & Shipley



"We're now splitting tenths, thanks to Moore's

say Karl Harig, chairman, and Herbert Harig, president of Harig Manufacturing Corporation, Chicago

"Our operators feel these are the best machines they have ever worked on...

"Moore's No. 3 Jig Borer and No. 3
Jig Grinder take care of the
tenth-splitting tolerances required
by industry today..."


These are the words of two of America's acknowledged tooling leaders, active heads of one of the country's foremost independent producers of accurate dies—carbide, lamination, progressive, and other precision tooling.

Says President Herb Harig, former president of National Tool & Die Manufacturers Association:

"Moore's line of Jig Borers and Jig Grinders has been an integral part of the development and success of our company from 15 employees in 1937 to 120 today. We have always been



manufactured by



new No.3 Jig Borer and Jig Grinder"

among the first to install each new model. That's why we are among the first with Moore's tenth-splitting No. 3 Iig Borer and No. 3 Jig Grinder.

"As evidence of how indispensable we consider this equipment, over the years we have enlarged our Moore Jig Boring and Jig Grinding Department to 15 machines!"

Sums up Chairman Karl Harig:

"When owner-management invests its money in machinery, it does so only after thorough analysis and careful selection. I don't know of any machine tool manufacturer which meets both tests better than does Moore."

There's little more we can add, except to say that we stand ready to help you duplicate Harig's record of satisfaction. You can start by asking today for our detailed literature on the new No.3 machines with their larger tables; hardened, ground and lapped ways; no gibs, no overhang.

Also, our dealer organizations will gladly share with you their extensive knowledge of holes, contours and surfaces (see column at right).

Moore dealers know holes, contours & surfaces

- Machinery Sales Company 2838 Leonis Boulevard Los Angeles 58, California
- B-H-S Machinery Company
 717 Airport Boulevard
 South San Francisco, California
- Brett Machinery Company
 639 Madison Street
 Oak Park, Illinois
- The Cameron & Barkley Co.
 Machine Tool Division
 107 South Franklin Street
 Tampa, Florida
- State Machinery Company, Inc. 1800 North Meridian Street Indianapolis 2, Indiana
- Allen Supply Company, Inc.
 221 Third Avenue, S.W.
 Cedar Rapids, Iowa
- Ernst-Eichman Machinery Corp.
 323 West Murdock Street
 Wichita, Kansas
- Peninsular Machinery Company 19178 James Couzens Highway Detroit 35, Michigan
- Ernst-Eichman Machinery Corp.
 1701 Locust
 Kansas City 8, Missouri
- William Scheer Company 6376 Clayton Road St. Louis 17, Missouri
- Jeffreys Engineering & Equip. Co.
 P.O. Box 3443—Guilford Bldg.
 Greensboro, North Carolina
- The C. H. Gosiger Machinery Co.
 1046 Delta Avenue
 Cincinnati 8, Ohio
- Parks Machinery Company
 4040 Mayfield Road
 Cleveland 21. Ohio
- The C. H. Gosiger Machinery Co. Bacon & McDonough Streets Dayton 2, Ohio
- Oatis Machinery Company 325 West Central Avenue Toledo 10, Ohio
- Martin Machine Tool Company
 514-516 South Peoria
 Tulsa 1, Oklahoma
- Hallidie Machinery Company
 1545 S.E. Union Avenue
 Portland 14, Oregon
- Wm. K. Stamets Company Jenkins Arcade Building Pittsburgh 22, Pennsylvania
- Hamilton Machinery Company
 P.O. Box 5959, 918 W. Commerce
 Dallas 22, Texas
- Hallidie Machinery Company
 210 Hudson Street
 Seattle 4, Washington

CANADA

- The D. T. Lawrie Machinery Co.
 98 Traymore Avenue
 Hamilton, Ontario, Canada
- Moore Bros. Machinery Co., Ltd.
 953 St. James Street W.
 Montreal 3, Quebec, Canada

MOORE SPECIAL TOOL COMPANY, INC.

Bridgeport 7, Connecticut

MOORE ACCURACY

FOR THE MISSILE AGE


NEW Friction Saw Cuts Structurals-Rails & Pipe.


FAST!

MODELS AVAILABLE IN

75 HP

150 HP





Ty-Sa-Man



These revolutionary new friction saws are one-piece construction . . . need no expensive pits . . . can be moved quickly and cheaply. New coolant system keeps cut hot, blade cool . . . electronic pressure feed eliminates complicated hydraulic system . . . varies pressure as blade moves through different thicknesses. Steel safety shroud reduces noise level . . . stops flying sparks.

FREE BROCHURE

Tells The Complete Story-Write Today


TY-SA-MAN Machine Co., Inc. 800 White Ave., Knoxville, Tenn.



VIBRATORY FEEDER for light, highly finished or fragile parts.



ROTARY FEEDER for high production feeding.




Shuffle and deal parts for automatic assembly with



ROTARY HIGH SHELL FEEDER for maximum holding capacity.





The most complete line in industry, DPS parts feeders include rotary, vibratory and elevator types. They handle any product from the tiniest of screws to assembly components the size of your fist . . . range in holding area from eighty cubic inches to 20 cubic feet.



DPS will welcome an invitation to analyze your assembly operations. Write today. Ask for catalog on selective feeders.



DETROIT POWER SCREWDRIVER COMPANY 15,080

2809 W. Fort St. • Detroit 16, Michigan

A Subsidiary of Link-Belt Company



In checking with the tool, die, gage and general production shops that use SAN-FORD SURFACE GRIND-ERS, the most frequent comment was that Sanford Grinders were the "most used" of any grinders in the shop.

PARTIAL SPECIFICATIONS-

Capacity - 8" x 12" x 12".

Table travel - 13", traverse 83/4". Vertical clearance 12" under 7" wheel.

Standard grinding wheel - 7"x 1/2", 11/4" hole.

Spindle speed approx. 3000 RPM. Motor, 1/2 HP, single or 3 ph., dynamically balanced.

Floor space-45" x 38" x 62" high. Net wt. with stand approx. 630 lbs. Others have tried to copy but there's a "feel" that comes from the precise individual quality and workmanship that goes into every SANFORD GRINDER. It's the factor that can't be found in any other grinder.

> So widely used you can ask users in your own area how they like the low priced Sanford Surface Grinder.

Write for illustrated and fully descriptive literature, reconditioning facilities, optional equipment and prices,

Representatives in major industrial areas


MANUFACTURING CORP. 1026 Commerce Ave., Union, N. J.





A few desirable territories open to qualified representatives





Serving the Industry Since 1852



Specify

WOODS MOTOR ARBORS


for MORE POWER

in LESS SPACE



"A"	HP at	FRAME	"B"
DIMENSION	3600 RPM	SERIES	DIMENSION
41/2"	1 - 71/2	20	31/4"
51/8"	1 - 20	30	4"
61/2"	5 - 30	40	51/8"
836"	20 - 60	50	7-1/16"

Send for descriptive material



S. A. WOODS MACHINE CO. 27 DAMRELL STREET BOSTON 27, MASS.

Combination Center Drills

CENTER DRILLS

NUMBER DRILLS

ALL THREE

in Regular, Arbor or Bell Type from smallest to 1" sizes

CIRCLE (R) Heat-treated

To Better Your Production



CIRCLE R Center Drills include "all three" in the full size range up to 1" plus special lengths and diameters to meet your requirements. And after precision manufacture, we perfect them for your use with our exclusive heat treatment. Ask your Circle R Specialist.

Consult these CIRCLE R Specialists . . .


BURBANK INDIANAPOLIS
Prefection Mach. Sales Inc. Walter F. Grance & Assoc. CHICAGO Bosoid Robertson & Co. CLEVELAND Production Tool Co. BAYTON J. R. Kunts Company DETROIT HACKENSACK

MILWAUKEE MONTREAL Humphrey E. Wolfon NEW YORK CITY

PROVIDENCE ROCHESTER ST. LOUIS B. C. MacDoneld & Co. WESTBURY, L. I.

PITTSBURGH Bolob Expenits & Com-

Specialists in Circular Cutting Tools Since 1923



METAL SLITTING SAWS . COPPER SLITTING SAWS . SCREW SLOTTING SAWS . COMMUTATOR SLOTTING SAWS . SEWELERS' SLOTTING SAWS . CUT OFF SAWS . CIRCULAR BUVES & ROTARY SHEAR BLADES . CIRCOLOY STEEL SAWS . SOLID & TIPPED TUMESTEN CARBIDE SAWS . COMBINED DRILLS & COUNTERSINES . CENTER REAMERS

Designed for the "Missile Age"

GORTON

race-Master" Mastern

with exclusive combination of sustained toolroom accuracy and precision-built Trace-Master Hydraulic tracer control



3. Models Available (1) 180° Vertical Hydraulic Feed to Knee (2) 360° Cross Hydraulic Feed to Ram and Longitudinal Hydraulic Feed to Table (3) 3D Hydraulic feed to knee, ram and table for 3-dimensional work. Trace-Master controls can be furnished with the Model 1-22 Mastermil illustrated above or the Model 9-J Super-Speed Vertical Mill with single spindle, twin spindles and/or six inch higher column for additional vertical capacity.

Nowhere Else will you find this combination

- 1. TWO H.P. spindle motor
- 2. Finest Milling Head in its
- 3. 80 to 5,600 RPM spindle
- 4. Rigidity . . . (2,800 lbs net weight)
- 5. Extra long saddle

Nowhere Else will you find this versatility

- 1. Production profiling
- 2. Scanning
- 3. Duplicating . . . die and mold work
- 4. Milling . . . conventional and climb
- 5. Boring

Write for Bulletin

2771-1404





GEORGE GORTON MACHINE CO.

1404 RACINE STREET

RACINE. WISCONSIN

Tracer-Controlled Pantographs, Duplicators — standard and special . . . Harizontal and Vertical Mills, Swiss-Type Screw Machines, Tool Grinders, Small Tools and Accessories

DIEMAKERS!

DIE-PART PORTELVATOR®

(OR AN ENGINEERED VARIANT)

will speed your work and ease your "handling."

Top plate raises and lowers for fitting operations •and rotates 360° to give easy access to die.





THE HAMILTON TOOL COMPANY 825 SOUTH NINTH ST. HAMILTON • OHIO • U.S.A.



A Lot More ACCURACY ECONOMY too!

INDEX "SUPER VERTICAL

● 1½ HP Head or optional 2 HP with continuous duty motor gives 50% or more capacity . . . More rigidity, more accuracy . . . Increased horse power and dynamically balanced Cast Iron Pulleys and Drive System afford improved production capacity . . . More weight in the column, heavier ribbed column, heavier knee, heavier saddle.

INDEX "45" VERTICAL MILL

Unique square design of overarm affords more rigidity, greater accuracy... Provides extra range and capacity... More power at the cutter. No adjustment required on overarm and head after use ... No need to re-indicate head after moving overarm... Speed range with nine changes makes possible the use of high speed or carbide tipped cutters to best advantage.

INDEX MACHINE CO.

543 N. MECHANIC ST., JACKSON, MICH.





GRIND...POLISH...DEBURR in one operation with Frammond FLAT FINISHERS

For fast, uniform, economical finishing of flat work such as sheets, bars, strips, stampings and extrusions with one machine, one operator and one pass.

AUTOMATIC AIR TENSIONING: maintains correct tension on abrasive belts and conveyor belt . VARIABLE SPEED CONVEYOR: rate of feed is adjustable from 0 to 60 FPM . WORK HOLDERS: hold-down rolls, electro-magnetic platen and various types of conveyor belts . AMMETER CONTROL: an ammeter for each head allows operator to determine and maintain the polishing pressure necessary for a uniform finish and longer belt life . V-BELT DRIVE: allows abrasive belt speed to be changed to suit the work . MICROMETER DIAL: controls heads for required depth of cut.



SEND SAMPLES Send us one finished and several hed and severale You will receive Report

Hammond Machinery Due 1614 DOUGLAS AVE.

See Us At The Industrial Finishing Exposition - June 15-19 - Detroit - Booths 261-266.

1 TO 6 HEADS

6" to 12" WIDE

to 6" high.



The CFC Delpark Disposable Media Filter is self-cleaning... automatically. Full flow filtration of coolants is uninterrupted during the cleaning cycle. There's no costly downtime for cleaning the filters or reservoirs.

By continuous removal of solid particles, clean coolant is returned continuously to the work area. You get greater machine efficiency, better finishes, increased output, less wheel dressing, longer wheel life, and extended coolant life. Valuable materials, such as diamond wheel particles, are easily recovered.

The filter material, fed from a roll, rests on a flat endless conveyor. Dirty coolant is fed on to the filter material. Clean liquid passes through by gravity while solid contaminants remain on surface of filter material. When flow rate is reduced sufficiently, liquid level rises raising a float. This actuates a switch which causes conveyor to carry filter material and swarf forward, and bring a new clean filter surface under the incoming dirty coolant. Cycle is repeated automatically as necessary.

The CFC Delpark Disposable Media Filter is also designed for cutting oils, quenching oils and other liquids of light viscosity. Standard units have capacity of 2 to 700 gpm. Write for technical literature to Dep't MT

COMMERCIAL FILTERS CORPORATION
MELROSE PA. MASSACHUSEITS
FIANTI MILEOLE MASSACHUSEITS DIGUELANON INDIANA

MICRO-CLARITY AT MINIMUM COST



with genuine Haneycomb Filte Tubes for controlled microclarity of industrial fluids.



Selective filtration of oils • water-oil separators • magnetic separators • pre-coat filters • coalant clarifiers • automatic tubular conveyors.



for complete information on

LO-AIR

low temperature-air hardening*
TOOL and DIE STEEL



Brochure No. TS-101 gives you the facts on LO-AIR, the modern cold work die steel which provides ease of machining with maximum hardenability. This means lower cost—safer die making. Due to the balanced combination of carbon, chromium, manganese and molybdenum, LO-AIR can be heat treated at low temperatures, resulting in excellent dimensional stability—and at no increase in hardening costs over oil hardening tool steel (AISI 01). LO-AIR is now available from branch warehouse stocks. Order a bar today!



TOOL STEELS . STAINLESS STEELS . HIGH TEMPERATURE METALS



Write for your copy of the most complete catalog in the industry-includes Tools and Blanks for all size Brown & Sharpes and Davenports as well as

Blanks for New Britain-Gridley, Cleveland, Warner & Swasey, National-Acme and Conomatic machines.

Let Somma Standard Circular Form Tools give you uniform, correct dimensions, better finish and appearance, less set-up trouble. In short -Maximum production at the lowest cost.

OOL CO., INC. 121 SCOTT ROAD, WATERBURY, CONN.

West Coast Warehouse: 576 N. Prairie, Hawthorne, Cal.

Use postpaid card. Circle No. 268

District Managers MACHINE and TOOL BLUE BOOK

EASTERN DIVISION

Dan E. Roerdon, V.P. In charge c/o Hitchcock Publishing Co. 55 West 42nd Street New York 36, N.Y. Yelophone: LAckawanna 4-4528

CONNECTICUT

Dan E. Rearden, V.P. Box No. 1, South Glastonbury, Conn. Telephone: MEdford 3-7083

Telegraps: MEGIFER 3-7083
NEW YORK, N.J., MD., D. of C., EASTERN
PA., DELA.
Raymond J. Sletsema
e/e Hitcheeck Publishing Co.
85 West 42nd Street
New York 38, N.Y.
Telegraps C. Alexansma 4-4528
Home Tel.: (Cedar Grove, N.J.) Center 9-4364

MAINE, N.H., VERMONT, MASS., R.I., LONG 18LAND, N.Y. Domaid J. Loverich 49 Standish Red. 8tamford, Conn. Telephone: Davis 3-8156

CENTRAL DIVISION

SOUTHWESTERN OHIO, INDIANA. KENTUCKY Henry J. Smith, V.P., in charge e/o Hitcheesk Publishing Co. Wheaton, Illinois Telephone: MOntrose 5-1080

MICHIGAN, NORTHERN IND., NORTH-WESTERN OHIO William E. Jacobs 18055 James Couzens Highway Detroit 35, Michigan Telephone: Diamond 1-9525

ILLINOIS, MISSOURI, IOWA, WISCONSIN, MINNESOTA, UPPER PENINSULA of MICH., & SOUTH DAKOTA Robert G. Belinder e/o Hitchcock Publishing Co. Wheaton, Illinois Telephone: MOntroso 5-1000

WESTERN NEW YORK STATE, WESTERN PENNA., EASTERN OHIO Ralph E. Helfrick 1507 Edgefield Road Cleveland 24, Ohie Telephone: Hillerest 2-0189

WESTERN DIVISION

CALIFORNIA, ARIZONA Keith H. Evans Keith H. Evans 3723 Wilshire Boulevard Los Angeles 5, California Telephone: DUnkirk 8-2981

sand 593 Market St. (Reem 818) San Francisco 5, California Telephone: YUkon 2-4280

OREGON, WASHINGTON
Lloyd Therpe
212 General Insurance Building
Seattle 5, Washington
Telephone: MElrose 3-4242

HITCHCOCK PUBLISHING CO.

Telephone MO 5-1000 Wheaton, Ill.

GREEN Pantograph Engravers

ELIMINATE DELAYS!

Keep the work in your own plant.



40-POUND BENCH-MODEL 106

Famous 2 or 3-dimensional engraver, successfully used by thousands, features 5 positive, accurate pantograph ratios. Versatile ball bearing spindle has three speeds up to 14,000 rpm; height of pantograph and position of cutter are continuously adjustable: one copy carrier (supplied) accepts all standard master type sizes.

The Model 106 has proven incomparable for speed and accuracy . . . vet reasonably priced.

Cutter grinders, rotary tables, master letters, compound slides, name plates and all required accessories. For complete information, write to




- 575 pounds rigid. sturdy, precise
- Vertical adjustment of copy table automatic with Pantograph
- Unobstructed on three sides to take large work
- Micrometer adjustment for depth of cut Ball-bearing construction throughout —
- super-precision ball bearing spindle Spindle speeds up to 26,000 rpm for
 - engraving or machining modern materials
 - Ratios 2 to 1 to infinity master copy area 26" x 10"
 - Vertical range over 10'



GREEN INSTRUMENT COMPANY, INC.

386A PUTNAM AVENUE, CAMBRIDGE 39, MASS.



Micro-precision extended for years ON EVERY COVEL TOOL-ROOM SURFACE GRINDER

Grinding plastic mold dies like this calls for MICRO-PRECISION . . . and the 14" x 24" Covel ''60'' has it! Also accurately grinds trim, forming blanking and die-casting dies in addition to jigs, fixtures, dovetail and flat form tools. Ideal for high speed or carbide production parts grinding, too. Covel precision grinders save you money because they give new-machine performance longer—stay ''front-and-center'' in your tool-room grinder lineup for years and years of MICRO-PRECISION performance. That's because Covel-pioneered features preserve new-machine accuracy longer—for example, hard chrome table ways maintain built-in accuracy far beyond the life of ordinary ways. Before you buy your next surface grinder, it will pay you to learn all the facts about this and other Covel advances.

First with hard chrome table ways...



Send today for your copy of "The Covel Precision Story" and complete data on the Covel Surface Grinder that meets your needs — seven sizes from $6'' \times 12''$ to $16'' \times 36''$. Ask for Bulletin BB-49





FROM DENISON a small hydraulic press so productive it...

GUARANTEES YOUR SAVINGS

If in 45 days the Denison Model "A" Multipress does not cut your production costs or does not improve production quality, simplify operation or give your shop more versatility — simply return the press.

Multipress is ideal for assembly, forming, staking—and 101 other shop jobs. No cost or obligation to try it out now, in your own plant.

YOU PAY ONLY FOR THE FREIGHT



Denison Model "A" hydraulic Multipress. Available in 1-ton and 2-ton ram capacity.

Write for your copy of the detailed bulletin

DENISON ENGINEERING DIVISION American Brake Shoe Co.

1245 Dublin Road . Columbus 16, Ohio

Denison Stocking Branch Offices: LOSANGELES • DETROIT

HOUSTON - DAYTON

CHICAGO . NEWARK

Denison, Denison HydrOILics, and Multipress are registered trademarks of Denison Eng. Div., ABSC



RIGHTMOS . ZOTOM . EQUIPS . PERZERY SILVERGEN

Are you **SAVING** through **ENGRAVING?**



RADIOTELECHAPH
TRANSMITTER
TYPERM 4.8 SERIKUM*
FRES, ENCHEMNS
DOWN 4.48
PRESS WIRELES N
WIRELES N






· 213B ·



YOU CAN mark parts, make signs and nameplates, improve your product and cut your costs in 1001 ways with the portable



Engravograph

It's tracer-guided for unskilled labor. Every plant needs one, wherever permanent lettering or numbering has to be done. There is a complete line of models to meet your application, from \$298.00 up.

Consult our engineers on how ENGRAVOGRAPH can help your operation, or write on your letterhead for our 28-page fully illustrated catalog MM-2


II PIT II PI III PS ENGRAVING MACHINE CORP

13-19 UNIVERSITY PLACE, NEW YORK 3, N. Y

MONDIALE CELTIC PRECISION LATHES

QUALITY . PRECISION . DEPENDABILITY

OVER 30,000 MONDIALE LATHES ARE IN USE THROUGHOUT THE WORLD



CELTIC 20" LATHE MADE IN 12"-14" -17"-20" SWINGS

OUTSTANDING FEATURES:

Precision hardened and ground spindle • Standard taper keydrive spindle nose • Hardened and ground gears and shafts • Equipped with anti-friction bearings • Automatic built-in safety devices prevent simultaneous engagement of the lead screw and feeds • Helical gears in the apron assures smooth and silent operation • Removable gap affording extra capacity at no additional charge • Splash lubrication • Direct Vee-belt drive between motor, gearbox and headstock results in smooth and fine finishes • High spindle speeds.


DEALER INQUIRIES INVITED

INDEX INDUSTRIAL CORPORATION

150-MT Broadway, New York 38, N.Y. - BEckman 3-4540

Can You Hold Your Shaper Without Bolts?

VES - with new WEDGMOUNT which anchors Shapers, Presses, etc. and permits precision leveling!



Free folder gives complete facts about

WEDGMOUNT with

"Air-Lec" patented vinyl, sisal and cork pads top and bottom grip machines to floors

double-wedge construction which permits immediate precision leveling

keyed construction which prevents movement within the mount

sizes available thru distributors, and prices

write to ...

This Gould & Eberhardt 24" Industrial Universal Shaper, operating at 120 cuts per minute with a 4" stroke, is installed without bolts on a new type machinery mount called WEDGMOUNT. A dial indicator at the base of the shaper showed a total oscillation of only .022" during operation, and no "walking." The 7,800 lb. machine is installed on six WEDGMOUNTS, each type 3" x 6" S. Before operation, precision leveling is achieved by simple adjustment of a bolt within each mount. Top and bottom of each mount is surfaced with patented "Air-Loc" pads, which provide the high degree of friction required to hold the machine in place despite its strong lateral thrust.

Hir-foc WEDGMOUNT

Clark-Cutler-McDermott Co.

3 West Central Street, Franklin, Massachusetts

Features in This Issue

Interview with Robert W. Galvin,	
president, Motorola, Inc.	95
Mist Cooling Up-to-Date1	05
Arbitration of Work Standards—2 Cases1	10
Outlook for Man-Made Diamonds	18

Interview with Robert W. Galvin. Every year the consumer has a wider choice of goods and services from which to select. Some industries are feeling the pinch of consumer resistance, but Motorola, Inc., one of the leaders in the electronics products field is going great guns in the stereo high fidelity, car radio and portable radio branches of their business. Robert W. Galvin, president of Motorola, Inc. asserts that sound design and engineering will pay dividends in the coming months and years because the consumer is upgrading his tastes and, more than ever, qualityvalue will be the basis for his choice. Mr. Galvin foresees more ways that the electronics industry can join with the metalworking industry to produce more efficient machine tools,Page 95


Mist Cooling. Cooling with a mist in atomized form is changing the entire concept of cooling and lubricating all types of fabricating operations. Here is a general discussion on the principles of the process, and what users report about the advantages over conventional methods of flood cooling with respect to various types of applications.

Pape 105

Arbitration of Work Standards. Anyone

having had an experience with a work standards dispute going to arbitration should compare his methods of attack with Harold R. Nissley's account of his experience in arbitrating two cases: 1) When an increased work load is required of a day work operator; 2) A new inspection rate is challenged. Although these cases may differ from particular cases you have in mind, Mr. Nissley's methods of attack are worth studying. This is the fourth installment in the series on Practical Arbitration, Time Study and Work Simplification.

How Good are Man-Made Diamonds? Laboratory and field tests conducted under controlled conditions by Simonds Abrasive Co. confirm the superiority of man-made diamonds in resinoid, vitrified bonds for carbide grinding. Man-made diamonds in 75 concentration top the performance of 100 concentration natural diamonds in selected applications. This article by Chester A. Nisula, Product Manager of Simonds Abrasive Co. presents tangible evidence of the superiority of the man-made variety over natural diamonds.



58-tooth gear, 11 N.D.P. 17* 49' helix, 2' face width.

Grinding allowance: 0.014" over pins. Material: 4140 stoel,

245-285 Brinell hardness Grinding time: 15 minutes.

14-tooth pinion, 11 N.D.P., 17° 49' helix, 2½" face width for full depth teeth.

Grinding allowance: 0.012" over pins. Material: 4140 steel, 269-321 Brinell hardness Grinding time: 8 minutes.

Tolerances: Lead--0.0001" per inch. P.D. runout--0.0005" T.I.R. Involute profileplus 0.000, minus 0.0002".

Reishauer Gear Grinding Machine

THE PRECISION LINE

Fellow

RINDING

HILADELPHIA GEAR



When speed reducer gears need that extra degree of precision for smoother, quieter operation, the well-known Philadelphia Gear Works grinds them on a Reishauer because it is accurate and fast. For example, grinding time was only 15 minutes for the gear and 8 minutes for the pinion shown on the opposite page.

Gear grinding by the Reishauer method is a generating process. The involute gear teeth are generated by a grinding wheel on which a helix has been developed. The tooth section of the wheel is usually that of the basic involute rack.

Fellows builds the No. 12 Fellows-Reishauer Gear Grinding Machine under license from Switzerland's Reishauer Tool Works. The No. 12 grinds in both directions of travel of the work-slide and has a built-in device for crown grinding. Short set-up time permits the economical production of single pieces as well as long runs.

Capacities for the No. 12 are: Max. O.D., spur and helical, 12"; Max. face width, spur, 63/4"; Max. face width, helical, depends on pitch and helix angle; Pressure angles, 141/2° to 30°; Pitch ranges (two lead screws are available), 6 to 48 D.P. or 20 to 120 D.P.

Grinding gears by the Reishauer method will give you precision gears at real production speeds. Ask your Fellows Representative about it.

THE FELLOWS GEAR SHAPER COMPANY
78 River Street, Springfield, Vermont
Branch Offices: 1048 North Woodward Avenue, Royal Oak, Mich.
150 West Pleasant Avenue, Maywood, N. J.
5835 West North Avenue, Chicago 39
6214 West Manchester Avenue, Los Angeles 45

ar Production Equipment

We would like to receive twenty reprints of the article appearing in the January issue of your magazine on page 83, entitled "Practical Arbitration, Time Study and Work Simplification."

F. T. Wilson, Assistant Secretary The Thompson Grinder Company Springfield, Ohio

Tear sheets of this article are exhausted. However, the entire series will be reprinted after it runs its course. This will also include the 1954 articles by Mr. Nissley and make this a really worthwhile work on arbitration, time study and incentives.

Tape Control

We are interested in obtaining any additional information on the Micro-Path Control System noted on pages 123 through 128 of the January 1959 issue. Since we are unable to locate an address for Micro-Path, Inc., it would be appreciated if you would forward our request to this company or inform us of the proper address.

We would also appreciate any literature or the name of the manufacturer of the Ringspann discs noted on page 116 of the same issue.

> R. J. CUTSHALL SPEEDWAY FLAME PLATING LINDE COMPANY Indianapolis 24, Indiana

In the January 1959 issue of BLUE BOOK, page 123, describing a tape control milling process we would appreciate receiving more information on this or a reference as to where it could be obtained.

H. H. WYDOM BROCKTON TOOL CO. South Easton, Mass.

Producer of the Micro-Path system

is Topp Industries, 5221 W. 102nd St., Los Angeles 25, Calif.

Stub Drilling

If you have any reprints of Harry Conn's article "The Potential Savings of Stub Drilling" they will be appreciated. As many as possible. These will be used for distribution among our Seminar members.

HORACE FROMMELT, DIRECTOR SPRING GARDEN INSTITUTE METAL REMOVAL CENTER Philadelphia 23, Pa.

Short Run Parts

We would appreciate receiving at your convenience two (2) reprints entitled "Economical Production of Short Run Parts", appearing in your interesting monthly magazine Machine and Tool Blue Book; November, 1958 issue.

R. BOUSQUET
INDUSTRIAL ENGINEER
PRIMARY PARTS DIVISION
CANADIAN MARCONI COMPANY
Montreal 16, Quebec, Canada

Work Holding Discs

The January issue of your magazine has an article by A. Maurer pertaining to work holding discs produced by Ringspann. We wish more information on who produces these discs and where they may be procured.

J. E. Lass Chief Tool Designer International Harvester Co. Melrose Park, Illinois Distributor for the Ringspann disc is Neise Modern Tools, 404 Fourth Ave., New York 16, N.Y.

Endless Belt Feeding

I am interested in the article in your December issue of MACHINE and TOOL BLUE BOOK entitled, "Endless Belt Feeding to a Progressive Die."

> Fred J. Hauser Western Electric Co. Chicago 23, Illinois



Fiske's Darl Base

A base cutting oil for use in working both ferrous and nonferrous metals. Can be used straight or reduced with mineral oil to suit the metal and work. Non-corrosive. Permits visibility when mixed. Has exceptional anti-weld properties, lubricity and film strength. For better finish of product and longer tool and die life, use "DARL".

Bulletins describing Fiske's Darl Base Oil and other specialty lubricants and coolants sent on request.






METAL WORKING LUBRICANTS

FISKE BROTHERS REFINING CO.

129A LOCKWOOD STREET, NEWARK 5, N.J.

Plants: Newark 5, N. J., Toledo 5, Ohio

for MAXIMUM capacity in MINIMUM space...




VERSA Control Valves

IN OVER 110,000 VARIATIONS!

You can get immediate delivery of Versa Control Valves in any size or actuation, to fit your most exacting Hydraulic or pneumatic requirement.

Versa's compact design, simple construction and precise manufacturing guarantees many millions of cycles of satisfactory, trouble-free performance.

All Versa Valves are available in 2-, 3-, 4-, and 5-, way types in sizes from 16'' to 1'' NPT and for pressures from partial vacuum to 500 PSIG.



VERSA

VERSA PRODUCTS COMPANY INC. 249 SCHOLES STREET BROOKLYN & N. Y 0

The entire line of VERSA valves is explained in our new comprehensive Folder \$14

Use postpaid oard. Circle No. 277

MACHINE and TOOL BLUE BOOK



Fastest way to find any file There isn't a file you can't find and get fast. First look in your Nicholson or Black Diamond Catalog. Then call your Nicholson or Black Diamond Industrial Distributor.... There are thousands of different files. There are General Purpose varieties for the usual kind of work. There are Special Purpose files to improve the work on specific materials — brass, lead, aluminum and steels, for example. Your Nicholson or Black Diamond File Distributor can meet all your file needs.... If you have a problem that calls for an entirely different kind of file, we'd like to work with you to solve it. Our research laboratory is available to you for this.... Your Nicholson or Black Diamond File Distributor is the man to call first if the subject is Files or Filing. Ask him now for a catalog.

* Industrial Distributors provide finest goods and services in least possible time. Our products are sold exclusively through them.

Files and Rotary Burs · Hacksaw and Band Saw Blades · Ground Flat Stock · Industrial Hammers



NICHOLSON





Nicholson File Company, Providence, Rhode Island Use postpoid card. Circle No. 279

Meetings

- Apr. 3, 4—American Society for Quality Control, 7th Northwest Conference on Quality Control, Oregon Museum of Science and Industry, Portland, Oregon. Headquarters: P.O. Box 2001, Portland 14, Oregon.
- Apr. 6-10—American Welding Society, AIEE Electric Welding Conference, Hotel Sherman, Chicago, Illinois. Headquarters: 33 West 39th Street, New York 18, New York.
- Apr. 13-17—American Foundrymen's Society, Engineered Castings Show, Sherman and Morrison Hotels, Chicago, Illinois. Headquarters: Golf & Wolf Roads, Des Plaines, Illinois.
- Apr. 14, 15—Conference on Industrial Instrumentation and Control. Illinois Institute of Technology, 35 West 33rd Street, Chicago 16, Illinois.
- Apr. 18-22—American Society of Tool Engineers. Schroeder Hotel, Milwaukee, Wisconsin. Headquarters: 10700 Puritan Avenue, Detroit 38, Michigan.

- Apr. 20, 21—Seventeenth Annual SPI Canadian Section Conference, The Society of the Plastics Industry (Canada), Inc., Windsor Hotel, Montreal, Canada. Headquarters: 77 York Street, Toronto, Ontario, Canada.
- Apr. 21, 22, 23—American Society of Lubrication Engineers, 14th Annual Meeting, Hotel Statler, Buffalo, New York. Head-quarters: 84 East Randolph Street, Chicago 1, Illinois.
- Apr. 26-30—National Screw Machine Products Association, Hotel Roosevelt, New York. Headquarters: 2860 East 130th Street, Cleveland 20, Ohio.
- May 25-28—American Society of Mechanical Engineers, Design Engineering Conference, Convention Hall, Philadelphia, Pa.
- June 14-19—Society of Automotive Engineers, Summer Meeting, Chalfonte-Haddon Hall, Atlantic City, New Jersey. Headquarters: 458 Lexington Avenue, New York 17, New York.



Feature for feature, Price for price...

FOR DRILLING AT A

SPINDLE ACCURACY
Bearings at TOP and
bottom of spindle
pulley.

BUILT-IN ELECTRICS with overload protection.

> POSITIVE DEPTH GAGE Quickly set for positive stop.

RAPID SPEED CHANGE Five spindle speeds.

SPACIOUS TABLES
Unusually wide
work range.

APPEARANCE Streamlined functionally.

ACCESSORIES
Profit-boosting
attachments and
accessories.

CINCINNATI 16 ROYAL

this

DRILL BUY!

This is a real metalworking drill — a multi-purpose machine tool built to handle light drilling on a production basis, and for utility operations. "CINCINNATI-quality" means that it holds its accuracy longer, stays on the job longer.

ROYALS are built in 16" and 18" bench and floor types, single and multiple spindle.

*Only \$128 for the Cincinnati 16" Royal bench type drill shown. Complete with 0"-½" chuck or #2 M.T. spindle, built-in single phase manual control with overload protection—less motor. Floor model, as above, only \$143.

See your CL&T Dealer, or write us direct.



Improved Machining Through Research

CINCINNATI LATHE AND TOOL CO.

3207 Disney Street . Cincinnati 9, Ohio

"TRAY-TOP" Lathes / "CINCINNATI" Drilling Machines / "SPIROPOINT" Drill Sharpeners

WHY is chaser hardening important to your threads?

When cutting threads-long tool life, maximum accuracy, and trouble-free operation can only be assured by proper chaser hardening. For example, LANDIS Tangential Chasers are often given special hardening treatment when workpiece design or material specifications so indicate. Just as with the blacksmith of years gone by, so chaser hardening today is an art. The ability to determine and apply the proper chaser-hardening technique is the result of our more than 50 years experience in a single field-THREADING. This is but one of the many ways in which LANDIS Threading Specialists may be of help. Whatever your need for generating threads-Cutting, Rolling, Grinding, or Tapping-LANDIS Threading Equipment will accomplish it most efficiently and economically.



LANDIS Machine COMPANY

Roundup of Washington News



We have the power to destroy Russia utterly, and she has the power to destroy us. There is no way in the future for either of us to win a war.

Adm. Arleigh Burke Chief of Naval Operations

Democratic Senators Aspire to Presidency

At least four Democratic senators await the sound of the bell in the Presidential ring, and it appears that Majority Leader Johnson (Tex.) is the ringside favorite. His broad legislative program is skillfully designed to appeal to most Americans. He has also proved himself capable of dealing successfully with liberal and conservative factions of his party. Mr. Johnson's southern affiliation is perhaps the most formidable deterrent to his nomination.

Senator Kennedy (Mass.), high on the list of contenders, is a staunch believer in legislation designed to promote labor reforms, but he realizes that his platform must be tempered to appeal to those who hold moderate views. Senator Symington (Mo.) will base his campaign on defense legislation.

Liberals are supporting Senator Humphrey (Minn.), an advocate of major social and civil rights reforms. Mr. Humphrey, recently returned from Russia, stresses the need for a thorough analysis of foreign affairs.

Labor-Mgmt. Racketeering Cases to be Prosecuted

Twenty-eight lawyers of the Justice Department's Antitrust Division have been assigned to prosecute labor-management racketeering cases under the Sherman Act. Although officials avow they will not use the Act as a club to attack unions, labor-management "payoffs" will be considered violations of the antitrust laws. Monopolistic practices of unions engaged in commercial ventures also shall be investigated.

The Senate Rackets Committee has criticized the Department of Justice for not taking action on some of the Committee's disclosures. If weaknesses in the antitrust statutes become apparent through the prosecution of these cases, the McClellan group will ask Congress to strengthen the laws.

California Captures Lion's Share of Defense Business

While eastern manufacturers of missiles and aircraft are operating below capacity, e.g., Martin (Baltimore), Republic (New York), and Fairchild (New York and Hagerstown, Md.), approximately 21.4% of Government prime missile contracts, amounting in the aggregate to \$8 billion, are held by California contractors. In addition, California's subcontracts total about \$1.3 billion.

This disproportionate allotment has caused many eastern and even some western members of Congress to rise up in arms, and they are taking steps to prevent further awarding of missile contracts to the Pacific Coast. If necessary, they will take their grievance all the way to the White House.

Senator Butler (Rep., Md.), is one who vehemently protests the situation. Says Mr. Butler: "It is most important to maintain in an excellent state of health vital facilities for missile and aircraft manufacture in the East. It is against the Nation's best defense interests to concentrate such manufacture in only one State in the Union. The Golden State is facing a battle on this issue because it doesn't seem content with the hog's share. So, if it wants a fight—California, here we come."


National Chamber Seeks to Reconstruct Tax System

The Department of Taxation and Finance of the U.S. Chamber of Commerce has announced that it is urging Congress to reconstruct and simplify our national tax system. It is promoting the establishment of an impartial study group which would take a keen look at the strengths and weaknesses of our present tax system, investigate the tax systems of other nations. consider the writings and proposals of learned men in the field of tax philosophy and tax practice, and devise a tax structure which will stimulate rather than retard our national economic growth. Constant tinkering with our tax laws, they believe, will do little more than "add a further layer of patchwork to the existing crazy-quilt pattern."

"Controlling Inspection Costs in Small Plants" is Bulletin No. 96 of the series, "Management Aids for Small Manufacturers," published by the Small Business Administration, Washington 25, D.C. It admonishes the reader to make sure that inspection procedures are set up and run efficiently; that inspectors are properly chosen and trained; that gages and equipment are maintained; that inspecting is done accurately.

FOR HIGH SPEED PRECISION TAPPING CHOOSE THE

KAUFMAN



MODEL 10E-20 Z

Six features of this new, precision-built Kaufman Tapping Machine are:

- Lead screw control for accurate threads and maximum tool life. Maximum 4½" lead screw travel.
- Rapid approach of spindles to work.
- Clutch operated for faster operation — Reversing spindles at twice forward speed.
- Six speed transmission providing spindle speeds of 80-350 RPM with 3-1 ratio or 160-700 with 1½-1 ratio clutch.
- 5. Units provided with 5-7½-10 H.P. Motors.
- 6. Speeds and H.P. available for highly efficient tapping from %6" through 2" NC taps or smaller taps with use of multiple head.



For additional information about the new Model 10E-20 or other Kaufman machines for single or multiple operation, write or telephone:


KAUFMAN MFG. CO.

539 S. 29th Street

Manitowoc, Wisconsin

its specifications add up to high production capacity





Logan designs greater reliability and accuracy, and longer life into its lathes by a generous combination of high-capacity features. For instance—

- An oversize spindle with 1%" bore turns on four superprecision ball bearings with built-in preload
- A variable-speed drive lets you change speed while work is turning—without shifting belts
- A warp-free lathe bed with high, strong walls breced by oversize ribs to withstand heaviest stresses; two V-ways and two flat ways are flame-hardened and precision-ground.

There are many more reasons why this and other Logan Lathes have a greater capacity. The complete specifications tell the story. Write for them.

- Spindle speeds to 2000 rpm
- 1½" Levermatic collet chuck capacity
- 1458" swing over bed
- 9" swing over saddle cross slide
- 40" between centers

LOGAN ENGINEERING CO. Dept. J.459 4901 Lawrence Avenue, Chicago 30, Illinois
Use postagid card. Circle No. 284

Measure Everything in Terms of Cost?

Has top management been overconditioned to base their decisions in terms of costs? Just how far can we go with cost consciousness?

Let's take the appraisal of supervisory effectiveness as a case in point. It is very important that top management be aware of the attitudes of the department heads. High morale is the sum of a person's confidence in the organization, his on-the-job associates and himself. Sometimes we forget that high morale and good performance go hand in hand.

One sure way to impair the morale of a department head is to judge his performance on the basis of "production costs" alone. There are several reasons why low production costs are not the only criterion.

When a department manager is led to believe that his chances for advancement—or even holding on to his job—rely primarily on his success in keeping costs down his efficiency becomes impaired. For one thing, errors in judgment are inevitable. If, in one department, the quality control is allowed to become lax to rush the work along to another department, the latter may make a comparatively poor showing because of the lower production standards.


It is safe to assert that costs do reflect managerial skill if the factors to be evaluated can be equalized. Some factors that do have some bearing on the size of production costs are the nature of production, degree of mechanization involved, stipulations of the labor contract, economic conditions, etc.

It is one thing to expect a department head to utilize effectively the productive capacity of the men and machines under him, keeping scrap production or rework at a minimum. If the necessity to keep the production lines going has resulted in unrealistic bidding or other practices by top management, the department head can't be expected to recover the losses that are inevitable. This would take a miracle.

The ideal situation at the department manager level is to provide them with the proper number of subordinates to allow them more time for instruction, control of individual performances and cost control. Managerial work is divisible, but if a department head must assume all the duties of planning, organizing, directing, controlling and coordinating then the least top management can do is to refrain from putting road blocks in his way.

PAUL A. MELINE Managing Editor now...over

standard Microbore boring bars from stock!



Your choice of over 330 Microbore standard single-tool or two-tool precision boring bars. A complete range of sizes and types available for boring and facing operations on any make of boring machine, milling machine or turret lathe. Microbore micrometer vernier adjustment of each tool point makes it possible to quickly set tools to precise dimensions. Boring range from 1/2" to 71/4" dia. Standard Boring Rings and Adapters extend range to 1334". Available with Straight Shank, NMTB Taper, Morse Taper or Flash-Change. Carbide, ceramic, or high speed steel cartridges. Ordering is Simple! Fast! Direct! Standardize on Microbore - the complete tooling system.



Catalog No. 58 lists industry's most complete line of standard general purpose precision bor-ing bars. Write for your copy.

Also available—special tooling designed from your part prints by our Proposal Engineering



DEVLIEG MICROBORE SYST



DEVLIEG MICROBORE

DIVISION OF DEVLIEG MACHINE COMPANY

An Interview with

Robert W. Galvin

President, Motorola, Inc.

Is the consumer a wiser buyer today? Dynamic, young Bob Galvin thinks he is and relates what's ahead in the electronics field for the general public and industry

By **Paul A. Meline** Managing Editor

Q. The financial pages report that consumer electronics products have made a strong comeback saleswise in the latter quarter of 1958. It appears that your company and your industry are giving the public more of what it wants. What have you to say about the trend of consumer wants that is taking place?

A. Probably the most significant



Significant today in the marketing world: the consumer ha

thing that has happened in our business in the last couple of years is that the consumer is a better informed buyer. The buyer has reached a new level of tastes.

In our case, we were able to add more value to our products in an area where people have become educated to want certain features. In the case of high fidelity, for example, many people discovered that there was a value or an enjoyment factor in really good music reproduction and that it could be acquired at a reasonable price. The situation that existed eight or ten years ago, was that there were phonographs on the

About Robert W. Galvin -

Born in Marshfield, Wis. on Oct. 9, 1922, Bob Galvin was raised in the Chicagoland area and attended the University of Notre Dame and the University of Chicago.

Bob has worked with Motorola Inc. since 1940. In 1949 he was elected executive vice president, and on Nov. 15, 1956 became president. He is a member of the board of directors.

One of his principal civic activi-

ties is the Junior Achievement of Chicago, a program that is national in scope, the purpose of which is to bring high school youngsters in direct contact with and actively operate small but real businesses. Bob Galvin is a trustee of the Illinois Institute of Technology and a member of the executive committee of Armour Research Foundation. He was chairman of the Republican Dinner in Chicago, held Jan. 20, 1958, an affair attended by President Eisenhower and 5,000 people.



Photographed at head table with President Eisenhower at the 1956 Republican Dinner in Chicago, Chairman Bob Galvin is busy directing activities.

higher level of tastes

market, but people didn't realize that there could be available good quality music reproduction for a fractionally higher price. The industry didn't realize that the customer was sufficiently educated to want anything better. We then all felt that the customer was only interested in certain average qualities.

We have since learned that the customer is more educated in the culture realm. A growing proportion of the buying public has learned also that, from a practical commerical standpoint, they can achieve culture at a reasonable price. This has added up to a value concept: the customer can get better music or in the case of television, better viewing pleasure. He can get a more reliable product for a marginal increase in price, which, because he is now better informed, he realizes is a better buy for him.

Q. Has this phenomena come about because of more informative advertising and sales promotion?

A. I think it is a broad gage phenomenon for which a lot of people deserve credit. I think that generally we have a more educated consumer today than we've ever had before. For one thing, more people are going further in school.



Bob Galvin and foreman observe television chassis on overhead conveyor prior to transfer to Franklin Park, Ill. branch for completion and assembly.

Advertising has played a significant role in upgrading the educational level and tastes of the American consumer, but I think it is as much a cultural revolution as it is anything else. I have often pointed to this little symbol: When has there been such an acceptance of the fact that the President of the United States paints in oils? People have just come to accept this as a good standard. I think that this acceptance, this willingness to go along, instead of playing down the culture aspect, relates to people who want better music in their homes.

Q. Would you say then that products with important fundamental improvements are the most effective means to create obsolescence?

A. The popularity of high fi-

Motorola is aware of the wisdom and potential in



"We are developing new techniques . . ."



". . . which we think may revolutionize the science of electronics."

delity reproduction demonstrated the public's interest in really good sounding music. The reason why stereo has increased interest in hi-fi, and the reason why stereo has been such a phenomenal success is that it provides a demonstrable, audible feature that the customer can understand and appreciate from the very first demonstration. It probably is one of the most demonstrable products our industry has had since television came along. Any person with two ears can hear a difference.

There are actually two answers to your questions about creating obsolescence. One, people who have good high fidelity equipment are getting an excellent value from it, and will continue to receive value for years to come.

Two, many people with good hi-fi equipment are impressed with the greater value of stereo to the point that they are willing to convert it, trade it, or supplement it with stereo equipment.

Q. I'd like to get your thinking on the place of the design and production engineer in industry Would you say that their importance is increasing? I ask this because it seems that in the past emphasis has been on sales promotion by way of frills and low price appeals.

A. All functional departments in our business or industry have always been important. However, the design and production engi-

oncentrating more on basic research



"With the fantastic achievements of miniaturization . . ."



". . . industry will be able to do more kinds of jobs electronically."

neer are playing a more prominent decision-making role in our product decisions than they have at any time in our history. They are very persuasive to the marketing department personnel. If they say a given product can be manufactured to a certain high standard only if we can put so much cost into it, the marketing department will be more persuaded to go in this recommended direction than if the engineers conversely say, "you can make a dollar out of your product and we will go the other way, but we don't recommend it." Therefore I would say that their status is higher.

Q. Regarding your research program at Motorola, has there been any trend toward emphasizing one area over another? I'm referring to such areas as development of new products, product improvement, fundamental research applicable to your industry and consumer attitudes.


A. The practice in our company, and probably in general throughout our industry up to a couple of years ago, was to concentrate research efforts in the direction of product development and improvement. However, in the last few years we have seen the wisdom and the potential in concentrating more on basic research. By this I don't mean just the exploring of any new field of science that comes to mind. We always have a definite target.

Price cutting? The consumer has demonstrated he wil

Q. What are some examples of your research efforts, significant to the metalworking industry?

A. The whole semi-conductor field, particularly transistors, is one of our important projects. We are working in this area with semi-conductor materials, and, of course, we have to develop all new techniques of assembly which require all new forms of machinery.

Another example is the development of new techniques which we think are going to revolutionize the science of electronics. The solid states electronics art is sort of an expansion or an extension of the semi-conductor art wherein we can make use of wholly new metal-like substances to achieve the same functions that were achieved by old-fashioned components a few years back.



Guidance system for the Terrier missile was developed and produced by Motorola, Inc.

pay more for quality

Now, this should be important someday to the whole metal working trades, in addition to the economy as a whole, because we probably achieve superior components, possibly some day at lower prices with a great deal more reliability. With the fantastic achievements of miniaturization, industry will also be able to do more kinds of jobs electronically than have been done before by pneumatic or mechanical means. I'm not referring solely to programming devices. The whole solid states electronics art is so new you are going to find many new applications of it. Undoubtedly we'll find ways of offering electronics service to the metalworking industry which today neither mechanical or electronics engineers are yet aware.

Q. From the general public angle, what are some of the developments in electronics that you anticipate will materialize in the next couple years?

A. The public as a customer is going to be the beneficiary of a number of new developments in electronics in the next couple of years. Many of these are built around the stereophonic phenomena. Already we have the stereophonic phonograph and records. Soon there will be magazine-



Industry's first practical, portable transistorized television set is exhibited by the president of the company that produced it.

load, cartridge-filled binaural tape players.

There are a number of laboratory efforts being made in the area of stereophonic radio broadcasting. This divides into two parts: the stereophonic broadcast over FM stations and the stereophonic broadcast over AM stations. We look forward to the time within the next couple of years when we will be manufacturing higher quality radios, somewhat more like the old console radios of some years ago, with excellent amplifiers and very high quality speaker systems; we will be picking up a single signal of one radio station but dividing it into two channels for a stereophonic effect.

Another stereophonic phenomenon that probably will be a practical and very desirable product will be stereophonic audio on TV. This we will achieve by the same techniques as stereophonic radio, but we will have two speakers. With a speaker on each side of the picture and different sounds coming out of each side, a three-dimensional effect is the result.

Then, of course, there is the potential which has been discussed for some years, yet looks like it's still many years off: picture on the wall television. It appears to have promise, but before that comes we will probably have transistorized television products, which will give us the characteristic of more portability.

Q. Every year the consumer has a wider choice of goods and services from which to select. Some manufacturers think this is a time for price cutting. What is your philosophy on this?

A. Our conclusion is that this is not a time for price cutting. We think the American consumer wants the very best product he can possibly get at a very high level or standard; they will pay for such a product if it's reasonably priced. The reason we have turned away from the philosophy of delivering the lowest priced

product is because the customer has demonstrated he is willing to pay an extra margin of ten or twenty dollars, or whatever it may be, in order to get a product that



Several months during the year Bob Galvin commutes 100 miles daily by helicopter from his Wisconsin residence to his office. Here he is taking off from the roof of the main office building with Billy Talbert, captain Davis Cup team

is more reliable, save him service costs and also gives him greater pleasure. The bulk of our public is not shopping as they were a few years ago for just the lowest price for any given standard of product. They are obviously shopping for the best competitive price, but not necessarily for the lowest price.

PROVEN! A SUPERIOR COOLING METHOD



1ST-1 LC

Used for -

- DRILLING
- MILLING
- BORING
- TAPPING
- GRINDING
- SAWING
- And all other types of machining

Let us engineer your cooling needs



- Outperforms all other cooling methods
- Extremely small precise nozzle
- · Simple cleaning and filling
- Precision air and liquid control
- Available with up to 10 outlets

MISTIC MIST GENERATORS—the most modern cooling method-saves time, labor and tool costs. It assures greater tool life, closer tolerances, better finishes and increased production. It's clean, simple to use and provides cooling for even the most difficult machining operations.

Centralized Mistic Mist Coolant Systems are also available for complete shop installations. Detailed information on request.

AETNA MFG. CO.

183 S. York Rd. Bensenville, III.

POrter 6-3810

THIS PART MACHINED

24% FASTER

from new Ledloy 170 tubing

This part for an automotive air suspension system was formerly machined at 131 s.f.m. from MT-1015 tubing. New Ledloy* 170 tubing increased machining speed by 24% to 163 s.f.m., giving a superior finish and extended tool life of 25%.

Ledloy 170 tubing is the world's fastest machining steel tubing—and only Ryerson has it available from stock. It's a cold-drawn, seamless product of low carbon analysis with .15% to .35% lead added. Sizes available to date: 1" to 2½" O.D. with maximum ¾" wall thickness.

Ask your Ryerson representative for complete details on Ledloy 170 tubing—and new Ledloy 375, world's fastest machining bar stock. These two newest additions to Ryerson stocks supplement the already large supply of screw steels and leaded alloys for all applications.

FREE-MACHINING STEELS IN STOCK

Ledioy* steels and screw stock—Ledioy 300 rounds to 4", squares to 1½" and hexes to 3". Ledioy 375 rounds to 1" and hexes to 3". Also on hand—all your requirements for C1213, MX1213, and leaded and non-leaded C1117 and C1141.

Carbon steel tubing—All the popular sizes and wall thicknesses used by automatic screw machine shops are ready for shipment, including new Ledloy 170 tubing.

Alley bars—Complete selection of leaded alloys, including Ryerson Rycut® steels—fastest machining in their carbon ranges.

Stainless bars and tubing—Here, too, our stocks are the nation's largest, including easy-machining Types 303 and 416 in rounds, hexagons and squares.

Carbon steel plates—New EZ-Cut®-lead-bearing plates (hat rolled, low carbon manganese).



RYERSON STEEL

Member of the TATE Steel Family

NATION'S MOST COMPLETE SERVICE . . . ON STEEL . . . ALUMINUM . . . PLASTICS . . . METALWORKING MACHINERY SERVICE CENTERS IN PRINCIPAL CITIES COAST TO COAST

MIST COCLING

By Paul A. Moline, Moncomo Editor

• Cooling with a mist in atomized form, discovered some years are as making gradual progress in metalworking operations. It is classified the cooling and lubricating all types of fabricating operations. In fact, it is making many operations practical that were formerly constant the possible.


The period has cooling is now used to define the use of course it must be unabled form. It is a method of supplying the latest cutting and grinding operations in a latest cutting and grinding operations in the atomic build is directed from a nozzle, with air to the cutting operation. Cooling of high speed it is never before possible, is now practical with mist cooling and has resulted in as much as 500 percent increase in

How It Works

The basic parts of a mist spray system include a liquid reservoir and air and liquid control valves with spray nozzles.

Mist is generated by a specially designed nozzle, using compressed air from the shop air line. The air, passing through the nozzle, creates a vacuum in the liquid line which siphons the coolant from the tank. There is no pressure in the tank. The coolant is instantly vaporized and forms a conical mist pattern.

The principle utilized in a home refrigerator is that gases expand within a coil to absorb heat inside the box.



Longer life for carbide tipped milling cutters has been reported by users of this Aetna Mistic Mist installation.




When a mist is employed.

Five cooling factors are present when water-coolant is entrained in an air stream and fed to a machin-

ing operation as a mist:

(1) Pressurized air, released thru a suitable orifice displays an elementary refrigeration principle; i.e., the temperature of compressed gas or air lowers as it is allowed to expand. Entrained liquid (a saturation of water-based coolant) supplements and increases the heat transferring ability of the cooling, expanding gas.

(2) The mist of the water base is the heat transfer medium.



The points of Trico mist generating nozzles are directed to the work by use of a magnetic base and adjustable arm.



Milling of non-ferrous material with a Precise Vapor Lub unit set-up.

cooling is on the tool and workpiece only, not the chips

(3) As the water content of the coolant is evaporated, the lubricating elements remain within the work zone in concentrated worm. If fed correctly, these elements penetrate to the interface of the chip and tool where they function in reducing friction, and thus, heat.

(4) Convectional cooling takes place as the water vapor is rapidly moved out of the work area by the

air stream.

(5) The water content of misted coolant is instantly evaporated by the heat of the machine operation.

With the mist spray directed at the cutting edge of the tool, the result is a cooling effect which cannot be equalled by any other method.


Heat absorption is dependent on pressure rather than volume. It is possible to do more with a small amount of high pressure than a wide stream of air at low pressure.

It is safe to say that 90 percent of all machining operations can be done in the average shop with mist cooling. As far as automatic screw machining operations are concerned, the run, of course, should be long enough to justify the time involved in setting up.

This method of cooling has many advantages over conventional methods of flood cooling. With the latter, heat is removed from the chips



Nozzle directs mist spray for single point turning tool from below.



Contour sawing is done without chips covering layout lines. Speed may be increased 50% without heating and with longer blade life.

and transferred to the liquid. When a mist is employed, cooling is on the tool and workpiece only, not the chips. Mist can remove heat from the tool as fast as the heat is generated. The nozzle can be placed so that the spray is directed to the underside of a curled chip.

Clean, uncontaminated coolant is always used. Coolant is not recirculated or reclaimed so pumps, filtering systems are not needed. Neither are coolant reservoirs necessary. The mess, usually associated with flood cooling, is eliminated with the result that the operator's hands and clothing remain dry. With splash guards unnecessary, the work can be loaded faster with improved visibility.

All that is required to put a mist method of cooling into operation is a simple hose connection from the air line and a supply of coolant. No regulator is needed, no pressure tanks, floor stands, filters, fittings or tubing. A magnetic nozzle holder makes location and adjustment of the mist simple and secure for temporary installations.

Advantages of Mist Cooling

Users of mist cooling report the following advantages with respect to various types of applications:

Drilling Machines—Chips are blown away from work and mist is forced down drill flutes to cutting edges. Deeper holes can be drilled without pull out. SURFACE GRINDERS—Reduces loading of wheels. Prevents breakdown of form-dressed wheels, checking of hardened steel, and prevents warpage of work.

Jic Borers—Eliminates haphazard brush application of coolant. Allows closer tolerances with better finishes.

ABRASIVE BELT GRINDERS—Reduces loading of belts. Work is kept cool.

TOOL ROOM LATHES—Allows heavier roughing cuts, finer finishes and closer tolerances without flooding the machine.

OFFHAND GRINDING AND SNAG-GING-Reduces wheel loading. Eliminates cooling in the water pot.

CONTOUR BAND SAWS—Keeps scribed lines free of chips for closer



Cooling of high speed dies, never before possible, is now practical. As much as 500% increase in die life is reported.

work, work is kept cool, allows higher blade velocity for faster cutting.

VERTICAL MILLS—Keeps cutter and work free of chips, produces better finishes with longer tool life.

Power Hack Saws—Increases blade life up to 80% over dry cutting.

Tapping—Blows chips from the tap. Supplies constant lubrication. Keeps taps cool. Taps hold size. Time required to drain and wipe tapped parts is saved. Speed increased 35%.

Boring Machines—Makes close tolerances easy to maintain since work does not heat up. Better finishes because coolant reaches tool.


PROGRESSIVE DIES AND DIEING MACHINES—Tremendous increase in parts per grind. Parts are burr free, galling and pick up eliminated or greatly reduced.

MILLING MACHINES—Increased cutter life. Carbide tipped cutters running too fast for flood can now be cooled and lubricated.

HAND SCREW MACHINES AND SEC-OND OPERATION MACHINES—Greater tool life, complete visibility of work, elimination of splash guards.

DIAMOND WHEELS—Wheel life increased a minimum of 100% over dry grinding. Complete visibility of work at all times. Wheels cut faster.

Internal Grinders—Greatly reduces loading of small mounted wheels. Keeps work cool and minimizes distortion.



Sc.ew adjustable nozzle of Lloyd Tool's Koolmist can be regulated with such a fine pin point mist spray it is invisible to naked eye.

The Central System

The established efficiency of individual installations has resulted in a gradual development of centralized coolant systems. Groups of machines are equipped with mist cooling, the coolant mixture being supplied from a single source.

Each machine is provided with a liquid and air control valve permanently mounted on the machine convenient to the operator. The operator has immediate, separate control of the air volume and moisture content of the mist at all times.

The coolant tank is mounted above the highest nozzle level, so that the coolant can be supplied from the tank to the control valves by gravity through permanently installed tubing or pipe. The air supply line is also permanently connected to the valves by tubing or pipe from the shop air line.

Practical Arbitration, Time Study and Work Simplification Part IV

How Do Work Standards Hold Up



2 Cases:

- 1. Increased Work Load Required of a Day Work Operator
- 2. New Inspection Rate Challenged
- · Because of the technical nature and the importance of work standards, companies and unions are usually cautious (a) about arbitrating standards and/or (b) about their selection of an arbiter once a decision has been made to arbitrate a standards dispute. In an increasing number of cases, parties to a work standards dispute are demanding that arbiters step out onto the production floor and gather their own data when there are wide differences in the data and claims made by both sides. Obviously, if a company feels this should be done (and the union

concurs), this arbiter time-study skill requirement should be made known to the American Arbitration Association or to the Federal Mediation and Conciliation Service at the time the parties request a list of suitable arbiters.

1. Increased Work Load Required of Day Work Operator

Issue: Is the Company right in asking its day-work screw machine operators to service two machines instead of one machine?

History and Background: This company makes screw machine parts for the air-airplane industry. Most of its steady repeat items are

in Arbitration ?

By **Harold R. Nissley**, P. E. Consulting Enginer

on incentive. However, the job in dispute is not a repeat item and hence is on day work.

The base pay for non-incentive operators is \$1.70 an hour. Good (normal) incentive operators average \$2.00 an hour. All incentive operators operate three machines. Day work operators tend but one machine.

The grievant operator in the present case does manual work during one-third of the manmachine cycle time. He loads his machine; he checks an occasional part for size and finish; and he replaces a filled tote pan. This consumes 3.5 minutes out of a total of 12 minutes per cycle.

Union's Position: Historically this has always been a onemachine-per-operator job. To ask an operator to take another machine without rewarding him corMr. Nissley discusses two work standards or incentive cases in the present article. Although these cases may differ from particular cases the reader has in mind, the methods of attack are worth studying for any person who may be interested in exposing his work measurement techniques to outside engineering scrutiny. Thus, if the reader has a work standards dispute going to arbitration, he might compare his "trump cards" with the "trumps" which follow.

respondingly is a speed-up of the rankest sort. Obviously, if an operator receives \$2.00 an hour for tending three machines, an operator tending two machine should receive at least \$1.85 an hour.

Company's Position: The Company rests its case on the provisions of the Labor-Management Agreement which says in part: "Employees are expected to give a fair day's work for a fair day's pay." And "Management reserves the right to set work standards for any job covered by this contract; and the Union has the right to grieve against any work standards which it deems unreasonable."

There are, therefore, two questions that should be answered before a decision can be rendered on the foregoing issue: (1) Does a work assignment which involves two-thirds of an operator's time

The arbiter was not asked to verify Company time-study figures

instead of one-third of his time constitute an *unreasonable* assignment? (2) Is \$1.70 an hour an oppressive wage for day work screw machine operators?

The Company points out that it never puts a job on incentive until the work content on that job approaches the effort and work content of jobs already on incentive. Indeed, in the present instance, the Company feels that it is grossly over-paying day-work operators (at \$1.70 an hour) when they exert themselves only one-third of the day.

But the hourly rate on this job is really not within the legitimate purview of the Arbiter. The hourly rate on this job is well covered by (a) the negotiated Job Evaluation Plan and (b) the latest Labor-Management Agreement. The Job Evaluation Plan which was adopted by the Company and the Union two years ago puts the screw machine operators in a Class III job classification. The current contract stipulates that all Class III jobs shall carry a base rate of \$1.70 an hour (see table of wage rates at the end of the Agreement). Thus, for the Arbiter to set any other rate on this job besides the \$1.70an-hour rate which the parties agreed to would be going outside

the province of this arbitration and would, in effect, be setting aside the contract. The real issue, then, is: Is the addition, of another machine bringing the operator's work load up to 2/3 of a day's work (instead of 1/3) "unreasonable"?

Arbiter's Opinion and Award: Many industrial engineers (and arbiters) have attempted to segregate work and money. They argue that a fair day's work is one thing; a fair day's wage is something else. This position has some merit. But its rigid application leads to as many misunderstandings as the separation of product and price in other matters. For example: One might say a new car buyer who just paid \$8,000 for a car got a bargain; but he could only say this after he learned more about the car (in this case, a new \$15,-000 Rolls Royce). In another instance one might think a car buver was gyped when he paid \$200 for a car (a 1947 convertible in poor condition).

The Arbiter was asked to decide: "Is the Company right in asking its day-work screw machine operators to service two machines instead of one machine?" Because the key word to the issue is "right" it might be well to focus attention on this word. Webster's New In-

out on the production floor


ternational Dictionary (1958 edition) offers the following synonyms for "right": "equitable; fair; true;

appropriate; faultless."

To be sure the present labormanagement agreement sets the day work or base rate for screw machine operators at \$1.70 an hour. Historically one screw machine operation has been accepted by the Company as "day work." Historically the operation of three screw machines by the Company has been considered incentive work. Historically, nothing has been done about 2-machine operation.

Because the equities in the present dispute are intimately tied up with wage rates the Arbiter cannot disregard this Siamese twin of the work-content and pay combination. The Arbiter, therefore, rejects the Company's claim that the wage rate for this job is outside his province in the present dispute. Indeed, there would be no dispute nor arbitration, if the wage rate were adjusted to the satisfaction of the grievant screw machine operator.

On the other hand, if the Union accepts the principle that 100% incentive effort should receive 100% incentive pay, then it is incongruous to say that 58% incentive effort (2 x 3.5 minutes divided by 12 minutes) should re-



". . . to grant relief to an operator exerting 2 percent less effort would be unfair."

ceive 92% of Incentive pay (\$1.85 divided by \$2.00).

If the Company had asked this screw machine operator to devote 90% or 95% of his available working time to physical or mental effort, then some relief would seem reasonable. But to grant relief to an operator who is exerting 42% less effort (100%-58%) than the effort exerted by normal incentive operators would be unfair in two respects: (1) The Company would be paying, in effect, 92c for a 58c item. (2) Other screw machine operators delivering 100% effort (operating 3 machines) would find it hard to rationalize a 92% incentive payment for 58% incentive effort (compared with their 100% over 7½ hours).

The Arbiter must, therefore, deny any relief to the grievant operator. The Arbiter's award is in favor of the Company.

2. The New Inspection Rate is Challenged

Issue: Is the new incentive rate for the RS Speed Reducer a proper rate?

History and Background: This Company manufactures a wide range of speed reducers (and transmissions). The small highly repetitive reducers are assembled on an assembly line. Each reducer is given exhaustive tests particularly after its final assembly.

The present dispute arose from the establishment of an incentive rate on the final inspection job of a new (high volume) reducer the company developed to meet domestic and foreign competition. The inspector is required to make many of the same tests that he makes on other (low-volume) speed reducers. But the high volume of the RS speed reducer justified the expense of some combination tools and special gages so that an inspector is now expected to inspect 70% more speed reducers than formerly.

The labor-management contract has this to say about incentives: "A normal incentive operator, working consistently through his shift at a normal incentive pace, will or should earn 30% incentive bonus over and above his base rate of pay." In another part of the contract there is this: "Work standards for incentive operators

will be set so that a normal operator working at incentive pace will earn, without undue strain or fatigue, 30% bonus above his base pay."

Union's Position: The inspector on this job is an old time inspector with over 10 years of inspection experience (5 years on final inspection of speed reducers). His average incentive earnings for the past two years, before he went onto this new job, has been 40%. But on this new job he can only earn 15% bonus. In other words the Company expects this man to do the same amount of work now for \$2.30 that he formerly did for \$2.80 an hour.

The Company will say that this inspector's earnings have dropped because he is not exerting himself fully. We say he is losing 50c an hour on this job for three reasons: (1) Unsteady flow of work thereby depriving him of incentive opportunities; (2) frequent rejects and re-works; and (3) tight work standards. We can and will document each of these claims.

Company's Position: The base rate on this job is \$2.00 an hour. An inspector exerting full incentive effort should, therefore, make \$2.60 an hour. So we are talking of a 30c hourly difference in this man's expected earnings and his

actual current earnings—not 50c an hour as the Union claims.

The Union says the flow of work is unsteady. Because this is a new model we have made extra provision for this by incorporating an extra (temporary) unavoidable delay allowance of 5% (24 minutes over an 8-hour shift). All of our incentive operators have downtime cards which they ring out whenever a delay of more than one minute occurs. During such down time the contract calls for paying a man his base pay-in this case \$2.00 an hour. A recent check of the down time on this final inspection job over an 8-hour period indicated the down time to be 15 minutes-not 24 minutes as we originally had estimated.

The Union complains about the number of rejects and re-works. We know the number of re-works is greater in most new models so we made another 10% allowance for this factor (48 minutes a day). On our recent 8 hour check we found it took 55 minutes for rejecting or re-working defective reducers on the RS model.

The Union claims that our work standard on this job is tight thus resulting in sharply decreased



earnings. We think we have leaned over backwards in setting the work standard on this job. We borrowed 30 elemental time values (out of a total of 45) from previous similar jobs; indeed, most of these 30 common elements were derived from time studies made on the grievant operator before he took his present RS inspection job. Only 15 non-comparable elements have newly established time values.

Thus we feel that this inspector is holding back until we loosen the piece rate on this job. Obviously, he is not putting forth the same effort as formerly, otherwise he would be making \$2.60 an hour instead of his present rate of \$2.30.1

¹Because of the disparities in the conclusions drawn by the parties in this case the writer welcomed the suggestion (by both parties) of stepping out onto the production floor and making his own time study observations. The first day of these 8-hour studies the writer clocked 30 minutes of down time compared with the Company allowance of 24 minutes); the second day disclosed 38 minutes of unavoidable delays. But the re-work

Arbiter's Opinion and Award: After each 8-hour time study by the Arbiter he asked the Company and Union representatives for their appraisal of the skill and effort demonstrated by the inspector during the 8-hour day (the Arbiter's observation sheet notations for this rating factor were in the 100% range). The Company estimates ranged between 85% and 95%; the Union estimates ranged between 110% and 120%. Hence the Arbiter's 100% rating was a trifle below the average of these widely differing ratings of the Company and Union representatives.

At the start of the time study observations the Arbiter asked the grievant inspector to call to the Arbiter's attention any unusual conditions, if and when they occurred. (The Arbiter had previously admonished the Company and Union representatives to do the same.) Only one unusual con-

dition was called to the Arbiter's attention during his two days of observations. One of the Union Stewards pointed out that according to the detailed Company elemental description the inspector should be using a fast-acting ratchet wrench for a difficult inside adjustment; instead the inspector was using a slow open-end wrench for this adjustment. When the Arbiter asked the inspector about this deviation from Company instructions his reply was: "Someone swiped my ratchet wrench and the Company refuses to furnish me with another."

Because the grievant inspector averaged only 16% bonus during the two days of time study observations by the Arbiter (in the presence of non-protesting Company and Union observers); because of the implied accuracy of the Arbiter's time study techniques and conclusions (due to his 99% agreement with the Company's 30 common or bench-mark elemental

times checked closely with the Companys 48 minute allowance for this item (45 minutes one day and 55 minutes the second day).

Of greater interest was the elemental time comparisons. Fortunately the writer followed the Company's element job breakdown. Although individual elemental times varied by as much as 25% in some of the 30 "borrowed" elements, the total of the writers 30 borrowed (or common) elements matched the Companys total for these same 30 elements by a surprising degree; the writer's total allowed time for these 30 elements was 15.27 minutes; the Companys allowed time for these elements as 15.41 minutes—a difference of about 1%. But the writer's allowed time for the other 15 elements was nearly twice the total allowed time of the Company!

times); because the Arbiter's production standard is 11% less than the Company's (due largely to the wide disparity between the Arbiter's allowed times for the 15 new elements compared with the Company's allowed times for the same 15 elements); for these and other reasons the Arbiter rules the new incentive rate for the RS speed Reducer is not a proper rate.

To convert the Company's new incentive rate for the RS speed Reducer into a proper rate under current operating conditions, the present rate on this job must be multiplied by 1.12 to bring it up to the contract level of 1.3 (or 130%) of the base rate. Thus, this 1.12 multiplier, if applied to the average 16% bonus earned during the two days of time study obser-



". . . to make the Company's new incentive rate a proper rate."

vations by the Arbiter, should yield a 30% bonus for those two days.

The Arbiter, therefore, awards in favor of the grievant operator.²

²A subsidiary consideration in this arbitration was the matter of retroactive pay for the grievant inspector. The contract was not clear on this point indeed, (the contract said nothing, directly, about retroactive pay for piece work operators). Moreover, the parties did not mention the matter of retroactive pay during their presentations; obviously it does not appear as an issue presented to the Arbiter. The Arbiter was, therefore, reluctant to bring up the matter of retroactive pay during the hearing lest the Company think he was prejudging the case. For these reasons the Arbiter did not include the matter of retroactive pay in his award. However, he was subsequently asked to rule on retroactivity. Here was his ruling:

Retroactive pay is due the grievant inspector. The amount of retroactive pay shall be calculated by multiplying his income during the dispute period by a factor of 0.12 which represents the difference between the 112% piece rate adjustment figure alluded to above and the 100% pay which the grievant actually received. The dispute period may be defined as the time between the first day the grievant worked on the RS Inspection job and the day the foregoing 1.12 adjustment in the present piece rate is put into effect (and shall include the first day on

the RS Inspection job).

Long Range Outlook for Man-Made Diamonds


Tangible evidence points to greater use of MD's

By **Chester A. Nisula**, Product Manager Simonds Abrasive Company

• Both laboratory and field tests have been conducted during the past year by Simonds Abrasive Co. to determine the comparative value of man made diamonds in relation to natural diamonds. Following the usual practice, the laboratory tests, under rigidly controlled conditions, came first. This was to give an indication as to what might be expected under production conditions in the field.

In our laboratory, surface grinding tests were conducted under completely automatic controls. Figure 3 illustrates the grinding machine, work piece and accessory equipment. On the surface grinder was placed a Type D1A1, 6 x % x 1% diamond wheel of the general specification D (or MD) 100-N100-B %. With flood coolant (120 to 1 soluble oil), this wheel ground a solid piece





Wheel Life Comparison

MD diamonds

D diamonds

1. Set-up for intermittent grinding tests to compare MD with D diamonds.

2. Curves are plotted volumetric wheel wear versus down feed as measure.

3. Set-up for grinding solid piece of carbide under automatic controls.



of carbide-surface to be ground measuring approximately 1-63/64 x 4-11/16. Traverse was on the shorter dimension and cross feed on the longer. In the comparison made between wheels, identical conditions of grinding (e.g., traverse, down feed, total down feed, cross feed, spindle speed and traverse speed) were used. Power consumption was recorded at all times. Wheel wear and material removed were determined. Thus, the variables were limited but easily measured. Data obtained was then converted or utilized in terms which are common to industry.

At this point it would be well to stress a most important fact. Since this test was under ideal conditions (no operator error, etc.), the actual values are not important. but the relative values obtained from MD (man-made) and D (natural) diamonds are. For example-if even under controlled conditions table speeds were changed, a completely different set of data would have been obtained. but the relative values of MD and D diamonds would be similar to those reported. Therefore, it was deemed best to show trends rather than actual data. Figure 2 shows the comparison made concerning wheel life. These curves are plotted volumetric wheel wear down feed as the measure of wheel life. Since at each and at all levels of down feed total down feed was

the same, volumetric wheel wear can be considered a measure of wheel life. The higher the wheel wear, the less the wheel life. Here it was noted that under conditions of the test, MD diamonds were superior to D diamonds when down feed was equal to or near the recommended level. General practice has dictated that down feed for 100 grit should be near 0.001" per pass. Under machine (positive) feeds as in these automatic grinding tests, this superiority continued up to 0.002" down feed. This observation indicated that under hand feeding conditions or when small pieces being ground, etc., the cross-over point of the two curves could move to the right 0.003" or 0.004" or more.

Similarly, if table speed were increased, the cross-over point could be moved to the left. Changes in other factors could also have similar effects. However, as down feed increases, grinding pressure on each individual diamond particle increases. Considering this fact, when observing Figure 3, leads to the observation that any condition leading to excessive pressure is detrimental to gaining maximum useful work out of a wheel containing MD diamonds. Of course, this is also true of D diamonds, but it is not as pronounced.

In any completely automatic grinding such as this, cutting ability (or rate of cutting) is re-

Questions and Answers about ELCIDE 75

Here's what you'll want to know about this new bacterial inhibitor for soluble oil emulsions:

What is Elcide 75?

Elcide 75 is a new bacterial inhibitor for standard duty soluble oil emulsions. Chemically, it is a combination of Sodium Ethylmercuri Thiosalicylate (Thimerosal) and Sodium *o*-phenylphenate in a concentrated solution.

What does Elcide 75 do?

Elcide 75 controls bacteria that contaminate soluble oil emulsions. Since both chemical ingredients are anti-bacterial agents, Elcide 75's double action controls a far wider range of bacteria than the commonly used germicides.

oil. And, because machines run longer between emulsion changes, production is increased proportionately.

Q: What is the exact dollar return from Elcide 75?

A: No exact figure can be established because conditions vary between plants. The type of metal, machines, and operations involved, the coolant, and general plant housekeeping are all factors that help determine savings due to Elcide 75. The best way to measure its value is to try Elcide 75 and compare the results with untreated machines in your plant.

Q: How is Elcide 75 used?

A: One ounce of Elcide 75 is added to each four gallons of emulsion. You know you have a safe, effective treatment because you control the dosage.







acteria like these can spoil emulsions. Elcide 75 stops their damage.

: Why is bacteria control important?

Bacteria enter emulsions through the air, water, and plant debris. They multiply rapidly and cause odor, corrosion, and premature emulsion breakdown. This compounded damage costs millions of dollars each year in higher maintenance and production costs. Bacteria control reduces these expenses.

How does Elcide 75 lower costs?

The use of Elcide 75 can increase emulsion life as much as 5½ times. You use less soluble oil. Fewer man-hours are spent servicing machines and disposing of waste

Q: Is more data available on Elcide 75?

A: Yes. Complete information on compatibility, disposal, stability, safety, and other pertinent factors is immediately available on written request.

Q: Where can I buy Elcide 75?

A: Elcide 75 is sold only through selected distributors. To place your order, or for the name of your nearest distributor, write Eli Lilly and Company, Agricultural and Industrial Products Division, Indianapolis 6, Indiana; or call MElrose 6-2211.

(Lilly's brand of bacterial inhibitor for cutting fluids)

Package Price per Gal.

1-gal. (4 per case), polyethylene...... \$8.50 5-gallon, polyethylene. \$8.00 55-gallon, stainless steel. \$6.50

ELCIDE 75

KEEPS COOLANTS FRESH AS A DAISY!

Lilly and company - agricultural and industrial products division - indianapolis 6, indiana

Regardless of the level of down feed, MD diamonds consume

flected in power consumption. Since total power was measured, and the power required for the machine was known, it was a simple matter to calculate the power consumed in actually removing carbide on each grinding pass. Reduced power consumption means that the wheel is cutting freer and faster. Higher power consumption means that cutting action is more harsh.

Figure 4 illustrates the comparative cutting ability of the two types of diamonds. Regardless of the level of down feed, MD diamonds consumed less power than did D diamonds. This indicates that in each case MD diamonds cut faster and cooler. Faster cutting and longer life may mean a more friable type of abrasive than D diamonds. (Such a comparison may be analogous to the difference between SA Borolon-a special refined, single crystal, white aluminum oxide, and WA Borolonwhite aluminum oxide.)

The lower power consumption, however, does not mean reduced carbide removal. Actually, MD diamonds removed more carbide on each grinding pass. This was illustrated when power consumption for clean-up passes was compared. A definite and marked reduction in power was required for the clean-up passes with MD diamonds.

This means less carbide remained to be removed after actual grinding passes with MD diamonds.

The reduced power consumption produces another very important result for any carbide consumer. The power used is consumed more in grinding than in developing heat. The less heat formed, the less the chances for cracking (or heat checking) of carbides. The combination of MD diamonds and the more recently developed aluminum powder-filled plastic core (for rapid transfer of heat) safeguards the carbide being ground.

The series of controlled grinding tests showed other characteristics which are of interest to diamond wheel consumers:

- 1. MD diamonds were easier to dress and to restore the wheel to true rotational form.
- Though not as important, MD diamonds consumed 1/5 to 1/7 as many dresser wheels as did D diamonds.
- The finish obtained on carbide at or near recommended feed with MD diamonds was equal to or better than D diamonds.
- As down feed increased, surface finish with MD diamonds became rougher than with D diamonds.
- Noise level of MD diamonds was lower than D diamonds.

ss power than D diamonds

Many consumers use such a property as a measure of cutting action.

- Because more power was converted to useful work with MD diamonds, the resin bond did not char as readily as with D diamonds.
- 7. This test included down feeds far beyond what was recommended in order to simulate the extreme of completely off-hand grinding. Based on this test, it appears that of all grinding operations, MD diamonds have the least chance of success on off-hand operations.

With the laboratory tests out of the way, it was desirable to check these findings under production conditions. Fortunately, it was possible to conduct the field tests in a number of plants and tool shops where conditions were varied. Some of these production grinding tests were very detailed but in order to protect these consumers' production data, the reports are in terms of number of pieces or percentage figures. Once again the important thing is the comparison, not the actual data. It should be mentioned. however, that the wheels containing D diamonds were from several vendors including ourselves. Those containing MD diamonds were of Simonds Cutting Ability

D diamonds

MD diamonds

Down Feed-increases

4. Comparative cutting ability of the two types of diamonds, MD and D.

Abrasive manufacture.

One of the earliest tests conducted utilized a tool and cutter grinder. The general wet grinding specification of D180-N100-B ½ was used. For this grit size we normally recommend that down feed be 0.0005" per pass. This consumer normally used more than was recommended. In fact, various feeds on the numerous shapes being ground were used in the following production evaluation. Table I illustrates the results.

Table 1 definitely confirms the laboratory tests that MD diamonds are superior when used at or near the recommended down feed. Yet when down feed increases, the limitations of MD diamonds be-

MAN-MADE DIAMONDS continued

come apparent very readily.

Some typical performance reports on man-made diamond wheels in resinoid and vitrified bonds are shown in Table 2.

This merely serves to illustrate that one or another property of a new product can be used to benefit the profit picture of any sound organization.

Another test report was obtained where no vendor or consumer company staff member personally Table 1 Effect of Down Feed on Wheel Life

Down Feed Life D Dia. MD Dia. 0.0010 100 207 0.0025 100* 153 100° 0.0025107 0.0030 100 138 0.0035 100 127 100 0.0045 80 100 0.008 54 *Note: Not the same wheel


,

	TABLE 2	
Source New England textile wind- ing machine manufacturer	Operation Sharpening carbide-tipped large cutters	Wheel Specifications MD120-M75-B 1/4, Shape D11V9 5" x 11/4" x 11/4"
Comment: 75 concentration M	ID equals 100 concentration di	iamond.
Detroit cutting tool manu- facturer	Sharpening carbide-tipped reamers and drills	MD150-R100-B 1/16 Shape D11V9 5" x 1¼" x 1¼"
Comment: Longer life than n	atural diamond wheel.	
Michigan cutting tool manu- facturer	Sharpening solid carbide keyway cutters and end mills	
Comment: Superior to natural	diamond wheels.	
Los Angeles saw sharpening shop	Resharpening carbide-tipped circular saws. All-over grind, two sides and top.	MD180-N100-B % Shape D11V9 5" x 1%" x 1%"
Comment: Sharpened 45% m	ore tips than natural diamond	wheels.
New Jersey laminating die manufacturer	Internal grinding carbide dies	MD180-N100-B 1/8 Shape D1A1 11/2" x 1/4" x 1/4"
Comment: Longer life and fa	ster cutting than natural diame	ond wheel of same size.
Midwest farm implement manufacturer	Sharpening carbide-tipped cutters	MD320-N100-B 1/16 Shape D11V9 5" x 134" x 114"

observed the grinding operation of carbide resharpening. The foreman gathered the weekly production reports of wheels containing MD and D diamonds. Wheels containing these two types of diamonds were used alternately, with the operators involved having no idea of the difference. This meant that down feed could vary as could all other variables (however, the operator was not on incentive pay). Here MD diamonds in resinoid and vitrilonger life than did D diamonds.

All of the above results serves to illustrate that, properly used, MD diamonds in resinoid and vitrified bond are superior to natural diamonds. Wherever this superiority has not shown up, the reason in each case has been the sameexcessive pressure on each diamond particle. In one sense, it makes no difference to the manufacturer: he has both available. On the other hand, each manufacturer is interested in giving his customers the product which will produce the best results. Properly used, MD diamonds will put money into any user's pocket.

Because of the original laboratory tests, the value of 75 concentration MD diamonds also was considered. To satisfy this curiosity, a similar controlled and automatic laboratory grinding test was conducted. This time it was felt that intermittent cuts would be more conclusive. Figure 1 shows the "work" set up for this test. It must be mentioned that the traverse across each of the three pieces was such,



5. Wheel cost as determined by dollars

that the time between the beginning and the end of each traverse before and after each piece was the same as between each piece. Wheel size and other grinding conditions were for all practical purposes the same as the previous test.


per cubic inch of carbide removed.

Since the economical factor of wheel cost now comes into the picture, we do not present life in terms of loss of wheel volume loss but wheel cost as determined by dollars per cubic inch of carbide removed. Figure 5 illustrates this. Note that under the conditions of this test, based on wheel cost alone, it may or may not be more economical to use 75 concentration MD diamonds rather than 100 concentration D diamonds. This test, once again, utilized 100 grit dia-

monds-general wet grinding grade (N). We should note, in all fairness, that at the recommended down feed in this controlled test. 100 concentration D diamonds proved superior. As down feed increased, for an interval, wheel life with MD diamonds definitely increased. Once again we must say that this period of improvement in wheel life can vary from operation to operation. Yet wheel life cannot be the only criterion when cutting ability of the two types of diamonds and the two concentrations are considered.

Figure 6 shows one of the most amazing grinding characteristics our laboratory has ever seen. After reducing diamond concentration to 75 with MD diamonds and comparing with 100 concentration D diamonds, the former proved to be freer and faster cutting. This is illustrated by power consumption (for grinding purposes only) per pass of MD100-N75-B % and D-100-N-100 B %. The only explanation that can be given for the freer and faster cutting rate of 75 concentration MD diamonds over 100 concentration D diamonds is that under intermittent cut or down feeds of short duration the more friable characteristic of the former prevails. The wider spacing of MD diamonds seems to give each friable particle more chance to function efficiently. This does not infer that 50 concentration MD diamonds would be even better than 100 concentration D diamonds. As a matter of opinion. this would probably not be true.

To date, field tests of 75 MD diamonds versus 100 concentration D diamonds have not been too conclusive. In cases where pressures have been very excessively



6. MD diamonds (75 concentration) proved to be freer and faster cutting compared to 100 concentration D diamonds.

over recommended, 75 concentration MD diamonds have not been superior. Yet, reports have also been received where 75 concentration MD diamonds have proven equal to or better than life and cutting ability of D diamonds.

The user, of course, is the final judge of the value of any product to him; only he is really in position to judge the weight of the various factors which he uses in selecting diamond wheels.

NOW...you can get

TYPE NO. O1 (A.I.S.I. or S.A.E. ANALYSIS)

FLAT GROUND DIE STEEL

from SIMONDS

For tool makers, die shops and machinists who prefer or who have standardized on Type No. 01 Oil Hardening Steel, SIMONDS now offers the most complete range of stock sizes in flats and squares made from Simonds own steel of No. 01 chemical analysis.*

Precision ground and ready-to-use, all "1001" sizes are accurate and uniform in dimension and and ends finished and squared. Heat treatment is simple and foolproof, with excellent results assured. Best of all, you can get delivery now of No. 01 Type as well as Air Hardening and Low Carbon Type Flat Ground Steel from Simonds distributors' stocks backed up by Simonds warehouse stocks in Boston, Newark, N. J., Detroit, Chicago, Shreveport, La., Los Angeles, San Francisco





Use postpaid card. Circle No. 289

GRAINED, FORGING & SILICON KILLED STEEL

REPORT FROM W. GERMANY

Gear Shaper Chamfers



1. Slide gear showing the shape of chamfer.

By J. Siegfried Spizig, Koln, West Germany


• The teeth of the transmission slide gear of Fig. 1 have to be chamfered approximately 45 deg. on the open face, to facilitate shifting. This is performed during the conventional gear shaping process by a special milling attachment. The generated teeth pass a plain milling cutter, positioned 90 degrees off-set to the disk cutter, as shown on Fig. 3. By this equipment the burr—generated in the shifter groove during shaping—will be removed continuously.


After a further quarter of a turn the first generated tooth terminates at the corner-rounding end mill opposite to the disk cutter. (See Fig. 3) The mill is then advanced by a hydraulically operated slide and locked in cutting position. A synchronized cam, driven by change gears to the work spindle, provides an up-and-down movement of the chamfer-cutter. The drive comes from the flexible shaft, coupled to an electric motor.

The time saving features of the chamfer and deburring attachments may be justified by the diagram, Fig. 4. Only a quarter of rotation more is required versus a normal gear shaping operation with a rough and finish cut. The latest quarter of turn, with only the deburr cutter in operation, will be rotated rapidly. Chamfering is al-

ind Deburrs, Too

2. Gear shaper with automatic loader.





3. Tool layout with shaping cutter, corner-rounding mill and plain mill in operation.


ready finished after a half rotation behind the rough cut.

Other significant savings include:

- Part handling to chamfer and deburr the gear is eliminated.
- Floor space of two additional machines is saved.
- The built-in features costs only a fraction of the cost of machinery

necessary to perform the combined operations separately.

With the automatic load and unload equipment, shown in Fig. 2, the gear shaper is a machine of high economy. It is possible to process other gears on the gear shaper or to have any attachment idle if necessary.



4. Cycles of the three cutters.



Illustrated-Logansquare Cylinder

the ultimate in air cylinder design



FREE SEND FOR THE "LOGAN CALCULATOR"

MEMBER: Natt. Mach. Tool Builders'

	100
PLEASE SEND COPY OF CATA 100.1 AIR CYLINDES 100.2 MILLITYPE AIR CYLS. 100.3 AIR OPAULIC CYLS. 1100.4 AIR VALVES 1100.5 LOGANDOLARE CYLINDES 110.5 LUCHAMATION CYLINDES 110.2 PRESSES 120.2 PRESSES 120.2 PRESSES	700.1 HYD. POWER UNITS 200.2 ROTOCAST HYD CUINDERS 200.3 750 SERIES HYD. CUINDERS 200.4 and 200.7 HYD. VALVES 200.4 and 200.7 HYD. VALVES 200.5 UPSER MATIC CYLS. 200.5 UPSER MATIC CYLS. ABC BOOKLET CIRCUIT RIDER
to:	
NAME	TITLE

Use postpaid card. Circle No. 290

Meets J.I.C. Standards

AUTOMATIC COMPENSATION FOR MISALIGNMENT WITH EMPIRE FLOATING TOOL HOLDERS AND TAP HOLDERS

Check These Exclusive Empire Floating Tool Holder Features:

- Automatically compensates for both angular and parallel misalignment.
- Eliminates bell mouthed and over-sized holes—permits extremely close tolerance work.
- Free and easy movement . . . tool holder sleeve and shank float independently of each other.
- Amount of float is infinitely adjustable.
- Smoother running . . . moving parts ride on rollers.
- Minimum of maintenance...holder has only five parts.






Standard equipment with leading Machine Tool Manufacturers. Tool Holders and Tap Holders are available with either straight or tapered shanks.

Check These Exclusive Empire Floating Tap Holder Features:

- Automatically corrects parallel and angular misalignment.
- Designed to prevent freezing under tension taps float in and out.
- Wide range of float—simple adjustment locknut provides accurate control of degree of float.
- No springs or pivot members to restrict float.
- Floatation feature makes it easier to hold close tolerances.

MPIRE TOOL COMPANY

Use postpaid card, Circle No. 291



 Smaller and lighter seals give cooler operation.
 Courtesy Garlock Packing Co.

Proper Care of Oil Seals

Oil seals are bearings and must be lubricated

Special to Machine & Tool Blue Book

• First, consider how an oil seal works. It is a device with a flexible member held in close contact under spring load against a rotating shaft. Inasmuch as the spring creates a load, the unit as a whole becomes a bearing.

This bearing is really a rather unique product. Unlike a normal bearing it does not have a fixed inside diameter. It has no running clearance. It has no provision for generating its own oil film. In fact this bearing must be designed to minimize the thickness of any film; otherwise, this film will carry too much oil out past the seal resulting

in excessive leakage.

Considerable work has been done with oil films and when one considers them in relation to oil seals, it is usual to imagine them as quite thick, especially if the 0:1 seems to be "pouring" through. Quite frankly the actual figure is not known. Attempts to apply Poiseuille's law of fluid flow to a seal would indicate clearances so small that we might say that they must be on the order of a molecule or two thick. Yet this cannot be or our seal would be quickly destroyed; thus one must follow an uncharted course of research.

The oil film must be of reason-

able thickness to insure satisfactory operation of the seal as a bearing. Yet the film must not be too thick or leakage would be severe. A narrow line of bearing means less gross drag and less heat, but it also means a thinner film and more careful control. Broad contact may be all right for slow speed jobs, but even here a heavier film is likely to develop which is in the presence of fine foreign material may mean the entrance of dirt and attendant wear.

Friction

Speaking of friction often raises the question of the co-efficient of friction of various materials. When applied to an oil seal this means little for a dry seal would not even come up to speed.

There must be at least a reasonable resemblance to fluid film lubrication or the end is at hand. The amount of friction is clearly a summation of several factors; first and foremost-the lubricant, then its temperature. Important also are shaft finish and seal finish. Seal finish is taken care of quite rapidly in the case of synthetics, provided that the shaft is not so rough as to cause excessive seal wear. The seal under normal circumstances, therefore, is quickly polished to a good bearing. Given time enough, the shaft too, is polished. With this latter combination optimum conditions are realized.

Having established good bearing conditions, this bearing must not let the shaft move radially from its own bear-



ing contact, Not that the seal should in any wise attempt to restrain the shaft, but rather that the seal should freely float with the shaft. This requires a flexible seal, flexibility but not softness for soft materials are not particularly good bearing materials.

Care of Seals

In considering the aspects of a seal, as a bearing, it should be realized that the seals should be handled as one. Great care is exercised not to scratch the mirror-like finish of the sleeve bearing. Care is taken to keep roller bearings clean. The seals should receive no less attention. No doubt the greatest problem lies in handling and installing the seals. In the storeroom they should not be laid on the floor, sooner or later to be stepped on and most assuredly to become full of dirt, nor should they be hung on a peg on the wall. When they are driven into the recess in the chock a good clean square edge piece of wood of fair size should be used. The actual driving should be a slow and easy job thus avoiding serious distortions or damaged lips or springs. The shaft should be smooth. The smoother the shaft, the better the seal type bearing will perform. Initial lubrication is not to be overlooked. Burrs or dents are still further by-passes, And as for helical lead or thread from machining here indeed can be an excellent pump.

Lubrication

As a bearing the seal requires lubication. With a single seal this is adequately handled by the lubricant from the bearing itself. The more critical job is where two seals are used. It has been customary to introduce lubricants between the two seals. This plan, if



set up and carefully followed, is a most important step toward obtaining reasonable seal life. Originally grease was injected between the seals at periodic intervals. On the older slow speed mills this is fairly satisfactory. There is an important consideration, however, namely: lubricant so fed to the seals will also find its way into the bearing lubricant, thus the lubricant injected should be the same as that used in bearings.

If a sleeve type bearing with oil lubrication is used, then feed oil to the seals. Should roller bearings be used with grease lubrication, then feed grease. This avoids contamination of valuable high grade bearing lubricants and yet insures the lubrication of the seals. It has been indicated that the

so-called slow speed mill set-ups are improved by seal lubrication. This is so, And if one considers some of the newer high speed mills, one would quickly learn that seal life would be very short if auxiliary lubrication were not supplied. Today, there are some oil lubricated high speed mills which have a separate oil pump metering a trace of oil to the seals continuously. This is indeed taking full recognition of the fact that oil seals are bearings and must be lubricated.

Bearing Materials

In bearing design there is a wide choice of materials available, so that with all factors fully known quite logical selection is possible with very good assurance of satisfactory results.

ONE OF ENGLAND'S FINEST!

CVA 3 JAW GEARED UNIVERSAL SCROLL

WITH AVERAGE GUAPANTEED ACCURACY OF .002" THREE INCHES FROM JAW FACE

. . And these other great features

ONE PIECE BODY
FLAME HARDENED JAW WAYS
INDUCTION HARDENED SCROLL FORM
COMPLETE WITH 2 SETS OF JAWS
AND CHUCK WRENCH

Size	Weight	Dia. of bore	Price*
31/2"	6 lbs.	56"	\$34.00
41/2"	6 lbs.	1-1/8"	34.00
51/2"	11 lbs.	1-1/2"	40.00
61/2"	16 lbs.	1-11/16"	46.50
72/2	26 lbs.	2-1/4"	55.00
9"	38 lbs.	2-3/4"	70.00
101/2"	68 lbs.	3-1/2"	86.00
12.	106 lbs.	3-7/8"	115.00

*Prices f.o.b. warehouse, N.Y.C. Back plates available at extra cost.



These are superior chucks produced by an English manufacturer famous for precision built machine tools and represent unbeatable values. A certificate is supplied with every chuck attesting to and guaranteeing its accuracy. All parts are quaranteed for a year against delective workmanship and materials. Repair parts available.

In stock for immediate delivery!

Manhattan Supply Company
151-A Grand Street, New York 13, N. Y.
Telephone CAnal 6-4992

WIDE APPLICATION

New jobs are being found every day for R-O equipment. Once difficult and highly special work is done faster and inexpensively with this standard fixture and grinder.



Form relieve reamers



Internal form relief grinding



Relieving forms on side cutting tools



Form relieving step drills



Form relieving gun drills



Sharpen tap chamfers with cam relief



Grind hexes. squares, flats



Grind cams and ellipsis



Form relieve small tools

UNIVERSAL FORM RELIEVING FIXTURE

R-O Grinder

GRINDER DIVISION Royal Oak Tool and Machine Co.

29800 Stephenson Hwy.

Royal Oak, Mich.

Please forward the R-O catalog.

Address

City Zone State

Per

Use postpaid card. Circle No. 1a

WHEREVER YOU TURN ...

WHATEVER YOU TURN ...

BALAS COLLETS and PUSHERS





Regardless of the type of automatic, lathe or milling machine you operate, it will work better...turn out a higher quality product when equipped with a Balas Collet or Pusher.

Regardless of the type or shape of stock you use, there's a Balas Callet or Pusher that will hold or feed it to perfection.

You get the greatest production results from Balas equipped machines because highly specialized design, engineering and production have combined to produce the finest tools at the lowest cost.

Master Collets, Conventional Collets, Master Pushers and Conventional Pushers in popular sizes for most machines are available for immediate shipment. Write for catalog and price list.

BALAS

COLLET MANUFACTURING CO.
CLEVELAND 14, OHIO

Most bearings combine two hard materials. Usually one of these hard materials is supported in a deformable matrix such as babbitt except, of course, in the case of anti-friction bearings, or in the case of some marine strut bearings, where a soft rubber sleeve does the job. The latter case does involve a unique lubrication job with water in large volume to absolutely guarantee that there shall be no dry contact: this requires unusual design. By comparison the oil seal quickly falls into the class of a plain bearing, lubricated through capillary action by any fluid such as may be present.

It has been found that flexibility gained through softness is dangerous; an oil seal must operate on such a thin film of lubricant that failure of the film for an instant may result in seizure. A harder stock is more nearly free of this, Flexibility must, therefore,

be gained by cross section design. (Fig. 2.) Through the moldability of synthetics, it is possible to design the lip section to suit this theory, and in addition to gains in flexibility it is possible to control and restrict bearing contact. This latter step is almost impossible with leather,

Wear

A seal operating as a bearing will scarcely more than polish a shaft. Wear of the shaft is invariably the result of foreign material getting under the sealing lip. The nature of this wear is a lapping action, wherein the seal acts as a carrier for the abrasive. There have been some isolated cases of element wear not attributable to shaft roughness.

The cause of this wear has not been determined definitely but it appears to be due to the quantity and type

INDEXING MACHINERY — CAMS — GENEVA GEARS — TURNTABLES

EISLER MAKES OVER 300 DIFFERENT TYPES OF INDEXING TURNTABLES. SPECIAL MADE TO YOUR SPECS. WRITE FOR CATALOG.





Dr. Charles Eisler Me. Founder Charles Eisler, Jr. Pres.


EISLER ENGINEERING CO., INC.
762 SOUTH 13th STREET NEWARK 3, NEW JERSEY

OIL SEALS continued

of foreign material. Coarse material seems to be worse than fine dust or powder. All wear is actually, therefore, the result of seal failure: neither sufficiently close contact, nor a thin enough oil film was maintained and dirt en-

The best solution lies in a thin film at the tip of the lip. Any curling away from the shaft, any fuzziness on the dirt side of the seal offers the necessary opening for wear to set in. In this respect, the finger spring either alone or supplemented by a coil spring.

The proper seal properly installed will give long service without repairs or replacements. There have been many improvements incorporated in such seals and vet it has not been necessary to rebuild or modify the bearing chocks, for the basic dimensions of these seals, although compact, still leave room for new improvements to be incorporated.



2. The flexibility in the seal should come from the crosssectional design.


HEATS FAST SAVES TIME

NUMBER 142 HEAT TREATING FURNACE

Powerful burners in this efficient furnace get heat up to the 1300°-2350° F, range in minutes. Temperatures accurately and quickly regulated. Does fast job with high speed and carbon steels. Ratchet-operated door opens upward. High temperature, refractory-lined firebox is 7" by 13" by 16½". 200,000 BTUs per hour. Carbo-frax hearth, G.E. Motor and Johnson Blower included, F.O.B. Factory....\$358.00 Write today for free Johnson Catalog

JOHNSON GAS APPLIANCE COMPANY 570 E Avenue NW, Cedar Rapids, lawa





Tape Controlled Combination Machine for Small Lot Manufacturer

MILWAUKEE—A new tape-controlled combination machine, the KTNC Milwaukee-Matic, performs milling, drilling, reaming, tapping, and boring operations, thereby reducing setup time, production time, labor costs, and inventory.

By minimizing setup and positioning time and by combining milling, drilling, reaming, tapping, and boring functions in a single machine, the machine can be kept in operation "well over 75 percent of the time," according to Francis J. Trecker, president of Kearney & Trecker Corp.

As many as 31 different tools can be loaded into the machine at one time—30 in a specially designed revolving tool storage drum and one in the spindle. There are 31 different combinations of 31 tools, ranging in size up to 2% inches in diameter, that can be utilized by the machine, making a total of 961 tools.

To make tool changes, a transfer arm automatically pivots out from its posi-

tion beside the drum, simultaneously removes the tool from the spindle and a new tool from the tool storage drum, rotates, simultaneously inserts the new tool in the spindle and the other in the drum, and returns to its normal position. Less than nine seconds are re-

quired for tool changes.

The General Electric control system makes the tool selection and directs the workpiece transfer. If the programmed tool has not been loaded into the drum by the operator, the drum will continue to revolve until it is stopped and the proper tool is inserted. Engineers pointed out that tools carry a binary code and can be placed at any position within the drum regardless of the sequence in which they are to be used. Mechanical "fingers" feel the tools and signal the control to stop the drum when the desired tool is in position to be removed by the transfer arm.

In operation, the worktable is automatically indexed to present workpiece surfaces to the spindle. The spindle moves longitudinally, vertically, and to depth. Feed rates range from 1 to 99 inches per minute and are selected in increments of 1 ipm. Spindle speeds from 100 to 4,000 revolutions per minute are selected in increments of 10 rpm.

As the spindle is used for tapping, a complete reversal requires 0.1 second at 100 rpm and 0.4 seconds at 400 rpm. Acceleration of the feed drives to 100 ipm is accomplished in 0.05 seconds. Where feed rates are not specified, posi-

tioning is done at 200 ipm.

The new control system not only directs positioning of the work table and three-axis spindle; it also controls tool selection, tool changing, spindle speed, feed rate, and auxiliary functions such as turning coolant on and off and shuttle work pallet between index table and load and unload stations.

Slope and arc cutting can also be performed by the machine. This feature does not introduce control complexity. nor difficult tape preparation problems

requiring computers.

The machine will perform circular cutting of radii from 0.1 to 9.9 inches in radius increments of 0.1 inch. The maximum error on arc milling is plus or minus two percent of arc length. Maximum speed for arc and slope cutting is 30 ipm for radii between 0.5 and



Rotary tool magazine loaded with 30 all different cutting tools . . . from shell end mills to boring tools to taps, each chucked in a coded holder. The tool change arm is shown here in parked position. The tool selection reader head can be seen at the left next to the shell end mill.

9.9 inches. According to design engineers the control permits users to mill clearances, "walk" around joint faces, and perform similar jobs where high

accuracy is not required.

First step in processing a part for the machine consists of listing dimensions, machining sequences and auxiliary functions on a simplified planning sheet. To do this, the engineer or technician takes the necessary information from an ordinary blueprint. Then a typist, using a standard typewriter-tape punch, transcribes the planning sheet data. To provide a visual check of the accuracy of the transcription, corresponding numbers are typed onto the planning sheet at the same time they are being punched into the one-inch, eight-channel input tape.

After checking the typed numbers against those originally placed on the

planning sheet, the tape is ready for use. If corrections are necessary, tapes can be readily duplicated with only the changed data requiring attention.

At the machine, tape is read by a standard mechanical tape reader. The control system is equipped with dual storage registers to eliminate any loss of machine time while tape is being read.

A push of a button is all that is required to put the versatile combination machine into operation. Once started, it will continue to function automatically until the programmed job is completed. While the machine is in operation, the operator is free to prepare the next workpiece for production and to select the necessary tools required if a new part is to be machined. This makes possible a complete change-over in minimum time.



Check Involute Profiles On Gears From 0-20" Dia.

with a Mahr 890

Error Magnification 500 and 1000 X

A precision-built, highly sensitive instrument, the Mahr 890 Gear Checking Machine checks involute tooth flank profiles on spur and helical gears (both external and internal), bevel gears and worm gears.

Reduced Testing Time—provided by an infinitely variable, optical, base circle setting for gear diameters from 0-20"—with no need for base circle discs.

Accuracy—guaranteed by an extremely sensitive, shock-proof stylus and a recording magnification of 500 and 1000 X. Involute charts can be selected in ratios of 1:1, 2:1 and 4:1. Dust-protected, ball-bearing guides and chromium-plated guide ways assure smooth, low-friction operation.

Range—pitches from DP 1½ to DP 50 can be inspected with standard gaging points. Surface finish can also be checked and recorded easily with a knife-edge gaging point.

Write For More Information

COSA


 nationwide sales and service of precision machine tools from bench lathes to boring mills.

COSA CORPORATION, 405 LEXINGTON AVENUE, NEW YORK 17, N. Y. Use postpaid card. Circle No. 298


How Pitney-Bowes Cuts Gaging Costs

STAMFORD, CONN.—Impressive savings in gage inventory and gage design time have resulted at Pitney-Bowes, Inc., makers of postage meters and business machines, from the use of a basic indicating gage unit to which can be attached various anvils and jaws to suit differing sizes and shapes of parts to be measured. Called Versa-Dial, this unit is a product of Standard Gage Co., Inc., Poughkeepsie, N.Y.

The entire general practice at PB was changed, starting three years ago, from using many gages, each good for only a single dimension, to that of using a relatively small number of these versatile units. In addition to cutting gage inventory the present sys-



1. Anvil for checking longitudinal spacing of grooves.



2. Rods with contacts which can be clamped on anvils.

tem affords quantitative measurements against only the go or no-go answers of the limit gages previously used. Versa-Dials are easily set up for parts as they are started in production.

In practice, 20 of these dial units and a variety of anvils take the place of what under the previous system would be 200 special, single-dimension gages. At PB the attaching anvils are made versatile as well as the indicating unit through a study of their various requirements and designs of anvils which permit adjustment.

Parts gaged include shafts with narrow annular grooves—the separation between grooves being important; rods with critical dimension from the center of a cross hole to a shoulder, and gears with a specified concentricity of pitch diameter and center hole. Most of the inspection is carried out while the parts are in process throughout the plant, thereby disclosing any out-of-tolerance conditions before they entail much scrap. (See illustration).

By far the most common type of measurement is that of the shafts with longitudinal spacing of the grooves specified to a total tolerance of .003" on the average. There are about 100 such dimensions differing from each



Test-checking cross hole locations in shafts.

other as to shaft diameter, groove spacing, or both, PB has covered all of these with only three pairs of anvils which have vees to locate on the rod and leaves protruding within the vees to enter the groove. (See Fig. 1) Each pair of anvils covers a range of rod diameters and their range as a group is from .040" to 13%".

The gage is set by inserting gage blocks between the vees or even by miking over the vees, proper allowance being made for the thickness of the vees and of the leaf, if necessary, The thickness of the vees is made to the same dimension within .0001" tolerance for all three pairs of anvils to permit and facilitate this method of setting.

Another type of measurement is that between a cross hole in a rod and a shoulder. For such gaging the unit is set up with one of the anvils described above, the other anvil carrying a pin to go in the cross hole.

Pitch radius of gears is measured by using specially designed anvils one of which carries vees for the accurate location of the gear shaft while still permitting its rotation. The other anvil carries a precision wire for contacting between teeth. Thus the gear can be merely rotated and checked at different points for being within the .002" tolerance.

PB's reports having set up Versa-Dials in short order for jobs which have arisen unexpectedly and which formerly would have involved delays of several days at best. An example of the versatility obtained by PB is the pair of anvils shown on the Versa-Dial in Fig. 2. These are for checking internal or external undercuts and take any of various rods fitted with special contacts on their ends.





THE CAPEWELL MFG. CO. HARTFORD T. CONN.


Grease Gun Barrel Production Upped 200%

Omaha Steel Works of Omaha, Nebraska, is machining grease gun barrels 200% faster than by former methods on a test run of 1000 pieces.

A Gisholt Masterline No. 12 Automatic Chucking Lathe is furnished with a standard cross feeding front carriage, a rear independent slide and an air operated tailstock mounted on a separate independent slide. The work is positioned longitudinally against a

special, headstock mounted air operated, retracting locator. It is held and driven by an expanding mandrel mounted on the spindle, expanded and supported at the other end by the tailstock. Tooling is designed to permit machining grease gun barrels that can be used with 3 different manufacturers equipment with no further

Simple setup upped production of grease gun barrels 200%. In 21 seconds floor to floor time, end of part nearest spindle is turned and thread-rolled, a trademark is rolled on the barrel O.D., 3 separate areas are knurled and the opposite end is "rolled-over" by a special spin-forming roller on standard No. 12 front carriage.



modifications required to permit interchangeability.

Made from welded steel tubing, the parts arrive at the No. 12, after being cut to length with welding flash removed and deburring completed in

a previous operation.

To start the operation, the operator slips the 12½" long, 2½" diameter tube on the arbor, against the locator. He then strikes a push button causing the tailstock slide to traverse 12" forward and the quill to advance 4" to engage the center in the end of the arbor. Pressure from the tailstock center expands the mandrel gripping the work. At this point the locator swings clear of the work and the actual machining cycle starts.

The front slide feeds toward center to the depth of the cut and then longitudinally turning the end for threading. As the turning cut is completed,

Carter NOW HAS BAND SAW GUIDES . .

- TO FIT ANY MACHINE
- SAWING ANY MATERIAL
- M AT ANY SPEED TO 15,000 FPM
- AT THRUST LOADS TO 500 Lbs.



Write for free Catalog

CARTER PRODUCTS CO., INC.

439 Helmer Building 50 Market Ave., N. W. Grand Rapids, Michigan

Use postpoid card. Circle No. 300

When you dress grinding wheels regularly you clean loaded pores, uncover fresh abrasive grains — GET NEW PERFORMANCE AGAIN AND AGAIN. Dressing makes every wheel more efficient. In the complete Desmond line there is a dresser to meet your requirement—at low cost. A typical Desmond-Huntington dresser* costs less than \$3.00: replaceable cutter sets average .36c. Ask your Desmond distributor's advice.

The only complete line of grinding wheel dressers and cutters

Desmond

Desmond-Stephan Mfg. Co. Urbana, Ohio

a special form roller engages the opposite end, spin-turning a radius (see part drawing).


Following this, the rear independent slide feeds in to roll the thread on the spindle end, knurl in three areas and roll the trademark on the tube. On contact with the work, the name marking roller makes only one revolution and is then cammed back into the holder while the slide maintains its "in" position until the completion

of the thread rolling and knurling operations,

Lastly, the spindle stops, the front and rear independent slides traverse out and back to their starting positions. A spring repositions the name marking roll for the next part. The tailstock quill and supporting slide reverse traverse to starting position providing ample clearance to permit quick removal of the finished part.

Floor to floor time is only 21 minutes.

high speed milling cutters FROM STOCK from one of America's Oldest **Cutting Tool Manufacturers** 6 FLUTE END MILL ---In sizes—2" x 41/4"—2" x 61/2" 2" x 81/2"—2" x 101/2" 3 FLUTE END MILL ----In sizes—2" x 6½" 2" x 8½"—2" x 10½" END MILL CUTTER WITH EXTRA 1/4" FLUTE LENGTH Two flutes cutting to center SHELL END MILL 31/4" x 41/4" with 11/2" Hole With end cutting flutes Manufacturers of Cutting Tools Since 1920 Write for Catalog and Representative in Your Area OOL COMPANY 401 Salliotte St. Ecorse (Detroit) 29, Mich.




Unique Locating and Clamping

DETROIT—An interesting locating and clamping problem has recently been resolved by Ex-Cell-O Corporation, on one of their Precision Boring Machines.

The component was an automobile universal joint ball and bushing assembly. The operation was to finish bore the bushing diameter and finish face and counterbore the body. It was required to locate from the inner spherical area and clamp on the outer spherical area. Radial location was from an internal slot in the part.

A special air operated chuck was designed and used in conjunction with a ram to fixture the part. After radial location by hand, the ram squared and held the part, clamping was then effected and the ram withdrawn.


The machine, equipped with two standard Ex-Cell-O Precision Spindles at each end, permits machining at one end while loading and unloading at the other. Holding close limits on diameters and concentricity, production is 180 parts per hour.



Sectional view of workpiece shows spherical locating and clamping areas. Heavy lines denote machining operations.

Belt Guard Is Made of Glass Reinforced Plastic

BRIDGEPORT, CONN.—The Producto Machine Company is using a glass reinforced plastic belt guard on their new No. 1 bed type miller. The pulley guard was re-designed and manufactured by Repco Incorporated, Worcester, Mass. The guard is made in two pieces and attached with a piano type hinge adhered to the guard with epoxy adhesive. This offers strength and eliminates drilling and tapping. Two clasps quickly open the guard to change the belts.



DIAMONDS

matched to industry!

Clipper fits the diamond tool to your exact requirements. Outstanding application experience is translated into the ideal diamond tool. Engineering and production facilities, second to none, are available to you. So, get our recommendations on

Single-pointed diamond wheel dressers

Cluster-type diamond wheel

Diamond-impregnated wheel dressers

Thread grinding tools
Special-shaped diamond tools for
turning and bering
Diamond tools for radius dressing and radius forming
Also outstanding selection of
diamond wheels and hones

• Latest Literature on Request

Clipper Diamond Tool Co.

345 HUDSON STREET, NEW YORK 14, N. Y. • CHelsea 2-7143





Greater Accuracy—with Ex-Cell-O Precision Boring Spindles

You know of the proven superiority of Ex-Cell-O precision boring spindles where close tolerances and fine finishes are required. But did you know that these same Ex-Cell-O boring spindles are available as replacement units?

Produced in belt-driven, standard motorized, or high frequency motorized styles,

MANUFACTURERS OF PRECISION MACHINE TOOLS • GRINDING AND BORING SPINDLES • CUTTING TOOLS • TORQUE ACTUATORS • RAILROAD PINS AND BUSHINGS • DRILL JIG BUSHINGS • AIRCRAFT AND MISCEPLANEOUS PRODUCTION PARTS • DAIRY EQUIPMENT

these Ex-Cell-O precision boring spindles are equipped with XLO Precision bearings for maximum spindle rigidity, long life and smooth operation.

For complete information, call your local Ex-Cell-O Representative or send direct for Bulletin 25477.



FORMING and FABRICATING



these and other Di-Aere ma-chines. Ask far year Copy teday. O'NEIL-IRWIN

MFG. CO.

METALWORKING MACHINES Consult the yel-law pages of your phone book under Machinery - Ma-chine Tools for the name of your nearest Di-Acre distributor or write us.



314 EIGHTH ST. LAKE CITY, MINN.









Hydra Power Bender 2 Models



Red Parter 2 Medels



Power Parter 1 Model



Notcher 1 Model



Power Notcher 1 Model



Power Press Brake 1 Model



4 Models



Punch Press 2 Models



Pawer Punch 2 Models








Powershear 4 Models

Shop Hints and Kinks

blue book



By H. J. Gerber

• Attachment of a dial indicator to the arbor of a horizontal milling machine has been accomplished by various methods, some of them rather cumbersome and lacking in rigidity. We have made up a simple holder which is not only easy to set up for use but is very rigid and easily positioned for most effective use.

The basis of this design is a rather

thin blade which can be inserted between any two of the collars on the arbor and locked in place simply by tightening the arbor nut.


As may be seen in the illustration, the holder consists of the tool steel blade inserted and set screwed into a thicker body which is in turn provided with a slotted hole into which a short length of drill rod may be inserted. This drill rod may be ex-

Shop Hints

continued

tended to desired length and locked with a knurled thumb screw. The dial indicator is attached to the drill rod by means of the usual swivel clamp so often used to hold indicators to a surface gage.

Small Magnets Hold Thread Measuring Wires





By H. J. Gerber

• Holding thread wires in position when measuring pitch diameter of a screw thread is usually an aggravating problem. A pair of small "button"



gives 10 to 20 times longer cutting life than

ordinary tools and often as much as 75 times longer cutting usefulness. Dixie's grinding methods tend to eliminate fracturing and chipping of the cutting edges as ordinary machine grinding does. The chipping and flaking of the cutting tool is virtually eliminated. This provides a longer lasting cutting edge, that reduces tool wear and does a smoother job in the finished surface.

Dixie Micro-finish carbide tools cut faster and last longer, saving you both time and money. Dixie can also regrind your worn out, damaged or discarded tools with the same "Microfinish" as on new tools.

Write Dixie today on your cutting tool requirements.

DIXIE TOOL INDUSTRIES 455 W. Franklin Ave.

BRIDGEPORT, MICHIGAN -------

magnets, used as illustrated, will greatly aid in this task. It will be necessary to flat grind a small area on the side surface of each magnet and parallel to the slot opening between the poles of the magnet.


To make this set-up I find it convenient to make use of a small angle plate as a support for the magnets. An ordinary "V" block or small toolmaker's vise will usually provide a good means of holding the work. Each

magnet is seated on the angle plate with contact being made by means of the above mentioned flat on the side of the magnet. The wires are then laid across the poles of the magnets, one on the top magnet and two on the lower one. The work is then positioned between the wires and magnets moved on the plate until the wires are seated correctly in the thread groove. Both hands are now free to manipulate the micrometer.



Operators like 'em... because Kent-Owens Machines are extremely simple and practical. Turn out milling jobs fast, with minimum worker fatigue! Twin-post head mounting assures balanced load. Only two gear contacts, motor to cutter, for greater cutting efficiency. Write for bulletins on wide range of single and double spindle hydraulic and hand-operated machines. Also, let Kent-Owens design and build your tooling and special machines. Kent-Owens Machine Co., Toledo, Ohio.

Call on KENT-OWENS



Parallel Facing Made Easy

By John M. Breen

• At times in almost every machine shop there arises a job where a quantity of pieces need be faced off perfectly parallel. Here is a system where it can be performed very simply and inexpensively.

Many lathe chucks have slots spaced between the jaws. This can be used for fastening the backups. There are four in all as we are working on the principle of four chuck jaws. Each backup consists of a block and two bolts. One bolt fastens it to the chuck. The other bolt is raised to the desired height, then locked with a nut as are the other three. With the four heights equal the facing cut is taken. Since bolt head facing utilizes very little cross slide travel, facing time is very short. We then have four perfectly parallel points to backup the work piece.

The work piece is then clamped in the chuck. Slight taps of a hammer will seat it against the backup. We can now face our piece part and be sure of perfect parallelism. These backups can be kept with the lathe tools and used for many jobs of this same nature.



COUNTERBORES

IN DECIMAL SIZES

ALSO Chucking and Stub Reamers THOUSAND'S by the THOUSANDTH'S Write for Latest Catalog and Prices


TWENTIETH CENTURY MFG. CO.
Box 429-BB LIBERTYVILLE, ILL.

Preventing Drill Damage With Thin Parallels


By F. A. Adams

 Many tool shops suffer a great amount of drill and piece part damage when it becomes necessary to use thin parallels for drilling thin walled parts. Quite frequently, the thin parallels topple over, the result being tool or piece part damage.

A very effective solution to this problem is shown in the accompanying sketch. The vise jaws are drilled and reamed to receive press fitted fiber bushings. Permanent magnets are then pressed into the fiber bushings as shown. These magnets hold the thin parallels tightly against the holding surfaces of the vise jaws thus prevent-



ing any toppling action which may sometimes occur. Chips clinging to the magnetized parallels are easily wiped off with an old paint brush. . . .



Thumb Screws at a Minimum Cost

By R. K. Dulek

 Many ingenious ideas originate on the toolmaker's bench. These small, time and money saving ideas are priceless in the cost conscious tooling programs of today.

Shown in the accompanying sketch

is one of these ideas. A thumb screw, made from a standard screw and a standard washer. A round or button head screw with a standard plain washer, brazed in the head slot, provides a perfect and inexpensive thumb screw for jigs, fixtures, etc.

STEELWELD SHEAR

Serves TOUGH JOBS Well



A part of an order of 120,000 gussets cut on the shear.

FOR several years a Steelweld Shear has been in operation at the Drake Steel Supply Co., Los Angeles, California. Most of the time it has been worked on a 16-hour-a-day schedule. It is used for a wide variety of shearing, mostly on ½/4-inch and ½-inch steel plate.

The machine has proven itself on all sorts of shearing jobs. A particularly tough one was the cutting of 120,000 small odd-shaped gusset plates. These were of three sizes and cut three to six at a time of ½-inch steel. The work jarred the shear terrifically, but because of its heavy construc-

tion, did not affect it in any way.

Considering the volume of work and hard service, the knives hold up very well. They need be turned only about once every six months.

Write for free capy of catalog No. 2011





Steehweld Machinery Includes: Mechanical & Hydraulic Shears and Piess Brikkii
One-, Two- and Fear-Point Straight-Side Presser, Seed-Drov Presser.

THE CLEVELAND CRANE & ENGINEERING CO.

5258 East 282 Street, Wicklitte, Ohio Use postpaid card. Circle No. 308

Free Literature

blue book



(See Number 1)



(See Number 2)



(See Number 3)

To receive copies of booklets described below, circle their identifying numbers on an Action Card, found opposite pages 72 and 168.

- 1. Carbides. Catalog No. A-102 presents carbide tools, tips, inserts, and blanks. Complete performance data on regular and premium grades is included, as well as information on special shapes and wear parts. Unimet Carbides, 435 W. Ontario St., Chicago 10, III.
- 2. Precision Jig Borer, Model No. 3, is capable of locating and boring holes to less than a tenth. Brochure shows the greatest possible error of positioning in longitudinal travel in any inch is 30 millionths (in 18", 90 millionths), and in cross travel, 30 millionths in any inch (90 millionths in 11"). Moore Special Tool Co., Inc., Bridgeport 7, Conn.
- 3. Aluminum Weldor's Training Manual is designed to train and qualify individuals in welding aluminum by the inert gas process. Material in the 144-page book covers three primary functions essential to aluminum welding: In the first section, essential factors about both tungsten-inert-gas and metal-inert-gas welding techniques are presented; second and third sections offer amply illustrated step-by-step exercises. Technical Publications Dept., Kaiser Aluminum & Chemical Sales, Inc., 919 N. Michigan Ave., Chicago 11, Ill.
- 4. Soft Blank Chuck Jaws. Bulletin contains complete specifications and data on jaws for all makes of chucks, including air chucks, hand or power operated geared scroll chucks, two- and four-jaw independent chucks, and combination chucks. The booklet is arranged to show interchangeability of chuck jaws between different makes and models of chucks. Gahr Machine Co., 19199 St. Clair Ave., Cleveland 19, Ohio.
- 5. Way Guards. Folder illustrates the Can-Pro accordion way guards, designed to assure protection against wear and damage caused by abrasive flying materials. Fabricated from Butapren, a special synthetic rubber whose flexibility and softness permits guards to be compressed in small areas. The material withstands temperature changes from —45° to 220°F without cracking. Guards are made to customer specifications. Can-Pro Corporation, Fond du Lac, Wis.

Free Literature

continued

- 6. Corrosion Prevention. Bulletin 93XG describes the Metco metallizing systems, a series of techniques which firmly bond properly treated pure metals to a steel base. These metal coatings assure protection against oxidation for many years. Bulletin pictures some typical applications on a broad range of equipment and structures. Metallizing Engineering Co., Inc., 1101 Prospect Ave., Westbury, N.Y.
- 7. Pneumatic Comparator Gages. Catalog No. 8008 presents a new line of air gages for dimensional measurement and a series of automation building-blocks for sizecontrol systems. It covers newly standardized purchasing data on pneumatic plus, rings, and gaging cartridges. Moore Products Co., H & Lycoming Sts., Philadelphia.
- 8. Carbide Tools. Enlarged lines of Coromant carbide blanks, inserts, tools and tool holders are described in 52-page catalog. Price list accompanies catalog. Sandvik Steel, Inc., Coromant Dept., 1702 Nevins Rd., Fair Lawn, N.J.
- Flexible Couplings. This catalog contains helpful information on various types of couplings. Dimensions, list prices, horsepower ratings are included. Acme Chain Corp., Holyoke, Mass.

- 10. Block-Type Boring Tools with throwaway carbide inserts are described in Bulletin DB-410-A. The new blocks are designed for use with standard Davis boring bars. Two-cutter blocks are for rough boring and single-cutter, micrometer-adjustable blocks for semifinish and finish boring. Davis Boring Tool Div., Giddings & Lewis Machine Tool Co., Fond du Lac, Wis.
- 11. Drilling, Tapping, Boring Machine. Bulletin announces the Burgmaster GE tape controlled six and eight spindle turret drilling, tapping and boring machine. It tells how to program a part, prepare the tape and operate the machine. Cost reducing features work equally well on short run jobs or high production, the manufacturer reports. Burg Tool Mfg. Co., Inc., 15001 S. Figueroa St., Gardena, Calif.
- 12. Steel Collets. Round, hexagon and square steel collets for Jacobs spindle nose chucks are presented in Bulletin JC. A steel emergency collet has soft face and pilot hole to permit rapid boring and stepping out when in place in the chuck. Hardinge Bros., Inc., Elmira, N.Y.
- 13. Engine Gap Lathes feature gap bed, all geared headstock (except one model), a wide range of feeds and speeds, and hardened and ground gears from chromenickel-molybdenum steel. Flyer illustrates six models, gives specifications for seven. Hermes Machine Tool Co., Inc., 48-15 Northern Blvd., Long Island City 1, N.Y.



(See Number 6)




(See Number 7)



(See Number 8)

Thompson

TRUFORMING CUTS COSTS 60%



For 140 years, the policy of The Draper Corporation of Hopedale, Mass., has been to offer the highest quality product at the least possible cost.

Following this policy, its subsidiary, BlueJet Corporation, manufacturers of the famous BlueJet saw chain, installed a Thompson Truforming grinder to grind the cutting edges on their chain saw routers. These routers were formerly ground, piece by piece, by a force of 8 employees.

The Thompson Truforming operation is now cutting former grinding costs by 60%. 3 men only are now required for the operation. 40 L.H. and 40 R.H. routers are now ground simultaneously

with one pass of the crush formed wheel, resulting in a day's production of over 12,000 pieces—many times that produced by the former method. Both the uniformity and sharpness of the routers have been greatly improved.

For 25 years, Thompson has pioneered and developed the modern advances in crush form grinding. If you have a time-saving, product-improving or cost-cutting problem in your operations, it will pay you to investigate the work Thompson Truforming grinders are now doing in plants all over the country. Our engineering experience is available to you without obligation. Write for Catalog T558.

"Keep Trossepson in mind for the daily grind"

THE THOMPSON GRINDER COMPANY

SPRINGFIELD. OHIO



Free Literature

continued

- 14. O.B.I. Presses, Minster Series 1, capacities from 35 to 75 tons, are described and illustrated in four-page bulletin. They are equipped with combination air friction clutch and brake unit. New features include a modified flanged slide that provides more die area and a time-saving lower connection ball box connection adjustment. The Minster Machine Co., Minster, Ohio.
- 15. Grinding Wheels. Catalog No. 7525 includes vitrified, resinoid and rubber bonds in cut-off, straight, recessed and platemounted wheels. Recommended applications are given. Chicago Wheel & Mfg. Co., 1101 W. Monroe St., Chicago, Ill.
- 16. Diaphragm Chuck. Illustrated with photographs, sectional views and dimensional drawings, folder gives detailed information and full specification data on the three basic models comprising the line. Erickson Tool Co., Solon, Ohio.
- 17. Diamond Tools, for general and special applications, are presented in 20-page catalog. Single point diamond dressers, hardness testing diamonds, boring and turning tools, gear grinding dressers are among products included. A. Landau Co., 247 S. Ninth St., Philadelphia 7.

- 18. Bearing Lubrication. Lubrication of miniature instrument bearings is the subject of lubrication manual claimed to be the first of its kind in the miniature bearing industry. It supplies data and information of the various types and brands of oils and greases available to bearing designers and users. Miniature Precision Bearings, Inc., Precision Pk., Keene, N.H.
- 19. Machining Aluminum. A handy size, ready-reference handbook provides complete data on machining practices, tool angles and designs, and tool materials. Proper speeds, feeds, lubricants and cutting compounds are explained fully, enabling machinists and engineers to realize the speed and ease possible in machining aluminum and its alloys. Reynolds Metals Co., Dept. PRD-3, Box 2346. Richmond, Va.
- 20. Variable-Speed Pulleys. Bulletin No. 4101 describes pulleys designed to eliminate freezing and sticking. Gives technical data for five MS sheaves for ratings of 2, 3, 5, 10, and 15 hp. Pulleys have no keys to obstruct the flow of oil between the flange hub and sleeve. T. B. Wood's Sons Co., Chambersburg, Pa.
- 21. Disc Grinding. Bulletin gives vital data on important time savings now possible in disc grinding. New DH4 double horizontal spindle disc grinder is claimed to make disc grinding virtually automatic. Features: push-button operation, accuracy to tenths, 3-step abrasive change, automatic dressing and sizing. Besly-Welles Corp., South Beloit, Ill.



(See Number 14)



(See Number 15)



(See Number 16)

MAKE "IMPOSSIBLE" HOLES POSSIBLE...

With
Lift Swing
Drilling Fixtures



Use the Lift Swing Drilling Fixture with a double top plate and drill two holes side by side with a minimum of wall thickness in between . . . this is accomplished without "special" drill jig bushings and without difficult-to-grind flats on bushings . . . just drill using one side of the double plate, swing 180° and drill using the other side—fast and simple.

You can drill and ream or you can drill two different diameter holes at the same location; yes, two operations without bushing changes. Lift Swing with a double top plate . . . provides Faster, Easier Tooling; Reduced Tooling Costs; Less Down Time; Increased Production.

Accurate Lift Swing Drilling Fixtures come in either single or double "Swing Away" Top Plate models—and in a range of sizes to fit every need.

Investigate the real production cost savings Accurate Lift Swing Drilling Fixtures can bring you . . .



Write for Lift Swing Tooling Suggestions. Bulletin LS-58

ACCURATE BUSHING CO.

SA Standard Drill Bushings . Precision Parts . Lift-Swing Drilling Fixtures

444 NORTH AVE., GARWOOD, N. J.

Free Literature

continued

- 22. Flotation System. Brochure describes flotation units employed in metal working operations. By achieving continuous, fully automatic clarification of water soluble oil coolants, the units increase productivity of machine tools, end down time due to failure of coolant supply and the need for sump cleaning. U. S. Hoffman Machinery Corp., Thompson Rd. Plant No. 1. Syracuse, N.Y.
- 23. Indicator Holders, Magnets. Erick Magna holders, as described in Catalog No. 958, are lifetime, magnetized holding devices and like an extra hand help produce more accurate work. The various holders are illustrated with features and specs. A magnetic base protractor is described as a combination angle finder, center locator and leveling gage. Vise liners, magnetic blocks, and magnets are also covered. Cullen Manufacturing Co., Racine, Wis.
- 24. Granite Surface Plates, from small toolmakers' flats to large 7' x 14' models, are described in illustrated brochure. Straight edges, surface plate stands, parallels and angle plates are also included. Surface plates are lapped to an over-all accuracy as close as 25 millionths of an inch. Pratt & Whitney Co., Inc., West Hartford 1, Conn.

- 25. Semi-Automstic Lathe (MR-6020) i built for applications in the fields of electro-mechanics, instrument manufacture, ordnance, optics, and fine mechanics in general. Brochure gives a chart of machining time per component in seconds main technical characteristics. One operator can attend two machine heads at the same time. Carl Hirschmann Co., Inc. 30 Park Ave., Manhasset, N.Y.
- 26. Barrel Finishing Equipment. Fourteer standard units, two small barrel models and 11 specialized barrel finishing machines are described in booklet. Free sample processing of parts in test laboratories. Almco, Queen Products Div., King-Seeley Corp., Albert Lea, Minn.
- 27. Cold Chambers (shotwells, shotsleeves bushings, plunger tips) are described in flyer. Customer heat treat requirements material demands and size tolerances are followed exactly, the manufacturer claims Advance Products Corp., North Shore Drive, Benton Harbor, Mich.
- 28. Drilling Teel. Folder presents the Roto-Bor, claimed to be the only tool that successfully drills holes in both light and heavy gauge sheet metal and plate, stainless steel, brass, aluminum, plastics, fibers cork, rubber, even honeycomb and paper Tool features disappearing center point Holes are accurate to .001". Jancy Eng Co., Davenport, Iowa.
- 29. Packaged Water Chillers. Catalog No 515 includes complete description, performance data, specifications and dimensions of the Acme Model RG packaged



(See Number 22)



(See Number 23)



(See Number 24)

MANUFACTURER:
Harvey Hubbell, Inc., Bridgeport, Connecticut.
PRODUCT:
Contact Spring.
PRODUCTION:
136 Parts Per Minute.

Blanking, Piercing and Preforming in Press



fac

nic

nds

the

nc.

leli na ree ra-

n

1000



Cutoff

Partial Forming with Slides

Final Forming with Slides

Nilson 4-Slide Machine with Built-in Press



NILSON 4-SLIDE BLANKS and FORMS IN ONE CYCLE!

Harvey Hubbell shifted production of this part from a conventional press and progressive dies to a Nilson 4-Slide with built-in press. The immediate results: elimination of two secondary operations . . . simpler die . . . higher production rate . . . no stripping problems.

Harvey Hubbell also found that vertical mounting of die makes replacement easy ... permits automatic disposal of scrap by gravity. And maintenance costs are incred-

ibly low—this machine has been operating for twelve years without major repairs!

Nilson builds 7 models of ribbon metal forming machines, with built-in press sections ranging from 5 to 75 tons capacity. One of these machines may help you bring your stamping methods up-to-date!

Write today for the Nilson General Catalog on Automatic 4-Slide Equipment.





THE A. H. NILSON MACHINE CO.

602 Bridgeport Avenue • Shelton, Conn.

AUTOMATIC WIRE & RIBBON METAL FORMING 4-SLIDE MACHINES • WIRE & STOCK REELS • WIRE STRAIGHTENING EQUIPMENT • AUTOMATIC STAPLE FORMING MACHINES • SPECIAL WIRE FORMING EQUIPMENT

Use postpoid card. Circle No. 311

Free Literature

continued

water chillers. This unit has been reduced in size from previous models. Capacity range, 3-30 tons. Acme Industries, Inc., Jackson, Mich.

30. Selenium Rectifiers, for efficient, economical AC to DC rectification, are catalogued in 10-page booklet. Cell sizes range from 1" square to 12" x 16". Four pages contain continuous DC current ratings for 26, 33, 36, 40, 45, and 52 volt RMS cells. Syntron Co., 300 Lexington Ave., Homer City, Pa.

31. Milling Machines. The Newton line of special production-line milling machines is discussed in Bulletin 675-A. Types included are straight-line, vertical openside, sliding head, shuttle type, rise and fall, rotary index, traverse, planer and traveling column. Consolidated Machine Tool Div., Farrel-Birmingham Co., Inc., Rochester 10, N.Y.

32. Bed Type Milling Machine. The Producto No. 1 is sturdily constructed for accurate, rapid milling of light and medium production work. The machine is available in three standard arrangements, with hydraulic or manual feed, and work surfaces of different dimensions for varied amounts and kinds of work. Booklet from the Producto Machine Co., 990 Housatonic Ave., Bridgeport 1, Conn.

33. High Temperature Steels and Alloys data card, 334" x 5½", lists 19 special metals used in high temperature applications, such as parts for jet engines, gas turbines, missiles. Composition of each alloy, its base material, density, rupture strength data at various temperatures, and its short time properties at room temperature and at 1200°F are included. Allegheny Ludlum Steel Corp., Oliver Bldg., Pittsburgh 22. Pa.

34. Precision Tools. Bulletin M81 describes convertible thimble micrometers with a range from 0 to 1" by .0001"; height gages with new versatility and stability; a Super Hite Chek, self-contained transistorized unit that reads in 25 millionths; tool setting gages; edge finders; radius gages; sine plates; dial snap and bore gages. Brown & Sharpe Mfg. Co., Providence.

35. Master Multi-Swivel Vises, Platens, swivel platens, swivel bases, flanged vises, swivel vises are presented in folder. Multi-swivel platen holds large or irregular-shaped parts and dies that cannot be held in jaws of vise. Multi-swivel base is recommended for use where it is necessary to have a fixture that will swivel up to 90° vertically and 360° horizontally. Donovan Mfg. Co., 80 Batterymarch St., Boston, Mass.

36. Hydraulic Panel Fabrication Technique, described in 8-page brochure, utilizes building block standard component subplates with pressure, return and drain lines manifolded within the block. Parts are reusable for future circuit modifications. Petch Mfg. Co., Detroit.



(See Number 29)



(See Number 30)



(See Number 31)



SUTTON TOOL COMPANY

Dept. MTB-4, STURGIS, MICH.

re


m d.

d

This Catalog is a 68 Page <u>Handbook</u> on Drills and Drilling Information



See your Cogsdill Distributor or send the coupon



"hot" metals


Greenfield,	Mass.
	copy of your new Cogsdill Drill Catalog and Cogsdill Distributor.
None	
Position	
Company	

Tough Grinding Wheel Forms Dressed Easy as A, B, C

eliminate elaborate set-ups and operations

Fluidmotion WHEEL DRESSERS

dress two angles tangent to a radius in one continuous motion



With the unique "Fluidmotion"

Dresser, you can dress two angles tangent to a radius — using one handle in one continuous motion.

Operation is so fast and simple that beginners can use them.

Adaptable to all type cylindrical and surface grinders.

- A. Obtain micrometer reading; add required convex radius or subtract required concave radius.
- B. Loosen jib with wrench and "mike" over lower pins to reading obtained above.
- C. Tighten jib. Set stops for two angles. Ready for action.



Also available: "FORM MASTER" Dresser, capable of dressing any radii up to 12" convex, up to 15" concave.

See your industrial distributor or write for free literature.



MY CLAMPS + PRECISION YESTS + SIGNIFIC HOLDING SEVICES

CLAMPCUT

J & S TOOL CO., INC.

880 DORSA AVE. LIVINGSTON, NEW JERSEY

NEW Electric Furnaces built for your specific needs!



TYPE 2100

for small parts and short runs

- · Top-loading
- . 6-3/4" dia. x 11" deep chamber
- 6-1/2" x 7-1/2" stainless steel pot
- · Triple-insulated



This low-cost, multipurpose THERMOLYNE Type 2100 Furnace is adaptable for use as salt bath, melting, vertical muffle or crucible furnace. Basic unit includes furnace, alloy pot and cover with lifting handle, and thermocouple in protection tube. Optional maximum-use accessories include refractory ladle and refractory liner with cover. Three types of insulation hold heat loss to a minimum. Automatic or semi-automatic electronic temperature controls available. 115 or 230 volts. Price of basic unit, without controls, \$180.00.

TEMCO

TYPE 1900

for long work parts and high temperatures

There's no waste space in this new TEMCO Type 1900 Furnace with the chamber long in relation to its height and depth. Choice of 2000° or 2300°F maximum operating temperature, 115 or 230 V. Gives fast heating, quick recovery time, and big power reserve for heavy loads. Available with wide selection of control instruments. Price (furnace only) \$215 or \$235, according to temperature range.



- Chamber dimensions: 13-1/4" deep, 4-3/16" high, 4-7/16" wide
- · Reinforced, welded steel shell
- Easily operated door

Write for information and name of nearest dealer

THERMO ELECTRIC MANUFACTURING

486 Huff St., Dubuque, Iowa

Use postpaid card. Circle No. 315

CO.

Machine Tool Orders, Shipments for January

From the National Machine Tool Builders' Association comes a preliminary report of activity in machine tool sales and shipments during the month of January.

Gross new orders for metal cutting type machine tools totaled \$28,700,000 that month (preliminary figure, domestic and foreign combined). December gross new orders were \$33,100,000.

Cancellations of orders for cutting type machines plunged to \$600,000 in January, down \$1,450,000 from December cancellations, and making net new orders for January \$28,100,000 (domestic \$23,650,000, a drop of \$2,450,000 from December; foreign \$4,450,000, down \$500,000 from December's \$4,950,000 foreign sales).

Shipments of metal cutting type machine tools for January (both domestic and foreign) are estimated at \$23,850,000. This is \$10,050,000 less than December, when shipments reached \$33,900,000. January's estimated backlog (in months) was 3.4.

In the metal forming branch of the industry, net new orders totaled \$12,-050,000 for January, down \$800,000 from December. Domestic net new orders for December were \$8,650,000 and foreign \$4,200,000, for a combined total of \$12,850,000.

Forming type shipments for January amounted to \$7,950,000 (\$5,850,000 domestic and \$2,100,000 foreign), \$2,100,000 below December's \$10,050,000 shipments. In January the estimated backlog (in months) was 3.7.

Cutter Service Company Organized by B & S

A complete cutter and tool sharpening service has been added by the Cutting Tool Div., Brown & Sharpe Mfg. Co., Providence, R.I., with the organization of "The Brown & Sharpe Cutter Service Co. of New Jersey," located at Ridgefield, N.J. This is an independently operated business staffed by factory trained cutting tool specialists.

Carborundum to Build Pilot Plant

The Carborundum Co. has announced that it will build a new ¾ million dollar pilot plant for its research and development division at Niagara Falls. About one year will be required for the construction of the building, procurement and installation of the equipment.

Carborundum's research and development division is turning out new products which require ultra-high temperature processing techniques not presently available in the main operating divisions of the company. The new R&D pilot plant will provide the special equipment necessary to bring these new products through development stages to a point where they can be allocated to present divisions for production and sale or form the basis for new operating divisions of the company.

The pilot plant will be operated by the new products branch of the research and development division, headed by **Donald G. Sturges**, manager of the branch.

Brown & Sharpe Buys Howe and Fant

Brown & Sharpe Mfg. Co., Providence, R.I., has announced the purchase of Howe & Fant, Inc., of East Norwalk, Conn., originator and manufacturer of turret drilling and jigless work positioning devices.

Acquisition was by stock purchase. Howe & Fant will become a subsidiary known as the Brown & Sharpe Turret Drilling Division, Inc. It will continue to operate at the East Norwalk plant with its present personnel.

Distribution of products of the new division will be through Howe & Fant's existing dealers in the metalworking centers of the United States. Arnold Charlat, formerly the company's vice-president and chief engineer, becomes president of the new subsidiary, succeeding A. S. Howe, Jr., who will continue as a director.



STYLE AND SIZES FOR ALL MACHINES ON WHICH THREADS ARE CUT

This die head is unique

THERE IS NO OTHER LIKE IT

It cuts threads with insert chasers. These are, in reality, small sections of the business end of large and expensive chasers, but with this important difference: their cost is so low they can be even thrown away when dull. For example, for less than \$50 you can get a dozen sets of insert chasers, each set ground ready to go. Change now to insert chaser die heads and watch your performance improve. "UNIFIED AND AMERICAN SCREW THREAD DIGEST" sent free on request.

THE EASTERN MACHINE SCREW CORP., 25-45 Barclay St., New Haven, Conn.



Counterboring

HOLDER

Heavy Turning



Chamfering I. D.




Facing




Chamfering O. D.









Ask your

mill supply house or Maxwell representative

- Adjustable carbide chipbreaker on cap assembly also can be indexed FOUR times. More economy!
- 5. Fast, convenient clamping speeds indexing or positioning inserts. Saves time!
- 6. No need to change tool holder for different work positions. Simply rotate clamping cap and adjust insert. Cuts set-up time!
- 7. Serrated clamping cap, forged shank and anvil and locking cap screw hold carbide inserts in perfect grip—no lateral movement, no chatter. Cuts scrap loss!
 AA-9176

MAXWELL INDUSTRIES, INC.

493 East 5th Avenue - Ashtabula, Ohio

clamping

cap.



J. J. Jaeger



H. J. Fredericks



E. J. Shages



H. A. Johnson

Appointments and Promotions

Personnel Changes . . . Executive and Production

Name	Company	To	Position
Robert H. Kemp	E. W. Bliss Co. Canton, Ohio	L &J Press Corp. Elkhart, Indiana	Chief Engineer
Jacob J. Jacger	Pratt & Whitney Co., Inc. West Hartford, Conn.	Same	Executive Vice-President
Henry J. Fredericks	Pratt & Whitney Co., Inc. West Hartford, Conn.	Same	Vice-President
Edward J. Shages	Pratt & Whitney Co., Inc. West Hartford, Conn.	Same	Vice-President, Mfg.
Roger Marriott	Barnes Drill Co. Rockford, III.	Same	SecyTreas.
Alfred G. Block	Barnes Drill Co. Rockford, III.	Has retired from his	position as Secretary-Treasurer.
Harold A. Johnson	Barnes Drill Co. Rockford, III.	Samo	Vice-Pres., Eng. & Mfg.

▶ BEDFORD GEAR'S "adjustable" CHUCK JAWS ... CUT SOFT-JAW EXPENSE ... REDUCES SET-UP TIME . . . ELIMINATES SOFT-JAW BORING ON REPEAT RUNS!





PAD TYPE

BEDFORD'S combination of Top-Jaw and Sub-Jaw, when positioned on chuck, have all the rigidity of solid jaw. Sub-Jaw adjusting feature made permanent when binding screws are tightened.

This combination adaptable to most power and scroll chucks . . . Will also fit chucks with receding jaws.

Top-Jaws can be shaped in tool room, or bored at production machine. Hardened jaws are now made practical for all jobs. Contact your dealer, or write:



New Type TOP-JAW Pointed or Rectangular.

Write for FREE Catalog 60

Gear AND MACHINE PRODUCTS THE 50 Krick Rd. - Bedford, Ohio



Personnel Changes . . . Executive and Production

Name	Company	То	Position
Affred T. Blackburn	Cincinnati Millina Machine Co. Cincinnati, Ohio	Same	Vice-President, Mfg.
Clyde Eby	Cincinnati Milling Machine Co. Cincinnati, Ohio	Same	Works Manager
Franklin Meyer, Jr.	Taft-Peirce Mfg. Co. Woonsocket. R.I.	Same	Mgr., Small Tool & Gage Divs.
Paul V. Miller	Taft-Peirce Mfg. Co. Woonsocket, R.I.	Same	Consulting Engineer
D. F. Griffin	Vanadium-Alleys Steel Co. Latrobe, Pa.	Landis Machine Co. Waynesboro, Pa.	Chief Metallurgist
H. E. Robison	Wheel Trueing Tool Co. Detroit, Mich.	Same	President, Treasurer
R. S. Fowler	Wheel Trueing Tool Co. Detroit, Mich.	Same	Vice-Chairman of Board
H. B. Wallace	Wheel Trueing Tool Co. Detroit, Mich.	Same	Chairman of Board



THE QUALITY EXTRA...

n SEE

Tungsten Carbide Tools

- IS FREE

Tool performance that increases your production and profits—yet costs you less money . . . it's what you want and what you get —when you use S&E TOOLS

That extra quality is no accident. It is the product of more than 20 years experience in the design and manufacture of Tungsten Carbide Tools.

Prove to your own satisfaction that the performance and stamina you need in tooling today—you get in S&E. A fully illustrated catalog of standard and special tools is available upon request.



WRITE:



MACHINE PRODUCTS INC.

Bridgeport, Michigan Representatives in all principal cities.



R. E. Reilly



S. E. Bergstrom



R. C. Bevis



J. F. Kelly

Personnel Changes . . . Sales and Service

Name

Robert E. Reilly
Lee P. Sinclair, Jr.
Thomas F. Lynch
R. E. Bailey
H. L. Cogswell
Swan E. Bergstrom

Robert C. Bevis

James F. Kelly

Company

Company

E. W. Bliss Co.
Washington, D. C.

E. W. Bliss Co.
Baltimore, Md.

E. W. Bliss Co.
Canton, Ohio

E. W. Bliss Co.
West Coast
Barnes Drill Co.
Rockford, Ill.
Cincinnati Milling Machine
Cb.

Ch.
Cincinnati Ohio
Cincinnati Milling Machine
Co.
Cincinnati, Ohio

To

Canton, Ohio. Washington, D. C.

Same

Los Angeles Same

Cincinnati Milling & Grinding Machines, Imc. Cincinnati, Ohio Cincinnati Milling & Grinding Machines, Inc. Cincinnati, Ohio Madison-Relee Tool Co. Providence, R. i.

Position

Sales Mgr., Spec. Prods. Div. Rep., Spec. Prods. Div.


Midwest Sales Mgr., Special Products Div. Rep., Spec. Prods. Div.

Vice-President, Sales


President


Vice-Pres., Director

Area Sales Mgr.









NOW! Cut Costs! Use Highest Precision WOHLHAUPTER Facing and Boring Masterheads
Facing, Boring, Turning, Recessing, Undercutting, Underfacing and Tapercutting

- Automatic Feeds
- Automatic End Release
- 9 Sizes for Work to 361/4"
- 12 Feeds in Larger Models


Also Tapercutting Heads for 0-180°

FREE! For illustrated catalog containing complete technical data, write today!

Sole Agents:



KARL A. NEISE
Dept. MT-49
404 • 4th Ave., N.Y.C. 16



ON KENCO SUPER HIGH SPEED PRESS

A leading manufacturer has increased the production of rubber parts from 100,000 parts per shift to 1,000,000 using a 5 Ton Kenco press operating at 500 strokes per minute.

Six rubber strips are roll fed automatically into the dies and the punched parts are dropped out of the die, six at each stroke, and carried away on a power driven belt conveyor. Production is reckoned on the basis of a six hour run per shift.

The cost of producing this item has been substantially reduced because Kenco Engineering enables this press to sustain production at 500 strokes per minute using adjustable automatic feed. The press is equipped with roller bearings which support the crankshaft, connecting rod and flywheel. Automatic lubrication is used with the result that this Kenco press will operate around the clock at high speeds showing no appreciable wear of the moving parts while permitting maximum life of the dies.

Let Kenco Engineers help solve your problems where more profitable punch press operation is your goal. Kenco presses are made in 2, 5, 8, 12, 15, 18. 21 and 26 tons capacities, with 108 Models to select from-the largest selection of small presses available anywhere.

Job Facts:

Machine: 5 ton Kenco Punch Press with high speed roller bearings and automatic lubrication. Feed: Automatic adjustable roll feed.

Stock: Rubber strip.

Production Advantage: Increased 10 times at rate of 500 spm compared to production on replaced equipment.

Maintenance: None to date:

WRITE TODAY for free literature describing the modern mechanical features and complete specifications of Kenco Presses.





KENCO MANUFACTURING CO

5211 Telegraph Rd., Los Angeles 22, Calif.

18, 21 and 26 tons capacities

THE MOST COMPLETE LINE OF SMALL PUNCH PRESSES IN THE WORLD

Personnel Changes . . . Sales and Service

Name	Company	То	Position
Charles Hoppe	Detroit Stamping Co. Detroit, Mich.	Finished Products Div.	Sales Manager
Eric Wormer	Adamas Carbide Corp. Kenilworth, N.J.	Tool Specialists, Inc. Westbury, L.I., N.Y.	New Jersey Representative
R. David Mathias	L & J Press Corp.	Same	Vice-President, Sales

New Dealers and Distributors


Company	Address	Distributor for		
J. W. Mender Chain & Gear Co. Roy Heyne Co. Frank J. Cox Sales Co.	6011 S Central Ave. Los Angeles, Calif. 728 W. Buchanan Phoenix, Ariz. 6 Elmview Court Islinston, Ontario, Canada	Acme Chain Corp. Holyoke, Mass. Size Control Co. Chicago, III. Size Control Co. Chicago, III.		
D. M. Duncan Machine Co., Ltd.	1958 Wyandotte St., East Windser, Ontario, Canada	Size Control Co.		

AVAILABLE FILMS

Screw Machine Tooling

Brown & Sharpe Mfg. Co., Providence, R.I., has produced a new 16 mm color sound film, "Engineered Screw Machine Tooling Applications," which features eight practical applications of the latest design automatic screw machines.

Utilizing close-up views and slow motion, some of the sequences detail the relative position of tooling during close timing operations. Standard and special attachments with explanations of the tool engineering involved in their practical application are featured. Running time is 35 minutes.



Typical parts produced in the filming of "Engineered Screw Machine Tooling Applications"

Film Acquaints Public with Machine Tools

This movie, designed to tell the story of machine tools to the general public, is not for the purpose of selling machine tools. Its purpose is purely educational. It shows the relationship between machine tools and the standard of living, explaining interchangeability of parts and quantity production. and showing machine tools making the working parts of not only the products which we use for daily comfort and convenience, but of machines upon which we depend for industrial processes. It makes clear that machine tools create jobs instead of destroying them, and it explains how the nation must rely upon machine tools for national defense.


The movie is entitled "One Hoe for Makwanga." Makwanga is a tiny village in the heart of Africa, where crude agricultural implements are still being made by the most primitive methods. In Makwanga it takes a whole day to make a single hoe. The movie opens with actual scenes taken in Makwanga. The contrast between that village and present day America points up the story of machine tools.

The film is available to schools and

RUTHMAN GUSHER **COOLANT PUMPS**

are

STURDY





AS AN ELEPHANT



AS A GIRAFFE



WELL DESIGNED

AS A THOROBRED

For Complete Satisfaction

GUSHER COOLANT Specify

thman

MACHINERY CO.

- CIRCULATORS . AGITATORS
- MOLTEN METAL PUMPS

CINCINNATI, OHIO

1816 READING ROAD

Use postpaid card. Circle No. 322

179

THRIFTMASTER

your source for

dependable DRILLHEADS

Universal Joint Type
Drillhead . . Full Ball
or Bronze Bearing Construction, Standard or
Heavy Duty. From 1/2"
minimum centers up.
Capacities to 1/2" in
Steel.





Single and Double Eccentric Type Adjustable Drillhead . . . Enclosed, Full Ball Bearing Construction. New Double Eccentric Type illustrated.

Special Fixed Center Drillhead . . . Made to your requirements. Full Ball Bearing Construction.



- We stock or can build the right drillhead for your jobs.
- Write for your free copy of the THRIFT-MASTER CATALOG or phone for a rush, on-the-spot quote.

Also Makers of DORMAN Automatic Reverse Tappers



1030 N PLUM STREET • LANCASTER, PA Use postpoid card. Circle No. 323 colleges, church and fraternal groups, service clubs, employee meetings, etc.

The planning of the movie has been under the direction of a special NMTBA committee, chairmanned by Rowell A. McCleneghan, adv. mgr. of the Barber-Colman Company, Other members of the committee are: Ross T. Beirne, adv. mgr., Giddings & Lewis Machine Tool Co.; Harry H. Gotberg, vice-pres., engineering, research, Colonial Broach & Machine Co.; James T. Harrington, Secretary, E. W. Bliss Co.: Alphons J. John. manager, employe & community relations, Kearney & Trecker Corp.: Robert D. Lawson, vice pres. & sales mgr., Grinding Machine Div., Norton Co.; Carl J. Linxweiler, advertising & sales promotion manager, the Sheffield Corp.: Frank W. Pensinger, advertising manager, the Monarch Machine Tool Co.; Charles M. Reesey, vice pres., Cincinnati Milling and Grinding Machines, Inc.; Chauncey P. Terry, advertising manager, the Hydraulic Press Mfg. Co.

Development of Twist Drill

A new 16mm 20-minute color sound film, "Pioneers in Precision," highlights the development of the twist drill from the time of its invention by Stephen A. Morse, founder of the Morse Twist Drill & Machine Co., New Bedford, Mass., through the growth of the Morse line and organization to its present position in the cutting tool industry.

CAM MILLING

Fully equipped modern machine shop with extensive Jig Boring, Surface Grinding, Horizontal Boring and Thread Grinding facilities as well as modern Cam Milling and Cam Grinding equipment.

Your Inquiries Answered Promptly

HIMOFF MACHINE CO., INC. 23-22 44th Rood Long Island City 1, N. Y.

Use postpaid card. Circle No. 324

MACHINE and TOOL BLUE BOOK

Boring Head Design

A new color-sound strip film on the design, construction and application of high-precision boring heads has been released by Briney Mfg. Co., 1165 Seba Road, Pontiac, Mich. Boring heads designed around the Briney principle can be adjusted in increments smaller than 1/10,000-inch without loosening or tightening any screws.

The film's running time is 11 minutes. It is suitable for showing to any size technical group interested in new tooling methods and applications. It can also be adapted to training machine operators in the proper use and mainte-

nance of these tools.

Concept and Principles Of Functional Drafting

A new 20-minute 16 mm, sound motion picture provides a graphic insight into the opportunities to make engineering drawings easier to draft, read and interpret.

The purpose of the film is to explain the basic concepts and fundamental principles of simplified draftinga technique that is already multiplying engineering output and making dramatic savings in thousands of companies of every size and type.

Further information may be obtained by writing to Gerard A. Glass. executive director, Industrial Education Institute, 25 Huntington Avenue,

Boston 16, Mass.

CAMS

To Your Specifications except Screw Machine Cams

Design Assistance Offered

KIDDE PRECISION TOOL CORP. 25 LOCUST AVE. ROSELAND, N.J.

Use postpaid card. Circle No. 325

TREATING

The Lucifer 7055 Series was designed for hardening, annealing, drawing, preheating and special applications, Produced in 13 standard models with heat ranges of 2,000°F. and 2,300°F., the 7055 Series operates on standard line voltage. No transformer is necessary. All models include . . ENERAL PURPOSE automatic controls, thermocouple. lead wire, magnetic contactor, horizontal swing door or vertical lift door, positive seal cam lock, cast hearth plate, long-life elements (low watt density), and our exclusive one piece monolithic holders that permit rapid element replacement at a minimum of down-

For a free brochure or engineering advice, write, wire or call . . .

LUCIFER FURNACES, INC. Neshaminy 1, Pennsylvania Diamond 3-0411

Use postpaid card. Circle No. 326

CD

April, 1959

181

Great Buys from

VICTOR

Extra Long, Straight Shank High Speed Drills

A	12"	OA,	9" FLUT	TE
SIZE	P	RICE	SIZE	PRICE
1/8		1.65	27/64	3.30
9/64		1.75	7/16	3.30
5/32		1.75	29/64	3.60
11/64		1.85	15/32	3.60
3/16		1.85	31/64	3.60
13/64		1.95	1/2	3.60
7/32		1.95	33/64	4.20
15/64		2.05	17/32	4.20
1/4		2.05	35/64	4.50
17/64		2.15	9/16	4.50
9/32		2.15	37/64	4.75
19/64		2.25	19/32	4.75
5/16		2.25	39/64	5.00
21/64		2.50	5/8	5.00
11/32		2.50	21/32	5.40
23/64 3/8		2.75	11/16 23/32	5.80 6.25
25/64		3.05	3/4	6.75
13/32		3.05		
18"	OA,	131/	2"-14"	FLUTE
SIZE	P	RICE	SIZE	PRICE
3/16		4.00	9/16	8.75
7/32		4.10	19/32	9.50
1/4		4.10	5/8	10.00
9/32		4.75	41/64	11.00
5/16		4.75	21/32	11.00
11/32		5.25	43/64	12.00
		5.25	11/16	12.00
3/8		3.63		
			45/64	13,00
3/8		6.00		13,00
3/8 13/32		6.00	45/64	

Order Today
IMMEDIATE DELIVERY!

VICTOR MACHINERY EXCHANGE INC.

Dealers in Tool Room Equipment 251 CENTRE STREET, DEPT. DA Tel.: CAnal 6-5575. New York 13. N.Y.

Use postpaid card. Circle No. 328

Hydra-Feed Lathe

A new color and sound motion picture entitled "Key To Machining Versatility" presents the Bullard Hydra-Feed lathe. The film clearly demonstrates the versatility of this machine tool, either as a tracer or multiple tool model.

Reservations for showing the film can be made by contacting the advertising department of the Bullard Co., Bridgeport 9. Conn.

NMTBA Lists Films Available

Of the 147 motion picture films on machine tools and machining operations listed in a 26-page booklet just published by the National Machine Tool Builders' Association, 84 are in color. Ranging in showing time from 5 to 70 minutes (average time about 30 minutes), all films are available without charge upon request to the member companies producing them.

With few exceptions, all films are 16mm., with sound. Many are in such demand that it is suggested requests for their use be made three to four weeks in advance of an intended showing.

Copies of the new booklet listing the films are available from the National Machine Tool Builders' Association, 2071 East 102nd St., Cleveland 6, Ohio. Requests for an individual film, however, should in all cases be directed to the member company concerned.

IMMEDIATE DELIVERY!





Cadmium plated, large selection of styles and sizes. Specials on request. Send for FREE catalog.

MACHINE PRODUCTS Corporation

Use postpoid cord. Circle No. 329

MACHINE and TOOL BLUE BOOK

17/32

NEW Enterprise

36-inch Band Sawing, Filing and Polishing Machine

- . Tool selector for 57 different materials
- . Convenient front controls
- Quick, automatic tension-release mechanism
- · Foot-controlled automatic feed
- Aluminum disc wheels reduce fly-wheel effect
- Upper wheel moves on machined dove-tailed ways
- No main power waste; separate air pump
- Built-in band welder with grinder and shear
- Sealed-for-life upper wheel bearings
 \$4595 including built-in welder

A custom-built metal supply cabinet is optional equipment.



Available through exclusive distributors in principal cities.

equipment.

Write for Bulletin 303

Exclusive
Distributors
of the
Enterprise
36-inch
Band Sawing,
Filing and
Polishing
Machine



THE ENTERPRISE COMPANY

Columbiana, Ohio

Since 1878

CLEVELAND

Wm, K. Stamets Company

DETROIT

The Chas. A. Strelinger Co.

KANSAS CITY

Haman Machinery & Supply, Inc.

LOS ANGELES

W. F. Wolf Machinery Company

PITTSBURGH

Wm. K. Stamets Company

SAN FRANCISCO

Bulotti Machinery Company



An extremely versatile, capable and fast, production tool for turning precision parts. Increases pieces per hour, lowers cost per piece. Lower tool investment, saves floor space, reduces power costs. Easily operated by anyone. Rapidly pays for itself in added profit. The extra capacity makes the lathe ideally suited for either high speed precision collet work or as a chucker.

This tool can be your answer to today's competition.

10", 11" and 13" Sheldon Lathes . Sheldon Variable-Speed Lathes * 13" and 15" Sebastian Geared Head Lathes . Sheldon Milling Machines . Sheldon Shapers.

Write for Turret Lathe Circular and General Catalog

& Push Button speed selection

- * Heavy duty power driven variable speed drive
- * Handwheel 6-station, 6 1/2" stroke bed turret
- * Lever-operated cross slide with front and rear tool blocks
- * Lever-operated 1-1/16" draw bar collet attachment (1 3/4" hole through spindle)
- * Zero-Precision taper roller spindle bearings
- ★131/a" swing over bed ways
- * 2-HP Motor
- * Complete Line of accessories and attachments

SHELDON MACHINE CO., Inc. 4242 N. Knox Ave. Chicago 41, Illinois

What's New in Metalworking


Eight-Station Rotary Handles 24 Machining Functions

This custom 8-station rotary index machine is processing oil pump bodies at a net rate of 68 pieces per hour. Machining operations are performed in both sides of the pump body and include spot facing, milling, drilling, tapping. reaming and core drilling. The material is gray iron, and critical dimensions-both roughing and finishing-are held to close limits.

The machine table is arranged with a set of eight 2-position work holding fixtures. Each side of the fixture is

equipped with an individual set of hydraulically operated, cam locked clamping members and manually actuated back-up jacks to rigidly hold and support the part. In order to perform the operations required on each side of the workpiece, the body is initially mounted in the l. h, side of a fixture and cycled through the machine. Upon returning to station 1, the part is then re-loaded in the r. h. side of the fixture and re-cycled through the machine.

The machine base and columns are of welded steel construction. A shot pin locates the indexing work table. Station 1 is, of course, reserved for loading and re-loading. Station 2 is arranged with a horizontally mounted slide for milling the flat surfaces of the part. A vertically mounted drill head and bushing plate assembly per-



Over-all view of the 8-station rotary index machine showing the machining slides in relation to the indexing worktable.



Performs operations on this cast-iron pump body.

forms a series of drilling and reaming operations at stations 3, 4, 5 and 6. An angularly positioned unit is utilized to bore the cored hole at station 7 and a vertically mounted head carries the taps at station 8.

Machine was built by the Ex-Cell-O Corp., 1200 Oakman Blvd., Detroit 32, Mich.

Faceplate Lathe for Large, Light Workpieces

Ravensburg faceplate lathe with baseplate is reported to provide an efficient and relatively inexpensive means of machining extremely large yet comparatively light workpieces. Its most economical application is in the turning and facing of large diameters, e.g., in the machining of missile bodies, steam turbine runner discs, and generating

plant, mining and shipbuilding equipment.

Headstock, baseplate and bed units can be built to meet specific requirements. The headstock is supplied with a 12-18 step gearbox containing hardened and ground gears; it is also available with mechanically or electrically controlled stepless speed variators. The baseplate is not connected to the headstock and has a built-in tailstock slideway. In addition, combined V-flat ways are provided for centering the bed either parallel or perpendicular to the turning axis. For machining long tapers or nose cones, provision is made to position the bed at any angle to the turning axis.

Saddle and cross-slide feeding is available in either inches/min. or inches/rpm. Feed gear drive originates from the main gearbox by means of an electrical shaft system that eliminates any mechanical connection between bed and headstock. Thus, only an electric cable is connected to the separate feeding motor on the saddle, so that a true and accurate feeding motion is reproduced as a function of spindle rpm.

The upper slide on the cross slide is mounted on a turn-table and feeds automatically at any angle within 360°. The top toolholder slide is hand adjust-



Ravensburg lathe. Economically turns and faces missile bodies.

able. The cross slide can also be provided with an optional hydraulic or electronic-hydraulic copying attachment for accurate reproduction of contours from a template.

Turning diameter over baseplate, 80-110 inches. Turning diameter over pit, according to pit depth. Weight of workpiece, unsupported, center of gravity 12" from faceplate, 6500-20,000 lb.

Cosa Corp., 405 Lexington Ave., New York 17, N.Y.

Use postpaid card. Circle No. 82

Surface Grinder for Close Tolerance Work

This extremely close tolerance surface grinder, for work on instruments, electronics and watches, features wheel head elevation control which is said to read to .0001" by means of a vernier. Transversal vernier is reported to read to .0005". Very fine laminations on the magnetic chuck securely hold the smallest parts. There is a built-in demagnetizer.

The wheel head elevating mechanism is totally enclosed against grit and dirt. The spindle is mounted on four selected ball bearings and has provisions for automatically removing play.

Specifications include: magnetic chuck surface, 4½"x6"; table travel, transversal, 4½", longitudinal, 8"; vertical



Close tolerance surface grinder.

movement of wheel head, 5"; diameter of grinding wheel, 434". The maximum height between chuck and wheel is 4". The weight of machine is 230 lb. without pedestal.

The American LIP Corp., Room 704, 610 Fifth Ave., New York 20, N.Y.

Use postpaid card. Circle No. 83



SHOP IN ONE MACHINE PULLMAX DOES ALL OF THESE OPERATIONS



★ CUTS MILD STEEL UP TO 11/32"

The one machine that's sure to save time, labor and material when you work sheet or plate. Eliminates expensive die costs—easy to operate. 7 sizes to choose from.

Visit us in Booth 5, Int. Petroleum Exposition, Tulsa, Okla., May 14-23.

Write for free catalog on Metalworking Ideas.





AMERICAN PULLMAX CO., INC.


2473 N. Sheffield Ave., Chicago 14, III.
Use postpaid card. Circle No. 331

Metal Lathe Features Variable-Speed Drive

A Delta 10" metal cutting lathe for heavy duty work features a variablespeed drive and 34" collet capacity. The drive is said to give the operator all the advantages of infinitely variable speed from 50 to 1500 rpm, plus the high torque transmitting power of matched V-belts in the final drive to the spindle. The 3/4" collet capacity, re-



34" collet capacity



In a word, plenty.

They can make your taps last up to six times longer.

They reduce work spoilage because they enable taps to cut more accurately, more uniformly, with less strain.

They can cut your present tap costs up to 65%. We didn't get these facts out of thin air. They come from actual case histories in metalworking plants where taps are sharpened regularly with Blake Flute and Chamfer Grinders.

These are high-precision machine tools. But they are not expensive. And they're simple enough to operate so that anyone in your plant can become accomplished at precision tap grinding with a minimum of fuss and feathers.

WANT PROOF? Just ask for it. You'll be glad you did.



Blake Chamfer Grinder/Blake Flute Grinder

Blake - and only Blake Flute and Chamfer Grinders, used in combination, create or restore: 1. exact indexing of cutting edges 2. controlled rake angles for each job 3. correctly ground spiral points 4. perfectly relieved chamfers . . . make one tap do work of six!

EDWARD BLAKE COMPANY, INC., 440 CHERRY STREET, WEST NEWTON 65, MASS.

ported as larger than any other lathe in its class, is obtained by using a 4-C style collet with a 15/16" hole through the spindle.

Features include a massive, double row, preloaded, inboard spindle ball bearing which is reported as sealed against dirt and lubricated for life; a quick change gear box which provides a choice of 54 feeds or thread pitches, and the variable-speed drive which can

be preset on the job to whatever high or low speed limit is desired in either direct or gear drive.

The lathe is used with a full ³/₄ hp motor and optional Delta bench which has adequate space for separate mounting of the motor.

Rockwell Manufacturing Co., Delta Power Tool Div., 451 N. Lexington Ave., Pittsburgh 8, Pa.

Use postpaid card. Circle No. 84



TAP with the quadtapper



turret. A real time and cost saver!

Send for complete details of both QUADRILL and QUAD-TAPPER construction and operation features. By attaching the QUAD-TAPPER to any of the four spindle assemblies of the QUADRILL, you can drill and tap almost simultaneously. Affords accurate tapping at high speeds. DESIGNED FOR PRODUCTION COST CUTTING

CHICAGO QUADRILL

Company

1846 BUSSE HIGHWAY . DES PLAINES, ILL.



ENCO Self-Indexing HEXTURRET

Convert your lathes for turret work this quick, easy way. ENCO HEX-TURRET gives you the accuracy, rigidity and speed you need to step up lathe production and cut "per piece" costs. Easy as mounting your lathe tailstock. Does both normal and heavy lathe and screw machine work, drilling, counter boring, counter sinking, spot facing, reaming, turning, boring, etc. Fit all lathes 9" to 16" swing.

Mail coupon for cat. #53 and name of nearest Enco Franchise Dealer.


ENCO Mfg. Co. 4520 W. Fullerton Chicago 39

4520 W. Fullerton, Chicago 39. Dept.	249	1	23	ONO	M
Please send catalog ENCO HEXTURRETS.	#53	and	full	details	of
Name					_

Use postpaid cord. Circ'e No. 334

Fluid Powered Drive

Fluid powered one revolution drive produces smooth, quiet, instant high torque through fluid motor, planetary reduction and solenoid actuated starter. Has built-in valve to compensate dur-



ing movement and unload while stationary. Cam and adjustable finger lever arrangement are said to provide rapid, smooth acceleration and deceleration as well as positive stop. Drive may also be arranged for manual or mechanical starting, or multi-revolution operation. It is available in a wide range of output torque capacities and speeds.

Applications: An accurate and automatic intermittent drive for indexing motions, feeders, turntables, packaging machinery, office equipment, and unlimited others.

Constant-Flo Div., John S. Barnes Corp., 301 S. Water St., Rockford, Ill.

Use postpaid card, Circle No. 85



Put Muscles In Your Lubricants

ANTI-FRICTION COMPOUND


A clean white powder. Improves cutting oils. Dies last longer. Solves tough lubrication problems. Ask for free samples.

SCIENTIFIC LUBRICANTS CO. 3469 N. Clark St. Chicago 13, III.

Use postpaid card. Circle No. 335

Address_

NEW CLAUSING



12% " swing, 1-1/16" collet capacity, ASA—L-00 spindle nose, "Zero Precision"Timken tapered roller bearings, flame hardened bed ways, ball bearing collet closer, 1% constant HP two-speed meter.

Hi-Speed (3200 RPM) Lathes with Hydraulic Feeds Variable Speeds

- infinitely variable spindle speeds up to 3200 RPM.
- hydraulic feeds on carriage, double tool cross slide, tailstock ram.
- · each feed is independent and infinitely variable.
- requires minimum of mechanical skill to produce precision parts — feeds are controlled thru levers, positive staps assure accuracy.
- law price includes machine, electricals and hydrautic system — completely assembled, wired, ready for installation.

The new Clausing is a first! There's nothing like it, and its productive capacity is sensational. Send for complete details today.

Hi-Speed (3200 RPM) Lathes with Hand Feeds

Variable Speeds

- · spindle speeds, infinitely variable up to 3200.
- six models, with choice of laths with six-station Timken bearing equipped bed turret and double tool cross slide ... with double tool cross slide and tailstock with lever-and-wheel feed ... or with precision compound and tailstock with lever-and-wheel feed.
- 12 %" swing, 1-1/16" collet capacity, ASA— L-00 spindle, Timken "Zero Precision" tapered roller bearings, flame hardened bed ways, ball bearing collet closer.
- built to rigid specifications for precision performance.
- outstanding in value low price includes motor and electricals, with machine assembled, wired, ready for installation.

The new Clausings are FAST . . . HIGHLY AC-CURATE . . . and LOW IN COST. They'll pay out quickly in your production department, tool room or laboratory. Investigate before you invest in any high speed lathe.



1-1/16" callet capacity hi-speed hand turnet lathe illustrated

Also available: Clausing hi-speed lathes with ½" collect capacity, spindle speeds from 250 to 3500 RPM. Prices, with electricals, stars at \$935 f.o.b. factory.



CLAUSING DIVISION

ATLAS PRESS CO.

KALAMAZOO, MICHIGAN


Use postpaid card. Circle No. 401

4-107 N. PITCHER ST.

Heavy Duty Band Machine Adapts to Diverse Applications

The Model C-24 power saw, available with a selection of work handling devices integrates a 24" x 24" capacity cutting head, main vise, hydraulic system, coolant system and movable control console. A 15 hp drive furnishes ample power for the cutting potential of 2" wide Demon high-speed steel saw band. A hydraulic motor drive provides variable tool speeds of 20 fpm to 200 fpm saw band velocity range. The controls for the drive are in a movable console.

enabling the operator to always view the work from his control station. A tachometer and infinitely variable speed and feed controls enable him to monitor



Drawing shows how power, rigidity is provided for 2" hss saw band.

the operation for maximum cutting rates and saw band life. Console mounting of the vise controls and work handling controls gives supervision of whole job.



THINK of it!

NOW you can have a boring head that will BORE, FACE, TURN and GROOVE at no higher cost than you would pay for an ordinary, single purpose boring head.

THINK this over before buying that new head!

Models for Any Size Machine
Write today for full details
CHANDLER TOOL COMPANY
MUNCIE, INDIANA

A Boring Head That Won't Face is NOT Complete



Chandler Duplex


The basic machine includes a roller table on the load side of the saw band with or without powered rollers. Up to 60 ft. of powered conveyor tables can be added to both the load and unload side of the basic machine, and additional runout tables can be added to the motorized units as far as required. The powered conveyor tables are reversible and controlled from the main control console. Either standard 3400 lb. or heavy duty 10,000 lb. capacity rollers

may be specified, and they may be hardened and ground for severe applications.

DoAll Co., Des Plaines, Ill.
Use restpaid card. Circle No. 86

Miniature Parts Grinder

The Miniature Centalign Model B internal grinder is built specifically for grinding bores in miniature bearing races and internal ball tracks in miniature bearing outer races. Of com-



MASTER BALLS

- For simplified checking of hole depth, ID's, internal tapers — locating holes and internal grooves — many other applications in shop, tool room and gage room.
- Accurate to .000010" on size and sphericity. Hardened and cold-stabilized for lasting precision.
- Furnished in sets or individually ¾" to 1" or larger.

FREE BULLETIN 552 gives methods and formulas for hole-checking, and details on Master Balls. Write for it!

INDUSTRIAL TECTONICS, Inc.



MANUFACTURERS OF PRECISION BALLS AND BEARINGS

3685 JACKSON ROAD ANN ARBOR, MICHIGAN



EXTERNAL HONES

SAVE MANY HOURS IN YOUR TOOL ROOM OR MACHINE SHOP

They produce exact size, mating fit or surface finish on O.D.'s of ... plug gages, shafts, arbors, spindles, pistons, plungers, leader pins, ejector pins . . . many others.

Guaranteed to produce geometric accuracy to "split-tenths" with surface finish as low as 2 micro-inches.

They correct all errors such as waviness, centerless grind chatter, bow and taper, Invaluable in production, job lot or tool room work.

They combine speed of honing with precision of lapping. Parts to be honed can be driven by lathe or Sunnen Honing Machine.

Available in 4 sets:

1/4" - 13/32", 13/32" - 13/16", 13/16"-11/2", 11/2"-23/4" diameters.

WRITE FOR FREE BOOKLET

Find out how SUNNEN **EXTERNAL HONES**



Use postpaid card. Circle No. 339



Miniature Centalign Model B internal grinder.

pact design, the machine requires only 81/4 sq. ft. of floor space.

Workpieces are automatically loaded, ground and unloaded by means of the new disc drive shoe centerless fixture, which provides interchangeable "packaged tooling" that can be set up away from the machine if desired. This allows almost uninterrupted machine operation and eliminates the need for long periods of downtime required to retool for workpart changes.

Bryant Chucking Grinder Co., Springfield, Vt.

Use postpaid card, Circle No. 87

SOLID HEAD CARBIDE BORING BARS

- Precision made with double brazed head for extra long teol life.
 Face grinding only, necessary to resharpen solid head—greater service at lower cost.
 Longer shank at no extra cost.

 Ideal for precision Jig Boring Opera-tion—Boring and Facing shapes available.

WRITE FOR LITERATURE AND PRICE LIST Dealer Inquiries are invited.

TITAN TOOL SUPPLY CO., INC. 1419 Hertel Ave., Box T, Buffalo 16, N.Y.

Use postpaid card. Circle No. 340

MACHINE and TOOL BLUE BOOK

WHY BUY METAL YOU DON'T USE?

Switch to **Allegheny Ludlum** Cast-to-Shape Tool Steel



Stepped-out forging for fabricating spinning cone: 2300 lbs.—\$2691 material cost plus cost of machining.



CAST-TO-SHAPE

Cast-to-shape spinning cone 1059 lbs. \$860.97 Includes cost of the pattern.

\$1,831 Saved by changing to Cast-to-Shape

Why pay for metal that ends up as chips on your floor? Here are two fine reasons for switching to Allegheny Ludlum cast-to-shape tool steels.

CAST-TO-SHAPE MEANS

YOU BUY FEWER POUNDS OF METAL.

Because the tool you buy is closer to its finished shape, you obviously spend less money on original metal. In the above example, the savings in metal cost alone amount to \$1,894.

CAST-TO-SHAPE MEANS

LEBS FINISH MACHINING.

A casting like that above has only 1/4 to 3/4 inches of machine stock on all surfaces, requiring very little machining compared to solid chunks. Cast-to-shape tooling is especially economical when working with intricate shapes.

Allegheny Ludlum, a tool steel producer who makes

cast-to-shape materials, casts them with the same precise quality control for which their tool steels is known. A full line of cast-to-shape tool steel grades is available. You'll find ones with high resistance to abrasion, compressive strengths of approximately 400,000 psi, easy machinability, hardening with almost no distortion, toughness, high red hardness, and the capacity to take a high polish.

Find out now how you can cut costs on your complex tools. Write for FC-4, a 28-page technical discussion of A-L's Forging and Casting Division with applications, pattern information, design tips, analyses, and heat treating instructions. Or call your nearest A-L. tool steel warehouse or distributor.

ALLEGHENY LUDLUM STEEL CORPORATION. OLIVER BUILDING, PITTSBURGH 22, PENNA. Write to Dept. MB-16.

WSW 7270

ALLEGHENY

Tool Steel warehouse stocks throughout the country . . . Check the yellow pages EVERY GRADE OF TOOL STEEL ... EVERY HELP IN USING IT

Two Dimensional Carriage Tracer for Turret Lathe

This hydraulically controlled tracer offers four automatically controlled tracing cycles. It will trace through 180° of tool travel while turning, with feed being either toward the headstock or away from the headstock. It will also trace through 180° of tool travel while facing, with feed being either toward the spindle center line or away from the spindle center line. Roughing and finishing tracing tools can be used

from the indexing square turret.

Complete size control for diameter is accomplished with the conventional graduated hand wheel for either tracing or mechanical operations.



Tracer offers four automatically controlled tracing cycles.

The tracer can also be used as a taper attachment. With a suitable threading device, it will produce tapered threads.

Feed limits are from ½" to 18" per minute. Feed can be changed by a



single control, even while machining. Turning capacity of the tracer is the same as the mechanical capacity of the machine in 20" increments. Facing capacity in either turning or facing cycles is up to 6" radius change.

Jones & Lamson Machine Co., Spring-


field, Vt.

Use postpaid card. Circle No. 88

Automatic Numbering

A new combination marking and numbering machine meets REA requirements of consecutive footage marking and numbering on trench wire or cable. It consists of two separate units: (1) to provide the marking of consecutive numbers and trade mark or code marking; (2) to provide controlled drive and measuring mechanism.

The numbering and marking head comprises a rotating member on which has been mounted a barrel type automatic numbering head and an interchangeable die holder. The numbering



Six machines protected from dust by Torit for \$666 15


This Torit Dust Collector, Model 219FM, complete with accessories, was installed by the Mohr Lino Saw Co., Skokie, Ill., to protect 3 belt sanders and 3 other grinders (2 grinders hidden from view) from destructive dust—at a total cost of just \$666.15!

After one year's operation, Mohr Lino Saw says this about their *low-cost* Torit installation: "The Torit installation has kept our shop *cleaner*, our operators *happy*, and *protected vital* machinery."

You too can achieve greater machine protection and cleaner working conditions by trapping dangerous or valuable dust at its source with a completely self contained and portable Torit Dust Collector. For full details write to:

TORIT MANUFACTURING CO. Dept. 603 311 Walnut Street, St. Paul 2, Minn.





Consecutive footage marking on trench wire, cable. head advances consecutively and numbers every two feet: 1002, 1004, etc. The die holder is located 180° from the numbering head in the rotating member and both the numbering and marking members are heated by means of a radiant heater with three-step. heat control.

Characters are ½" size and numbering head has to be reset every 99,998 feet. Cable sizes of ½" to 3" diameter are marked at speeds of about 300 ft. per minute.

The Acromark Co., 15 Morrell St., Elizabeth, N.J.

Use postpaid card, Circle No. 89

Improved Magnetic and Fabric Coolant Filters

The new line of Kleenall combination



Model MP-20 separator with trough type distributor tank and pump.



magnetic and fabric coolant filters features increased clearance between the filter fabric and distributor, which provides increased capacity for handling heavy swarf loads.

A separate sun gear on the drum drive shaft has been provided for ease of adjustment. Other changes include the relocation of the drip plate to give greater clearance and better operation of the conveyor. Two supports at the base give lifting support during instal-

lation or moving, without damaging the conveyor belt and filter mechanism.

The improved filters are available in standard sizes and capacities as formerly offered.

Barnes Drill Co., Rockford, Ill.
Use postpaid card, Circle No. 90

Air System Optional On Lapping Machines

A manually operated air system has been designed for the Speedlap 18



Drill press vises, angle vises, swivel machine vises, rotary tables, lathe milling attachments, production vises, heavy duty angle vises, and adjustable angle plates are illustrated and fully described in the New Palmgren Catalog. This is the only complete line of work holding devices available anywhere. Designed for production, tooling, and maintenance work, there are 68 different models and types to choose from. Vise jaw sizes are from 1½" to 8". Ask for your copy of this FREE Catalog No. 205 today. The complete line with details and prices are shown.

PALMGREN PRODUCTS

by CHICAGO TOOL AND ENGINEERING CO.



Get This Production Boosting

"TRICO-MIST" COOLANT SYSTEM

With Flexible Armored Coolant Lines And Kwik-Change Nozzle With Guard.




For drilling, tapping, milling, sawing, grinding, etc. Removes heat from cutting edges of tools and work. Feeds can be increased considerably, finer finishes and accuracy are obtained. TRICO-MIST absorbs heat, thereby quenching it faster than flood coolants which only transfer it. Chips slide freely up the tool face and are blown away automatically. Simple needle valve controls size and volume of mist spray. Attaches to shop air line. Available with one and five gallon containers — single or multiple outlets — single or dual valve control.

SEND FOR BUL. 37

TRICO FUSE MFG. CO.

Use postpaid card, Circle No. 346



machine as optional equipment. It can be added at a slight extra cost to existing machines.

The machine, equipped with the air system, can readily lap such materials as carbide, ceramics, semi-conductors, aluminum, and other common materials. Like the larger Speedlap 32, parts are ready for lapping as sintered, cast, stamped or turned.

The machine is suited for aircraft and missile parts, electronic components, instrument parts, as well as valve and seal faces.

Abrading Systems Co., 8020 N. Monticello, Skokie, Ill.

Use postpaid card. Circle No. 91



GEARS In Stock—Immediate

Gears, speed reducers, spreakets, thrust bearings, flexible souplings, pulleys, etz. A complete line is carried in our Chicago stock, Can also quote on special gears of any kind. Send in your blueprints and inquiries.

Send for Complete Catalog No. 18a CHICAGO GEAR WORKS 440-50 N. Oakley Blvd., Chicago 12, III.

Use postpaid card. Circle No. 347

MACHINE and TOOL BLUE BOOK

OVER 2700 PLANTS are saving money with WHISTLER DIES



MAGNETIC PERFORATING DIES

All parts reusable and interchangeable. Punches and dies stocked in .001" increments from .100" thru .500". dia. Larger sizes available.



ADJUSTABLE PERFORATING DIES

All parts reusable and interchangeable. Punches and dies stocked in .001" increments from .100" thru .500" dia. Larger sizes available.



manufacturer of all types of CUSTOM DIES for over 40 years

WRITE FOR COMPLETE DETAILS

S.	B.	WHISTLER	& SONS	s, INC.,	746	Military	Rd.,	Buffalo	23,	N.	Y
Mail	the	following: 🗌 N	Aagna-Die	Catalog	_ A	djustable D	ie Ca	talog			

More information on custom die work

NAME_____TITLE__

COMPANY

CITY_____ZONE___STATE__



Internal Lapping Arrangement for Air Brake Parts

A Lapmaster Model 24 is shown equipped with a five-station lapping attachment for lapping of air brake valves and other air equipment. This radially mounted fixture permits lapping of valve faces on lapping table while reciprocating blocks internally lap valve seats. When the small lapping blocks go out of flat, they are brought into perfect flatness by reconditioning on lapping table.

The Lapmaster, equipped with this multiple fixture, is reported to permit precision lapping of a wide variety of internally lapped surfaces simultane-



Lapmaster Model 24, with five-station lapping attachment.

ously at a substantial cost reduction over hand lapping.

Crane Packing Co., Morton Grove Ill.

Use postpaid card. Circle No. 92

"OLIVER" NO. 838 PLATE SAW

PRODUCTION SAW

for precision cutting of plates and sheets of all sizes up to 6" thick




NOW, good clean cuts within tolerance for nonferrous metals



For cutting aluminum, bronze, micarta, copper and other nonferrous metals . . . adaptable to individual requirements, yet provides economy of operation . . . satisfies rigid demand for accurate work and fast cutting. Send for illustrated folder giving full details.

OLIVER MACHINERY COMPANY

GRAND RAPIDS 2, MICHIGAN







kpert setup gets more work per chucking

How manufacturer uses C/F turret lathe to produce variety of chuck bodies with only one tool change

the job, the manufacturer selected a Gisholt 1L le Type Turret Lathe with a cross-feeding hexagon t. A 15" 3-jaw air chuck holds down chucking time. set of adjustable serrated jaw bases handles the ent workpiece sizes for first machining operations. ick-indexing square turret on the cross slide carries ng, facing and chamfering tools, which work simulnusly with tools on the hexagon turret.

ree stub boring bars on the hex turret bore, counterrecess and back face. Because size is set with the l-feeding turret, these same boring bars are used on ent part sizes. Also on the hexagon turret are 2 type tool posts for facing, boring or recessing—used ifferent size workpieces because of the cross-feeding feature. A threading attachment lets the manufacturer thread the hubs, and a taper attachment handles up to 8 inches taper per foot when required.

The sixth tool on the hex turret, a spade cutter, is used for final sizing and is the only special tool changed for each job.

Simple, low-cost tooling combined with the cross-feeding hexagon turret offers maximum efficiency in handling various sizes of similar parts. The rugged Gisholt MASTERLINE Saddle Type Turret Lathes have the speeds, feeds and power to complete the work in the least amount of time. Call your Gisholt Representative today, or write Gisholt for literature.



MACHINE COMPANY

WRITE TODAY for complete set of Gisholt MASTER-LINE Saddle Type Turret Lathe Bulletins.

Madison 10, Wisconsin

Investigate Gisholt's Extended Payment and Leasing Plans

Turret Lathes • Automatic Lathes • Balancers Superfinishers • Threading Machines • Factory-Rebuilt Machines with New Machine Guarantee


Four-Way Machine Accepts Ten Different Part Sizes

Four-way vertical indexing drilling and tapping machine features a 20-inch square fixture mounting area which raises and lowers automatically to various machining stations. Developed for a motor manufacturer, the versatile machine accommodates ten different motor frame bracket sizes.

Utilizing three 12" way type hydraulic drill units and an Air-Oil-Matic drill unit equipped with a turret head. the machine makes 21

drilling and 21 tapping operations in one completely automatic cycle. The operator simply loads the part and presses the cycle start.

The cycle takes only 30.5 seconds.



Fixture mounting area raises, lowers automatically to various stations.

To adjust the fixture to the different frame sizes, the operator simply interchanges the fixture adapter plate, which compensates for the various centerline heights of the parts, and adjusts the



ETTCO-EMRICK

uckle-heads


fully adjustable for dependable multi-hole drilling and tapping

5 models to choose from circle or straight line types

- Chrome nickel universal ball joint type spindles.
- · Adapt to any drill press or drilling or tapping unit or machine - Operate in any position.
- · Quickly convertible for either drilling or tapping on any drill press.
- · Lubricated ball joints with
- neoprene covers an Ettco exclusive.
- Tap or drill capacities up to in steel.
- · Precision built, lightweight and compact.

Unconditionally guaranteed for workmanship, material

and performance.



ETTCO TOOL & MACHINE CO., INC

596 Johnson Avenue, Brooklyn 37, N.Y.

Chicago . Detroit . Los Angeles . Indianapolis . Hartford

lamping fingers. Slip spindle heads are utilized to facilitate altering of the arious spindle centers required.

Morris Machine Tool Co., 2011 Eastrn Ave., Cincinnati 2, Ohio.

Use postpaid card. Circle No. 93

Expansion, Compression Equalized on Way Guards

Can-Pro accordion way guards, made o specifications, protect ways, cross ails, moving and sliding assemblies against wear and damage caused by abrasive flying materials. With the guards, clean fresh lubricant can be retained while excluding chips, grit, dust, chemicals, and paint.

The guards are fabricated from Butapren, a special synthetic rubber which is reported to have better abrasion resistance, oil and gasoline resistance, and water resistance than Neoprene. Butapren has proved to be five times stronger than rubber and three times



PRECISE PRODUCTS CORPORATION

3731 Blue River Road, Racine, Wisconsin, U.S.A. Branch Plant, G.m.b.H., Duesseldorf, Germany


THE BEST

PORTABLE

ELEVATING TABLE

YOU CAN BUY . . .

(Eliminates Cranking)



2000 LBS. OR *1000 LBS. CAPACITIES *ILLUSTRATED

A precision made MIDWEST TABLE Costs no more!

- It's hydraulic . . . positions work or feeds at desired height without use of hands
- Rigid cast construction
- ▶ Top turns 360° and clamps
- Foot release valve to lower
- Machined top surface can be used as work table
- Roller bearing casters with ball bearing swivels
- Floor clamping available extra

Write today . . . specials on request



112 WEBSTER ST., DAYTON 2, OHIO Use postpaid card. Circle No. 353 better than Neoprene, the guard manufacturer claims. The material has a high degree of flexibility and softness which permits the guards to be compressed into small spaces. It will withstand temperature changes from —45°F to 220°F without cracking.

The way guards are designed to expand and compress equally with the movement of the machine, regardless or position: vertical, horizontal or angular This feature (each accordion fold expanding equally and simultaneously helps to double life of guards.

Can-Pro Corp., Fond du Lac, Wis.

Hydraulic Power Unit Is Manifold-Circuited

Circuitpak, a low-cost hydraulic power unit, is manifold-circuited for



Hydraulic power unit.

JIG BORING

and

Large Precision Machining

Done to your specifications

WE HAVE 22 JIG BORERS

KIDDE PRECISION TOOL CORP.
25 LOCUST AVE. ROSELAND, NJ.

Use postpaid card. Circle No. 354

MACHINE and TOOL BLUE BOO

lirect connection to cylinder lines.

Four pump capacities from .8 to 5 gpm are available with 1, 1½ or 2 hp capacitor-start electric motors and up to four solenoid-operated four-way valves. Operation is at 3600 rpm with pressures up to 1000 psi.

Circuitry employs series connection of valves, and oil is blocked from all valves farther down the circuit when any valve in the series is shifted. Return lines are ported directly to the tank. To eliminate overheating when valves are in neutral position, pump discharge is circulated at negligible pressure.

Brown & Sharpe Mfg. Co., Providence, R.I.

Use postpaid card. Circle No. 95

Double-Acting Hydraulic Press

A 700-ton, double-acting hydraulic press is reported to hold parallelism to

The WELLS Model 600 Metal Cutting Band Saw

for Tool and Stock Room Service

for Medium Production Jobs



Rugged in design, dependable in operation, the Wells Model 600 is the ideal saw for tool and stock rooms . . . gives excellent service on medium production jobs. Uses 5/8" blade. Adjustable, uniform gravity feed is provided by hydraulic stabilizer and special coil spring. Casters available for portability. Write for Bulletin 260-A.



The Pioneers of Horizontal

METAL CUTTING BAND SAWS

WELLS MANUFACTURING CORPORATION 707 Coolidge Ave. Three Rivers, Michigan

True Conical Grinding on a STERLING Drill Grinder gives you Faster Cutting Drills and More Holes per grind

Conical grinding of a drill point produces the same clearance angle from O.D. to web. The drill enters the work easier. cuts a uniform chip that requires less pressure, less power.



90°-140° Included angle, variable clearance angle set with built-in gage. Grinds 1/6" to 21/2" drills; 2, 3 & 4 flutes.

Set-up is simple and fast because no chucks or collets are used. Built-in diamond wheel dresser produces a finished cutting edge that stands up longer. You get more, accurate holes with drills ground on a STERLING "DV".

Ask your STERLING Dealer for complete information on all STERLING Drill Grinders or write direct

McDONOUGH MANUFACTURING CO.

1520 GALLOWAY . EAU CLAIRE, WISC. Use postpaid card. Circle No. 356

Hydraulic press.


less than .002" over the full area under full load. Specs. include: down-acting 21" daylight, 15" stroke, usable plater area of 26"x30". Strokes up to 60", and controls to fit individual requirements are available.

Allied Engineering and Production Corp., 2421 Blanding Ave., Alameda Calif.

Use postpaid card, Circle No. 96

Automatic Machine Forms Conical, Contoured Parts


The No. 12 vertical Floturn machine is specifically designed for high production of parts ranging up to 16" in



DANNEMAN DIE SET DIVISION

Acme-Danneman Company, Inc. 203 Lafayette St., New York 12 . AL 5-7150 Use postpaid card. Circle No. 357

MACHINE and TOOL BLUE BOOK



Vertical Floturn forms parts to 16" dia., 15" long.

diameter and to 15" in length. It features an automatic cycle which may include automatic loading and unloading. The vertical design incorporates radially opposed "Dual-Sincro" rollers which are claimed to virtually eliminate deflection and assure extreme accuracy. Automatic hydraulic tracer control is provided to make production of complex shapes a push-button operation.

The machine produces conical, cylindrical, contoured shapes or combinations of these shapes from flat blanks, preformed blanks or machined blanks, working virtually any metal or alloy with speed and ease.

The metal-flowing rollers are synchronized; they work in the same plane, opposed to each other to eliminate deflection. The machine works on the sine law (where the sine is the instantaneous angle between the centerline of the spindle and the tangent to the contour at the point of roller contact).

Manual loading and unloading is expedited by the easily accessible working area. Setup has been simplified to require as little as 45 minutes time.

An inter-relation between the ma-

1 MACHINE marks all your parts

Have a variety of parts to mark? Need equipment that's versatile enough to handle all of them? Then, you're talking about the Matthews' No. 240 Hydra- Pneumatic, General Purpose Marking Machine! Marks round, flat—even contoured parts.

Write today for Bulletin 146-C6.

JAS. H. MATTHEWS & CO.
3946 Forbes Ave. Pittsburgh 13, Pa.



chine's ram (which holds the workpieces) and the template supports automatically adjusts template position to compensate for the smallest practical variation in blank thickness. When the variation is not compensated, the manufacturer states, as little as .003" variation may result in unacceptable workpieces, particularly on thin-wall pieces.

The Lodge & Shipley Co., 3074 Colerain Ave., Cincinnati 25, Ohio.

Use postpaid card, Circle No. 97



BY A QUICK, EASY INEXPENSIVE METHOD Your business letterhead will bring literature WATTS BROS. TOOL WORKS Wilmerding, Pa.

Use postpaid card, Circle No. 359

Step Collet Cuts Costs 80%

This step collet, comprised of a master collet with replaceable jaws, can reduce collet costs 80%, the manufacturer reports. The unit fits all lathes using standard 5C collets. Precision machined



Step collet fits lathes using standard 5C collets. radial groove affords accurate relocation of jaws for rerun jobs, thus saving time and effort in setups.

Soft jaws are finished in steel and aluminum. Special jaws in plastic teflon, brass or other material provide universal application for delicate work.

Crest Precision, El Monte, Calif.

Advance CROSS-SLIDE ROTARY TABLE for Vertical Milling Operations



High-Priced RESULTS for LOW-COST Investment

The Advance Cross-Slide Rotary Table permits fast, precise positioning of work-pieces from one set-up. Eliminated is the series of error-inducing multiple set-ups as done on conventional rotary tables.

Save 50% to 90% of Set-Up Time on Vertical Milling Precision, Heavy-duty Construction

Hundreds of Satisfied Users in Tool and Die, Missile and Aircraft, Nuclear, Electronics and Production Work

Call or Write for Complete Information

ADVANCE PRODUCTS CORP.

North Shore Drive

Benton Harbor, Michigan

WAlnut 5-8889

COMPARATOR GAGE

- Positive action through low-ratio initial amplification of 4:1
- Additional optical amplification of 250:1 = total of 1000x
- Rapid quantity gaging between adjustable colored tolerance masks
- Selective inspection from long range illuminated scale with 100 divisions
- Direct effortless reading in .00005"
- Variety of interchangeable anvils and contact tips
- Instrument also available for internal gaging

Request 8-page catalog 82-177



Use postpaid card, Circle No. 361

Precision Lathe for Toolroom and Production Jobs


The 19" Sabre all-geared head, precision gap bed lathe features: direct multiple V-belt drive; electrical equipment and controls; built-in electro magnetic brake for fast stops; 6/8 hp motor—

3/60/220. Headstock has standard range 12 spindle speeds, 20-1100 rpm. Quick-change gears provide 24 feeds.

Capacity 6"

Diameter

Index Industrial Corp., 150 Broadway, New York 38, N.Y.




19" Sabre lathe. Twelve spindle speeds; 24 feeds.

Thread Rolling Machine Handles Double End Studs to 13-1/2"

A Lanhyrol thread rolling machine has been developed to handle double end studs up to 13½" in length. Through extended spindles, the machine will produce these studs at rates of 102 3/8" to 9/16" and 80 5%" per minute.

The operation is performed by the continuous rolling method whereby the parts are automatically fed into the machine from an inclined magazine. They are held and carried into rolling position by an indexing workrest cage.

The thread roll dies



102 %" to 9/16" studs and 80 %" studs per minute.

are of the segmental type operating at a fixed center distance and held there hydraulically. Two parts are rolled per die revolution. Upon completion of the



VOGEL

TOOL AND DIE CORPORATION 1827 North 32nd Avenue
Melrose Park, Illinois

threading operation, the parts drop into a conveyor and are carried out the

front of the machine.

Two methods of rolling are available. The first and fastest is by segmental or cam periphery dies with mechanical indexing for parts up to and including %" diameter on either single or double end work and for ¾" diameter, single end only. In this range, combinations of coarse and fine pitches, left and right hand, large and small diameters

or identical threads may be rolled.

The second method available is used for work larger than 3/4" in diameter on one end only. Plain cylindrical infeed dies are used with an automatic infeed cycle and electro-pneumatic indexing is substituted for mechanical indexing.

A change-over from one diameter to another requires only interchanging the thread rolling dies, magazine chute rails and work carrying rings in the



indexing cage. Minor adjustment of the chute rails and indexing mechanism is needed when changing over to studs of different length but of the same diameter.

Landis Machine Co., Church & 5th Sts., Waynesboro, Pa.

Use postpaid card. Circle No. 100

Alarm Photographs **Burglar in Action**

Photolarm features a hidden camera that photographs the burglar in day-



Photo taken by Photolarm in total darkness.



The 3 purpose instrument with unlimited application in your inspection department

Use as Dial Indicator graduated to read in .0001".

Use as Bore Gage covering a range of .200" thru 5.090" and reading in .0001".

Use as Dial Test Indicator graduated in .0005".

The No. 99 incorporates a high quality dial indicator together with all the necessary gage heads and extensions. It may be used directly at your machines or clamped to your fixtures. Furnished in handsome plush-lined case.

Dial Test Indicator Set No. 98, a modification of the No. 99, is especially designed for applications where measurements must be taken in deep holes. slots, etc. Write for detailed brochure.



WRITE FOR ILLUSTRATED LITERATURE.

CORPORATION

122 East Second Street, Mineola, Long Island, New York

Alina Corporation, 853 East 8 Mile Road, Detroit 20, Michigan Use postpaid card. Circle No. 364

light or in total darkness with invisible light, and simultaneously rings a loud bell alarm. The unit is compact and camouflaged so thieves are unaware of its presence.

The device is easily installed by plugging into a conventional AC electric outlet.

Photolarm, Inc., 600 Michigan Bldg., Detroit 26, Mich.

Use postpaid eard, Circle No. 101

Machining of Small Parts With Vertical Borer


The sturdily constructed BV machine is reported capable of heavy cuts on castings and forgings as well as precision cuts of less than .0005 tolerance on finishing operations. Fourteen machines in the new BV series apply the building block principle to cam actuated precision boring.

A feature of the head and base assembly is clean sides which allow a



WITH DAVIS KEYSEATERS!

You can cut accurate, low-cost internal keyways at minimum cost with Davis Keyseaters. Here's why: (1) operation is designed for production speed; (2) machine sets up easily, does not require skilled operator; (3) maximum concentricity of the keyway in each bore assured; (4) Built in 2 sizes. Keyways range from ½" to 1". High speed steel cutters stocked in all sizes; (5) the best keyseater of its type, yet inexpensive! Write now for FREE DETAILED LITERATURE!



Tilting table sets easily for tapered keyways up to 3" per foot.

DAVIS KEYSEATER COMPANY DIVISION OF Hanaford MANUFACTURING CORPORATION 1239C UNIVERSITY AVE., ROCHESTER 7, NEW YORK



A two unit assembly on the vertical boring machine. number of independent units to be placed side by side and to be serviced by one operator.

Hoern & Dilts Division, The New Britain Machine Co., Saginaw, Mich.
Use postpaid card, Circle No. 102

Rubberized Abrasive Kit for Tool and Die Makers

To introduce rubberized abrasives to tool and die makers, the Cratex Mfg. Co., 1600 Rollins Rd., Burlingame, Calif., has developed tool and die makers kit No. 777. "Although the use of rubberized abrasives is steadily increasing," says Cratex, "their advantages in solving sensitive deburring, smoothing and polishing problems are not widely known "

The kit contains the 80 wheels and points thought to be most useful to tool, die and mold makers and component parts manufacturers. They are packaged in a plastic box, compartmented for fast selection.

The wheels and points are equally assorted in four grit textures (coarse-C. medium-M, fine-F, extra fine-XF) and four mandrels for 1/8" chuck.

Use postpaid card, Circle No. 103

Continental Pipe & Tube Cut-Off Wheels

HI-ALLOY for LOW COST CUTS

More cuts between sharpenings-made of Shok-Resisto steel. For Continental and other rotary cut-off machines. Send for CUT-OFF WHEEL CHART . . . shows correct cutting bevels.

MACHINE RENTAL PLAN





SINCE 1919 machine co.

CHICAGO 18, ILL

WRITE FOR CATALOG



HEAVY RECTANGULAR TUBES—accurately formed on Pines Model 4 on a 24" inside radius. for air cushian assembly on heavy duty truck chassis. Material is 4" a



-cold edge bending of 5%" s 11/4" steel bars on Pines Model 4 replaces hat bending on dozer produces more accurate parts at lower cost



ALUMINUM CHANNELS—rugged machine const and tooling on Pines Model 3 Machine cold forms 4' 134" s .320" aluminum channel without wrinkling or disng. Spring-back is controlled by simple machine settings.

FOR COST CUTTING IDEAS

INVESTIGATE PRODUCTION BENDING THE "PINES-WAY"

When you have a production job requiring the cold forming of parts from round, square, rectangular, extruded, or hollow stock to an even radius, or to different angles, we suggest you investigate the cost cutting advantages of production bending the Pines-way. The examples shown here illustrate a few of the many different and varied applications which are today profitably produced on Pines machines. Cold bending is a fast, accurate, easy to control metal forming process that is today more profitably applied in the production of an ever increasing variety of products. Call on Pines engineers for assistance without obligation on any specific job.





COPPER SERPENTINE BENDS-14" O.D. x .035 cooper tubing is rapidly formed on this Model 1/4 into tine coils on a 1" clr. A simple gang-slitting operaon produces 180° return bends.



WRINKLE-FREE SQUARE TUBE BENDING - Model 1 Machine, equipped with flexible mondrel and selfopening bending form, produces top quality office and hospital equipment at speeds of 250 bends per how.



FAST ROUND-TUBE BENDING Pines Model Atachines speed production of tubular dinette and lawn functure. Fast, automatic cycling and accurate progressive banding produce 600 to 900 bends per how

↓PINES Engineering co., inc.

ists in Tube Febricating Machinery 692 WALNUT - AURORA, ILLINOIS PRODUCTION BENDING

ing, write for free copies of "Pines News" - gives complete data on new production applications.



CHAMFERING MACHINERY Use postpaid card. Circle No. 367



AIR GRINDERS

MODEL JA
30,000 R.P.M.
\$6000
NU.S.A.

Weight 12 ounces; length 6% inches; chuck size ½ inch.
Wheel guard removed for better illustration.

THE SPEED of Kipp Featherweight Air Grinders stays up where it belongs, under load, for efficient grinding even with small wheels. This may not be true with most of the "Plug-In" grinders you now are using.

HAVE YOU GIVEN your toolmakers a chance to save valuable hours by providing them with enough Kipp Featherweight Air Grinders and accessories?



MADISON-KIPP CORP

207 Waubesa St., Madison 10, Wis., U.S.A.
Use postpaid card. Circle No. 368

Decorating-Mask Washer

The functions of automatic spray decorating equipment combined with automatic, efficient mask washing are possible with this washing machine, useful for those who do spray finishing



Paints areas up to 6" x 6" square or diameter.

which employs masks with fine detail. It is of value also where a heavy material is used for decorating and only a few shots can be obtained on a mask before washing becomes necessary.

A clean, dry mask is made available in less than a second by the machine operation, and the operator need at no time handle the masks.

Areas up to 6" x 6" square or diameter can be painted.

Conforming Matrix Corp., 394 Toledo Factories Bldg., Toledo, Ohio.

Use postpaid card, Circle No. 104



Write for FREE Catalog

- Ground Cut Rotary Files For Soft Metals.
- HAND CHISEL Cut For Hard Metals.
- Carbide Rotary Files
- Salvage and Regrinding Service
 Dealers Inquiries Invited

Rota FILE CORP.

1328 S8TH STREET
BROOKLYN 19, N.Y.

Use postpaid card. Circle No. 369

MACHINE and TOOL BLUE BOOK

This is a knock-out cavity bushing.



It is used in plastic injection molding.

It is manufactured by FASTEX,

Division of Illinois Tool Works, Des Plaines, Illinois.

It has a ______ internal taper.

It is ground from hardened tool steel, 58-60 Rockwell C

The tolerances must be held to 0.0002"



The grinder on which this bushing and all its cousins are made is a



RIVETT LATHE & GRINDER, Inc.

Dept. MTR 4 Brighton 35, Boston, Mass.

Use postpaid card. Circle No. 370



An internal specialist with external ability. Mounts interchangeable wheelheads for internal and external spindles. Capacities are 3" diameters, depth 4". Collets and step chucks mount directly in lathe-type spindle.

Good Work Requires A Good Bench.



\$61.92 30" × 5 H.

LAMINATED MAPLE TOP

Solid, quiet, non-skid and nonconductive.

ELECTRIC SOCKET

Can be mounted on leg for convenient use of power tools.

Write Today for Our Catalog and the Name of Your Local BAY Distributor

BAY PRODUCTS INC.

1827 CAMBRIA ST., PHILA. 32, PA.

Use postpoid card. Circle No. 371

Automatic Cutter Grinder

Labor savings in the grinding room and increased production in the machine shop are twin objectives of this automatic cutter grinder. It will do a complete sharpening job on a wide range of milling cutters, since it grinds on the OD as well as the face and bevel of any cutter within its 4-inch to 20-inch diameter capacity.

The machine spin-grinds newly filled cutters to size. A dust collection system is built into the machine and there is positive dirt protection for moving parts. As the grinding wheel wears, the spindle speed automatically increases so that constant surface speed is maintained. The wheel is automatically dressed with every stroke.

The machine was developed specifically for grinding a variety of inserted blade carbide cutters used in general purpose job shop milling. Setups are easily and rapidly changed from one size and type of cutter to another.




Mechanical control of grinding action lengthens cutter life, improves accuracy and finishes, and enables a man to operate more than one machine.

Ingersoll Milling Machine Co., Rockford, Ill.



Low cost precision boring

Patented oil displacement feed principle assures high quality finish. Compact design. Ideal for mounting in any position on work-holding fixtures, assembly jigs, etc. Simplifies production setups. Three models to meet all your requirements. Write today for further information.





GREENLEE BROS. & CO.

1794 MASON AVENUE Rockford, Illinois



Use postpaid card. Circle No. 373

Hand Press Features Controlled, Positive Action

A new hand press, HP Jr., features controlled, positive action and is designed for fast, versatile operation in riveting, assembling, forming, stamping, crimping, piercing, and all light press jobs.



Fast, versatile operation in light press jobs.

Stroke is ¾"; vertical opening, adjustable 1" to 2½"; horizontal gap, 1½"; spindle hole for punch, ¾" dia.; die space, 3¾" x 6"; handle leverage, 7"; bench space including handle, 10¼" x 10"; over-all height, 13½"; net weight, 50 lb.

High Speed Hammer Co., Inc., Rochester 21, N.Y.

Use postpaid card. Circle No. 106




3 lbs. 4,10 Spreads like paste — Hardens ta metal Metal - Wood - Plaster - Glass - Plastic EASY! FAST! NO MIXING!

Available at your distributor or write
ALVIN PRODUCTS, Inc. Worcester 4, Moss.

Use postpaid card. Circle No. 374

MACHINE and TOOL BLUE BOOK



BARNESDRIL units readily re-group or modify for new production needs

Here's how existing machines may be changed to handle new production problems.

- Modify auxiliary heads on existing machines.
- Use existing center section, modify or add new units.
- Adapt new center section, modify and/or add new units.
- Use idle equipment and group around existing or new center section.
- Use existing units, move from facility to facility, and adapt to required production.

Diagram shows BarnesdriL transfer machine as modified, original machine in white, with changes and additions in gray.



Barnesdril engineers have been building production unit-type machines since 1937. Many of these original machines have been re-grouped or modified several times, effecting tax savings and reducing capital investment requirements. If you have product changes at the present time, or want to change-over to new operations, ask Barnesdril, engineers to show you how existing machines can be effectively utilized, with savings up to 20% over new machinery costs.

New Bulletin

Contains Complete Story On Barnesdril Units. Write For Free Copy.





BARNES DRILL CO.

852 CHESTHUT STREET . ROCKFORD, ILLINOIS BETROIT OFFICE: 13121 Puritan Avenue

OBI Presses Improved

Improved design and operating features are offered in Series 1 OBI presses, available in 35, 45, and 60 ton capacities.

Recirculating lubrication system can be furnished as an optional extra. The system continuously lubricates main and connection bearings, gibs, gears and counterbalances. Enclosed within the press frame and protected from damage, it lowers maintenance and cleanup costs and prolongs press life.

A modified flanged slide gives larger die area as a standard. Lower connection ball box adjustment consisting of a threaded take-up nut, adjusted with a spanner wrench, quickly takes up a ball box clearance without the timeconsuming task of dismantling the slide.

Presses are equipped with a combination air friction clutch and brake unit which is claimed to provide torque overload control, greater tripping ef-



The 35-ton model. Others 45- and 60-ton capacity. ficiency, and controlled cycling and inching. A centralized press control package is mounted in a cored recess area at the top rear of the press frame.

The Minster Machine Co., Minster,

Use postpaid card, Circle No. 109

choose from 3 KELLER MODELS

Heavy ribbed table tilts 12° four ways. New fast acting chuck makes file changing easy. Generous Oilite bearings, balanced scotch yoke cuts vibration to minimum, two speeds with $1\frac{1}{2}$ " stroke and other features make these KELLER DIE FILLERS outsanding machines at low cost.

ECONOMY MODEL \$109.50

Without overarm. With motor

STANDARD MODEL F256A same as Economy plus the roller support arm. \$131.50.

DELUXE MODEL F256B same as Standard plus reciprocating vertical slide. \$149.50.

Low Cost DRILL PRESS VISE \$11.50

Jaws $4\frac{1}{6}$ " wide, 2" deep, opens to $4\frac{1}{4}$ ". Can be quickly set to any angle. Weight $16\frac{1}{2}$ lbs. An outstanding value at this 1956 price.

KELLER DIVISION

Sales Service Mfg. Co.

2361 University Ave.

St. Paul 14B, Minnesota





The Anderson Hydraulic Hand Press was developed to reduce costs. Checking and straightening are accomplished in one position . . . eliminating the time consumed shifting parts back and forth from checking fixtures to straightening anvils. Efficient hand hydraulic pumps power various models of presses ranging in capacity from 10 to 50 tons. Attachments make possible the checking of stepped or odd shaped parts with centers. Different lengths of work can be handled by easy adjustment of rolls and centers. A pressure gauge is standard equipment. A special attachment is an indicator calibrated to thousands of an inch for locating high and low spots on the work, and to indicate how much the shaft is bent under pressure. An Anderson Hydraulic Hand Press can help you solve your straightening problems.



Write for Bulletin No. 4-5

ANDERSON BROS. MFG. CO.
ROCKFORD, ILLINOIS

TOOL MAKER'S

TOOL-

EM 5/8" DRILL PRESS



features

INSTANT SPEED CONTROL

BUILT-IN GEAR DRIVE

FOR EXTRA LOW SPEEDS

PRECISION SPINDLE

Designed and engineered for

FLOOR MODEL



tool room and precision use. Accurate mounting of head and column insures squareness of spindle to table. Heavy construction. Convenient direct reading variable spindle speed control.

Write for Literature and Prices.

BENCH MODEL

THE ELECTRO-MECHANO CO.
263 E. ERIE STREET MILWAUKEE 2. WIS.

Use postpaid card. Circle No. 378

Coils of Varied Diameters Made for Tubing & Strips

Model C-1 coiler is designed for making coils of various diameters and pitch for tubing, bar and strip. The radius



A coil in 5/16 stainless tubing being made; smaller diameter coils beside it.

of the coil or circle can be varied by turning the crank at the left of the machine.

The push-button station on front of the machine permits running a straight length followed by a radius as is used in a U-bend, while the reversing switch allows forming either right or left hand coils.

Curvit Corp., Plainville, Mass.
Use postpaid card. Circle No. 108



Use postpaid card. Circle No. 379

MACHINE and TOOL BLUE BOOK

For the Precision of a Count-down

LAUNCHES A NEW CUTTING TOOL LINE FOR MILLING ACCURACY

For precision milling to close tolerances, so vital in today's high-speed, high-production manufacturing, T-J now offers a new, improved line of milling cutters. The new cutter line features a high helix angle, double back-off, and a right-hand spiral to produce more and smoother cuts between grinds, and a free-cutting, stronger tool.

Specially designed and precision-manufactured for die sinking and production milling, the new line is designed to include flats on the shanks for set screw type drivers on all of the end and side milling cutters. Write today for complete information to the Tomkins-Johnson Company, Jackson, Mich.

Ask for completely new cutter catalogue No. 259.



Spillproof Dispenser

Merely squeezing the plastic container produces either a squirt or a stream of oil (or other liquid). Available in 4 or 8 oz. sizes with straight or angle nozzles, each dispenser has a screw-on cap. Once sealed, the dispenser can be carried anywhere without worry of leakage. The user has visual control of the contents of this breakproof container.

Hunter Tools, P.O. Box 564, Whittier,

Use postpaid card. Circle No. 107



A squeeze gives a squirt or a stream.

MOST Value-Packed GRINDER MADE!





CARBIDE TOOL GRINDER



Model 153-6". Reversible $\frac{1}{2}$ HP motor, 3450 RPM. $1\frac{1}{2}$ " wide wheels. Every part oversize for rugged, longlasting use. Just \$189.00.

BALDOR

MODEL 153-8"

Feature for feature, no other grinder offers so much for so little. Compare HP rating, wheel size, shaft diameter, bearing size with any other similar-type grinder. You'll quickly see why you get more with Baldor!

- Big ½ HP motor; won't burnout even if repeatedly overloaded!
- Wide-clearance design provides maximum working room!
- Large 8" first grade wheels!
- Heavier ¾" arbor; larger ball-bearings!
- Dynamically-balanced rotor extra smooth operation!
- Exhaust-type guards!

Write today for Bulletin 321N on complete line of Baldor Grinders and Buffers!

BALDOR ELECTRIC CO.

4353 DUNCAN AVE. ST. LOUIS 10, MO.

Feedback Mechanism Gives Operator Complete Control

The H-P-M servo controlled C-press provides absolute control of all press actions without unnecessary and spacetaking linkages, the manufacturer



Bed and throat area is completely unobstructed. claims. Slow hand motion results in slow ram movement; fast action produces rapid ram movement.

This press is reported to be suited to straightening operations as the operator has complete control of ram speed, of travel, distance and tonnage imposed on work. This close control over the ram motion is desirable for applications of a research nature where the force of the ram must be accurately evaluated or controlled.

The Hydraulic Press Mfg. Co., A Div. of Koehring Co., Mount Gilead, Ohio.

Use postpaid card. Circle No 110



TAP BUSHINGS

Drives all standard taps from No. 0 to 1%" and pipe taps from %" to 1". Five o.d. sizes.

LESS TAP BREAKAGE LESS TAP WEAR

Write for Bulletin

BYCO INDUSTRIES

2201 Snelling Ave.,

Minneapolis, Minn.

Use postpaid card. Circle No. 382

"A.N.D." and "M.S." HYDRAULIC CONTOUR CUTTERS in stock

A.N.D. 10050 internal



Economy series; integral plain pilot



Turret lathe and drill press series; integral carbide reamer pilot



Heavy duty series; replaceable carbide reamer or plain pilot, carbide and HSS

MS33656, MS33657, MS33514, and MS33515 O.D. flat form tools

Carbide tipped High speed steel

MS33514 internal



Solid carbide, carbide tipped, high speed steel models

MS16142 internal



Carbide tipped; plain or reamer pilot

Write for sizes and prices. | or reamer

SONNET Tool and Mfg. Co. 580 North Prairie Avenue, Hawthorne, California


Jig Grinder Has Large Table 11"x24"x18"

Finer tolerances in the finish-grinding of tools for the missile era are claimed for the No. 3 Moore jig grinder, which offers a greater range and larger table than its No. 2 predecessor-11" x 24" x 18" height. It will grind, with split-tenth accuracy, straight or tapered holes and regular or irregular contours to size and location after hardening, the manufacturer reports, also providing this same efficiency for slot-grinding and chop-grinding operations. Spindle speeds are 40 to 250 rpm.

Accuracy of positioning reported for longitudinal travel: the greatest error in any inch, 30 millionths; in 18", 90 millionths. For the cross travel, the greatest error in any inch. 30 millionths: in 11", 90 millionths.

Moore Special Tool Co., Inc., 800 Union Ave., Bridgeport 7, Conn.

Use postpaid card. Circle No. 111



Spindle speeds are 40 to 250 rpm.



CONCENTRIC TOOL CORP., 2486 Huntington Dr., San Marino, Calif.

Two Honing Machine Series Feature Automatic Control


Two additional series of vertical honing machines are of the twin cylinder crosshead type, decreasing the over-all height of the machines. The Model 12 Series is available with up to 60" strokes and up to 25 hp, while the Model 18 Series offers up to 120" strokes and up to 35 hp.

Both series include the Fulmer Fulfeed system for control of honing tools, which has completely automatic and manual remote control of tool expansion and retraction. Featured are automatic fast feed-out, timed spark-out cycle and retraction of the tool.

Control for automatic operation is by cycle timer, or automatic sizer.

The C. Allen Fulmer Co., 105 E. 4th St., Cincinnati, Ohio.

Use postpaid card, Circle No. 112



Remote control of tools-automatic or manual.

POWER ... when you need power! 1½-75 TONS GREENERD, for 76 years, has manufactured Power-Performing ARBOR and HYDRAULIC PRESSES: maintenance-free; may be furnished to J.I.C. Standards, and designed to handle the following variety of work: * ASSEMBLING FORMING * BENDING MOLDING * BROACHING RIVETING

- SIZING

- STAKING

Received ARBOR PRESS C

" STRAIGHTENING

41 CROWN ST. NASHUA , N.H.

Use postpaid card. Circle No. 385

· BURNISHING

· EMBOSSING

· CRIMPING

Rotary Table with Unique Measuring System

To provide a stationary platform divorced from Mother Earth's rotation for the calibrating and testing of navigational gyroscopes, such as those used in missile and rocket development, a special tilting rotary table with Electrolimit measuring system has been developed. In effect, this rotary table places the instrument under test, while sitting on earth, in the same environment that would exist if the instrument were resting on a stationary platform out in space.

The bedrock of earth rotates one revolution in 23 hours, 56 minutes, four and nine one-hundredths seconds-the sidereal day. To counteract the earth's rotation, the rotary table is designed to rotate at an angle correlated to a selected star's path and at a rate of speed based on intervals in the sidereal dayin the opposite direction.

Since it is necessary to establish very



Rotary table with Electrolimit measuring system.

accurately the five degree intervals in the sidereal day, and pass this information on to computing equipment that



200-MT LAFAYETTE STREET . NEW YORK 12, N. Y.

calibrates the gyroscopes, the table is equipped with the high-precision Electrolimit measuring system. A special rim mounted on the 24" standard table face plate is equipped with Electrolimit lugs spaced five degrees apart. As the table rotates, an Electrolimit sensing head picks up the magnetic center of each lug and passes an output signal to the computing equipment, which in

turn sets up the machinery for calibrating the gyroscope.

The plus and minus tolerances for various degree points from 15° to 25,000° per sidereal hour are held to a small fraction of 1%. The tilt of the table is manually set and is not changed during the rotation cycle.

Pratt & Whitney Co., Inc., Charter Oak Blvd., W. Hartford 1, Conn.

Use pestpaid card. Circle No. 113

NEW, LIGHTWEIGHT, POWERFUL

FLEXIBLE TOOL SHAFT

Connects To Any Motor



Stow flexible tool shafts increase precision, eliminate operator fatigue on production grinding, polishing, sanding and other finishing operations in which the operator must hold the tool for long periods of time. Up to 3 HP can be transmitted through these new tool shafts, which consist of a core made of highest grade music wire rotating inside a rubber-covered casing. Each shaft furnished with ball bearing motor connection and high-speed ball bearing handpiece with removable wheel Arbor having $\frac{1}{2} \cdot 20^{\prime\prime}$ threads. An angle head can be used in place of the handpiece as shown in the photograph.

Four Sizes of these shafts are available . . . models 38, 40, 50 and 63, which come in 6-foot standard lengths. The largest shaft, model 63, will handle 3 HP at speeds up to 6900 RPM and has a maximum capacity for various accessories as follows: grinding wheel, 8" x 1"; buffing wheel, 8" x 1"; sanding disc, 9" diameter; sanding drum, 6" x $2\frac{1}{2}$ "; wire brush, 8" x 2"; steel drills, $\frac{1}{2}$ " diameter.

Write for Catalog 57

STOW MANUFACTURING CO.

30 Shear St.

Binghamton, New York

Heavy Duty Reinforced Wheels

Heavy duty wheels, developed for use on band saws and band resaws, feature rims reinforced with a double thickness of quality steel claimed to make them five times stronger. They are reported as ideal for use on resawing operations or on very thick work, on shakes, or any work requiring extreme blade tension. The wheels offer new dynamic balancing for absolute vibrationless operation, at any high speeds, the manufacturer reports.

Carter Products Co., 50 Market St. N.W., Grand Rapids, Mich.

Use postpaid card. Circle No. 114

Bearing Aluminum Bars

New bearing aluminum bars can be machined to fit any bearing use. They are formed of Alcoa B-750-T5, an aluminum-tin alloy with certain other



Precision-built of the finest tool steels, New Method's custom-made roll dies can be used on any secondary marking machine or special device.

No matter what your particular requirements ... graduated roll dies for marking on ANY SURFACE SHAPE, convex dies for concave surfaces, concave for convex surfaces, trade mark, segment insert, embossing, etc. ... New Method can engineer and

manufacture them to fit your particular needs.

Other New Method Marking Devices . . .

- ★ A complete line of automatic roll markers for most marking requirements, each designed for a specific need.
- \bigstar A complete line of manually operated marking devices.



Write today for NEW catalog MA-59

NEW METHOD STEEL STAMPS, INC.

Use postpaid card. Circle No. 388

MACHINE and TOOL BLUE BOOK

metals (copper, nickel, magnesium) added.

Good heat conductivity, excellent embedability, good ductility, high load carrying capacity, high resistance to corrosion, conformability to the shaft, and good fatigue strength are qualities which make this bar a satisfactory sleeve bearing material.

Bunting Brass and Bronze Co., Toledo, Obio.

Use postpaid card. Circle No. i15

New Sizes of T-Slot Nuts

Additional sizes of T-slot nuts have been added to the Northwestern tool line. They are now available for all machine tools with table slots ranging from 3/8" wide up to and including 1-1/16" wide in multiples of 1/16".

The nuts are machined from bar stock for safe and solid clamping. They are heat treated for long life and black penetrated to prevent rust. Selection chart shows the correct size T-slot nuts



Save Space, Weight & Piping



NO SEPARATE VALVES TO MOUNT OR PIPE . . . Modernair's VIH cylinders have directional and exhaust speed control valves built in!

FEATURES:

- *COMPACT CYLINDER-VALVE "PACKAGE" includes builtin directional control, exhaust speed control valves.
- *SOLENOID, BUTTON BLEEDER or PILOT PRESSURE valve operation.
- *INTERCHANGEABLE MOUNTINGS.

BRIEF SPECIFICATIONS: .

DIAMETERS: 1½", 2", 3"

ROD SIZES: ½", 5%", 3¼"

MIN. OPERATING PRESSURE: 20 p.s.i.

ANAL OPERATING PRESSURE: 150 p.s.i. (colengid)

MAX. OPERATING PRESSURE: 150 p.s.i. (solenoid) 200 p.s.i. (bleeder or pilot pres.)

Write for catalog, prices today—or phone your local MODERNAIR distributor (listed on your phone book Yellow Pages).

Modernair corporation

Dept. N-4, 400 PREDA STREET, SAN LEANDRO, CALIF.



For table slots from 34" to 1-1/16" wide.

for all machine tools and metalworking equipment.

Northwestern Tools, Inc., 118 Hollier Ave., Dayton 3, Ohio.

Use postpaid card, Circle No. 116

Attachments for Pipe, Bar, Angle Iron Bender

Two attachments for the Hossfeld universal pipe, bar and angle iron bender are available. Handrail capping can be bent into lamb's tongues, edgebends with the No. 2 bender and dies. Single



To indicate face runout, stand the Instrument Bench Centers vertically on precision ground headstock pads.

New! Instrument Bench Centers Speed Inspection of Miniature Parts



No. 9205M Instrument Bench Centers checking miniature crankshaft for concentricity after O.D.grinding operation.



Complete Line of Bench Centers

The Taft-Peirce Standard Bench Center Line includes models with work capacities from 8" dia. x 18" to 10" dia. x 60". Special sizes designed and built to order. These new Taft-Peirce No. 9205M Instrument Bench Centers are specifically designed for speed, accuracy, and versatility in checking miniature and sub-miniature parts.

When placed horizontally on a surface plate of known flatness, the centers line up automatically within close limits, and a quick turn of a knurled knob locks them in position. The entire unit may then be turned up on end to check runout and squareness of shoulders and sides of grooves.

An exclusive feature is an adjustable headstock center point that may be rotated to bring the work centers perfectly parallel to the surface plate. This allows the inspector to obtain a precise reading of concentricity and parallelism in a horizontal plane, and shoulder runout in a vertical plane.

Maximum capacity—8" long x 3" diameter. Send for new catalog No. 511 showing all Taft-Peirce precision tools.

TAKE IT TO

TAFT-PEIRCE



WOONSOCKET, RHODE ISLAND




Combination lamb's tongue and edge-bend being formed on No. 2 iron bender.


and double turn scrolls can be formed in seconds. The handrail capping and scroll dies make bender more versatile. For hard-to-pull bends on heavier material a hydraulic attachment is available. Hossfeld Mfg. Co., Winona, Minn.

Use postpaid card, Circle No. 117

Standard Subland Drills

Mohawk Tools, Inc., Montpelier, Ohio, has announced the immediate availability of Subland drills in all practical standard sizes for drilling and chamfer-





Three step lengths and three shank styles.

ing operation prior to tapping: tap sizes from 10-24 to 5-18 NC and NF, in three step lengths and three shank styles.

Drill sizes were selected for industrywide acceptance of unified standards and hole tolerances and to provide a faster, more accurate method of simultaneously drilling and chamfering clean, concentric holes for better tapping plus a saving in tap costs.

Use postpaid card, Circle No. 118

SAVE 50%

or more in

CONTOUR GRINDING

COSTS with
Micromaster

Sold by
Brown &
Sharpe
Mfg. Co.
Providence,
Rhode Island

Visual Grind is manufactured by

The CLEVELAND GRINDING MACHINE Co.

1670 EDDY ROAD . CLEVELAND 12, OHIO

Throwaway Insert Cutter Blocks

The advantages of throwaway carbide tooling now have been applied to block-type boring tools: (1) elimination of carbide grinding, (2) instant tip indexing, (3) lower cost per cutting edge, (4) lower tool inventory. Blocks are available in two-cutter and single-cutter styles; cover a bore range of 2½"-17"; can rough-bore to .004".

Davis Boring Tool Division, Giddings & Lewis Machine Tool Co., Fond du Lac, Wis.

Use postpaid card. Circle No. 119



Bores 21/2"-17"; rough-bores to .004".



In the GOLD BAND line Ideal has combined the latest production methods with their traditionally fine craftsmanship to bring you an unequalled standard of excellence in live centers. Accurate, (to ± .0001") GOLD BAND Live Centers offer "custom" quality at production prices. Specify GOLD BAND Live Centers and your every need can be accommodated from stock . . . 99 times out of 100.

Ideal's GOLD BAND Live Centers offer savings, simplified operations and higher lathe output both in quantity and quality. Contact your distributor today!



A COMPLETE LINE FOR EVERY NEED-SPECIALS TOO!



Write for Complete catalog data and specifications.





IDEAL INDUSTRIES, Inc.

1441-D Park Ave. Sycamore, Illinois

Taps 1/2" to 2" Forged on Tap Forging Machine

A precision tap forging machine, manufactured by an Austrian concern, is made available to the American market by Girard Associates. By this method for precision forging of taps, one operator can forge taps from precut bar stock, two at a time, in 15 to 20 seconds per pair for taps ½" to 2", the manufacturer claims. Flutes are reported to be forged with a tolerance





Koil Kradles form a slack loop between coil and machine from which any automatic feed can freely draw! The slack loop eliminates drag and resistance of pulling against heavy coils. Reduced drag improves accuracy of any feed device... records show up to 80% more footage handled per shift!

Koil Kradle's variable timer delays shut-off up to 10 seconds after motor switch trips off...forms a new slack loop before stopping, eliminates many unnecessary motor starts and stops! Adjustable plates center various coil widths; reversible motor for rewinding; power driven rolls; anti-friction bearings and numerous other features!

ASK FOR CIRCULARS, sizes and prices. Stock widths up to 50", coil weights to 20,000 lbs.



World's largest manufacturer of small punch presses and mills.

1835 W. Rosecrans Avenue · Gardena, California

of ± 0.004 " on all dimensions.

Savings are said to range from 200 to 300 lb. per hour for 1" taps, and from 450 to 675 lb. per hour for 1½" taps.

Girard Associates, Chambersburg, Pa.
Use postpaid card. Circle No. 120

Inspection Instrument For Surface Plates

Tol-Check is a new instrument for checking the tolerance accuracy of any



Accurate evaluations in 30 seconds without graphs

How to Install Machines



with Red Line UNISORB

Whether installing one machine or a whole plant, users report that Unisorb Pads make the job go "slick as a whistle." Here's why:

- Pads are cut to size, buttered with Unisorb Cement, spotted under legs and machine set immediately in place.
- Unisorb Cement has tremendous bonding power, will keep a machine safely in place even under severe side thrusts.
- No hole drilling, bolt alignment or pock-marked floors.

RESULTS ...

- Installation costs and time are drastically reduced.
- Absorbs up to 85% of transmitted vibration. Cuts noise, reduces maintenance and improves working conditions.
- Machines can be quickly and easily moved at any time.
 Ask about Unisorb Mounting Pads with engineered density and thickness for every type machine. Send for special trial offer, NOW.

UNISORB

Division of The FELTERS Company

Use postpaid card. Circle No. 395

203 South St. Boston 11 Mass. type or make of surface plate. Its function is to determine whether a surface plate is within the prescribed limitations of accuracy. It does this by visually indicating on a dial any over-all tolerance deviations. Accurate evaluations can be made in 30 seconds, eliminating the need for complicated graphs and paper work.

The instrument is supplied with a master surface plate for standard of calibration, durable instrument case and a protective surface plate cover. The unit can also be supplied mounted on a rolling stand for routine plant inspection programs.

Herman Stone Co., 1860 N. Gettysburg Ave., Dayton 27, Ohio.

Use postpaid card, Circle No. 121

Locating Pins in 368 Sizes

A new line of locating pins available in two styles is said to feature the largest range of sizes in the industry. They are made in diamond and round



GAGE SURFACE FINISH TO NEW A.S.A. STANDARDS - Quickly - Accurately


This convenient pocket comparator has 22 precision surfaces for specifying and controlling finish to the new A.S.A. Standard B46.1 - 1955. Electroformed in durable corrosion-resistant nickel, the S-22 Comparator provides every department with the most inexpensive method for uniform, accurate control of finish characteristics.

Save valuable time in engineering, inspection, quality control — eliminate costly overfinishing in purchasing and production. \$17.50 complete with leather case.

Available from leading industrial distributors, or write



FAIRFIELD DEVELOPMENT LAB., INC. (SUCCESSOR TO BAPTIST MACHINE CO.) 38 Ludlow Street, Stamford, Conn.



Locating pins are made in diamond, round styles.


styles for locating and are designed with a resting shoulder to act as rest pads. The pins are available in 368 sizes, ranging from 1/8" to 11/2" head diameters. They are used in bushing applications: also press fitted with lock screw holder.

Concentricity is held within .0002 throughout Both styles are carburized. hardened to Rockwell 60-62 for tough wearing surface with core left mild.

Jergens Tool Specialty Co., 712 East 163rd St., Cleveland 10, Ohio.
Use postpaid card. Circle No. 122

DUSTKOP

designed to collect dust from





portable easily installed

DUSTKO STOPS DUS

Self-contained Dustkop models, like the "520," are practical and effective in collecting dust from single machines. They're designed specifically for service with surface grinders tool and cutter grinders, offhand

grinders, boffers and other small wheel equipment. These units are also easy to install - are actually portable - and very economical to operate.

Write for illustrated literature

46 models to shoose from!

NEW DUSTKOP AUTO SHAKER shakes filters AUTOMATICALLY

AGET manufacturing company 1402 E. Church Street, Adrian, Michigan

Use postpaid card. Circle No. 397

ask for details



Compact, economical, trouble-free Abart power packages fill any speed reduction need. Any desired shaft arrangement-worm, spur or combination models - fractional to over 400 hp. ratings single or double reduction - ratios to 10,000 to 1.

Send now for Abart pocket-size engineering data book and catalog.

ROO WEST 14th STREET CHICAGO SO. ILLINOIS Use postpaid card. Circle No. 398



Use postpaid card. Circle No. 399

Screws in Pitches 4-10. 3/4" up to 11/2" Dias.

Wedin stock lead screws, with precision ground threads, cover pitches from four to ten in 34" up to 11/2" diameter. Length varies in 6" increments from 18" to 72". Each end of the screws has sufficient stock length for final turning of plain diameters, etc., to meet most conditions.

In addition to the stock screws, matching nuts are available both in the pillow type and cylindrical design. These lead screw assemblies can be selected in the design of new equipment as well as for replacements of screws in used machinery maintenance.

Because of quantity production of these stock screws, there is cost saving. and down time on machines with defective screws can be cut to a minimum.

Wedin Corp., 403 N. Lake St., Cadillac. Mich.



HUPPERT

Floor Model Furnaces **Built in 28 Standard Sizes**

- . Continuous operation to 1850 F.-intermittent to 1950°F.-for 2300°F. on special order.
- . Complete with indicating electronic controller.
- · Tight-sealing, wedge-type door.
- . Standard for 220 V. AC, single or 3 phase operation-110 V. or 440 V. on special order.
- · Multi-insulation for maximum efficiency.

Request literature on complete line of Huppert Furnaces

Model No. 16 Illustrated

K. H. HUPPERT CO. Manufacturers of Electric Furnaces and Ovens

6845 Cottage Grove Ave., Chicago 37, Illinois



Inside Dimensions 12" W. x 8" H. x 18" D. \$1050.00 complete

* Master MICROMETER *"GO" &

"NO GO" GAGE - 1" Range in .0001"

GUARANTEED Mahp QUALITY

INDICATING BENCH

MICROMETER with

HON-ROTATING

Use postpaid card. Circle No. 403

METER and COMPARATOR

TENTHS VERNIER

With the VISIBLE FEEL WILL DETECT OUT-OF-ROUNDNESS

OVALNESS - TAPERED CONDITION IN 1/10,000 LARGER SIZES UP TO 12" AVAILABLE 3 TOOLS IN ONE * COMPARATOR

IN HARDWOOD A RIGHT HAND TOOL

Release Button for Movable anvil on right hand side enables operator to hold tool the conventional way,

NEW ! lesetting to Zero in Seconds. Quick Adjustable Tolerance Hands.

HEAVY TUNGSTEN CARBIDE tipped Measuring Anvils. STAINLESS STEEL, one-piece spindle and screw, hardened with Ground Threads - Permanently Rustproof.

Reading .000050" from dial. Directly reading in .0001" from micrometer, 1-3/4" thimble dia. Dull chrome finished.

USE IT AS A COMPARATOR

Anvils RETRACTABLE for rapid repeat measurements. Adjustable Tolerance Hands. Instant Zero adjustment of Indicator. FEATURING . . . Adjustable Measuring Pressure to any desired tension. Non-rotating Spindle assuring absolute parallelism of anvits. Eleven Types of INTERCHANGEABLE Measuring Anvils available.

20 MILLIONTHS INDICATOR READING AVAILABLE

Spindle Range 0-1" for Tool and Instrument making

IF NOT AVAILABLE AT YOUR FAVORITE SUPPLY HOUSE - WRITE TO US FOR ILLUSTRATED FOLDER.

274-MA LAFAYETTE ST. . NEW YORK 12. N.Y.

MEARQUARTERS FOR PRECISION MEASURING INSTRUMENTS

AND FINE TOOLS

Here is a

PRECISION

MEASURING

MACHINE for the measuring of

small and

delicate parts


Use postpaid card. Circle No. 488

0-1" Range

Rectangular Steel Gage Blocks

Rectangular steel blocks formerly classified by Webber Gage Co. as Grade A, with accuracies of +.000004" and -.000002" reported, are now called A + by the manufacturer. The price of an 84-block set (including two .100" wear blocks of Croblox) has been reduced from \$413.00 to \$287.50. According to the company, these new A + blocks are of inspection quality, yet priced for everyday shop use.

In addition, an entirely new classification of Webber rectangular steel gage blocks has been created, featuring ±.000002" accuracies. Known as Grade AA, the new blocks are priced at \$555.00 for an 84-block set. Webber's former Grade B line, with +.000006" and -.000002" accuracies, has been discontinued. The manufacturer states that the new Webber classifications have



92-block set in new case.

been called Grades A+ and AA because their accuracies exceed those specified by the U. S. Bureau of Standards for Grade A blocks.

The steel blocks are now packaged in tough plastic chests.

Webber Gage Co., 12912 Triskett Rd., Cleveland 11. Ohio.

Use postpaid card, Circle No. 200



FISCHER MACHINE CO. ELEVENTH & WOOD STS. • PHILADELPHIA 7, PA.







.. OIL GROOVERS

The FISCHER No. 1 Oil Groover cuts a wide variety of grooves in bearings up to 8" in length and up to 5" inside diameter. A few simple settings permit you to cut continuous relieved, straight or spiral grooves at any angle from parallel to perpendicular to the work. Grooves may also be cut in shafts, housings, etc. This machine will slash grooving time and deliver continuous profitable production in your shop. It will pay to find out what it can do on your grooving jobs.

Test Indicators Provide for Deep Hole Work

Four new models, known as Models L-15, L-16, L-19 and L-20, have been added to the recently announced Federal Series L Testmaster line. In addition to providing long range and high magnification, these models are equipped with extra long contacts for deep hole exploration in jig borer and surface plate applications.

The .080" ball tip contacts are either



Long contact test indicator.

MINIATURE KNU-VISE CLAMPS DO MIGHTY JOBS

These tiny Knu-Vise teggle clamps are capable of exerting 100 to 150 Lhs. clamping force with a reach of 7/8 and 9/16 inch respectively in front of base. Other features are:

- · Clamping height, 19/32 above base.
- Double shear bearing pins prevent clamping spindle side-thrust or tilt.
- Largest diameter pins for size of clamp—80% minimum bearing area.
- When open, spindle head withdraws beyond front of base, permits vertical removal of largest parts.
- · All models have replaceable grips.



Four Models H-100 Twin-flange base



HL-100 Left-flange base



HR-100 Right-flange base





All shown 1/2 actual size

Write—TODAY, to Dept. A—for complete information.

Manufacturers of over 150 models of manually and air-operated clamps and pliers

KNU-VISE PRODUCTS

LAPEER MANUFACTURING CO.

3052 DAVISON ROAD LAPEER, MICHIGAN WESTERN DIV.: PECK and LEWIS CORPORATION 4436 Long Beach Ave., Los Angeles St. Calif., ADams 3-7146 CANADIAN DIV.: HIGGINSON EQUIP. SALES LTD. 1131 Pettit Road, Burlington, Ontario

1.446" or 1.497" long, depending on the model. All are graduated in .0005", have a total range of .080" (eight revolutions) and are available in either horizontal or perpendicular styles with either regular or large (1½" dia.) dials.

For more positive holding, these units are equipped with integral dovetails, rather than an end-mounted holding

bar.

Federal Products Corp., 1144 Eddy St., Providence 1, R.I.

Use postpaid card. Circle No. 126

Surface Finish Tester

Talysurf Model 100 is a portable, universal instrument, semi-automatic in its operation yet suited to a wide range of production inspection applications in the precision testing of surface finish. Work table, pick-up, stylus and support are combined with motorized drive in one solid assembly which can carry small work in universal work-holding fixtures or be fitted with quick loading production tooling.



MAGNIFIES AND ILLUMINATES FOR QUICK, EASY PRECISION SEEING



Other models available for bench or machine mounting. Write for catalog.

A sensational aid for increasing production speed and accuracy. Already in big demand throughout industry for easy viewing of tiniest work details. Many profitable applications for your plant.

* Trade Mark

Provides Binocular vision for fine assembly, inspection, testing and all precision visual tasks.

6" x 6" optically ground Lucite lens. 36 sq. in. viewing area, free from distortion.

High light transmission with two 4W fluorescent tube Localite.

Lens and light independently adjustable. Frictional collar disc joints give flexibility for any position.

1/2" steel tubular stand finished in Hammerine Metallic Silver. Rubber feet. Size 12" x 10" x 9" high.

Available at Electrical Wholesalers and Scientific Supply Houses

THE FOSTORIA PRESSED STEEL CORPORATION FOSTORIA, OHIO



Instrument easily checks many types of workpieces.

A lever starts the fast testing cycle, which gives in separate meter unit correct unwavering average readings in one stylus traverse. Talysurf Model 100 is claimed to provide the same positive surface finish values in arithmetical average microinches as does the master unit, Talysurf Model 3.

Engis Equipment Co., 431 S. Dearborn St., Chicago 5, Ill.

Use postpaid card. Circle No. 127

FRICTION SAWING STEEL, ETC.

IS EXCEEDINGLY FAST, SMOOTH, INVOLVES SO LITTLE DOWN-DRAG THAT FORMED PARTS CAN READILY BE CUT WITHOUT ANY REST.



Tremendous time and cost savings, in cutting sheet steel, formed or flat, trimming malleable and steel castings and similar operations, are available to you with these machines. Get the facts. Ask for FREE copy of "FRICTION SAWING".



The TANNEWITZ WORKS

GRAND RAPIDS, MICHIGAN TGL 6-1729



TANNEWITZ DIE-SAWS 24", 36", 48", 60" CAPACITIES

for CONTOUR SAWING, FILING, POLISHING The smoothest, fastest, most trouble-free Die Saws on the market. Write for bullstin.

SAWING MACHINERY SPECIALISTS


Portable Mist Generator

Designed for portability, this lightweight all-in-one mist coolant generator is easily detached and quickly moved from machine to machine. The steel mist nozzle, with its brass outlet, can be flexed in a fixed position to simplify mist applications. Mist can be applied directly to the cutting edges of tools where it is most effective. When chips interfere, mist can be applied from underneath.



Mist cooling from two sides.

In Checking Surface Roughness



In judging microinch roughness by eye or by "feel," sometimes you'll get the right answer, and sometimes not. You can never be SURE; for the "confusion factors" are many, and the brain misinterprets what the senses report — the same as with optical illusions.

That's one reason why industry depends on a confusion-proof shop instrument—the PROFILOMETER®when dependable roughness measurements are required.

FREE BULLETIN LT1 shows why surfaces that look alike, or feel alike, often differ in roughness by several hundred percent. Write for it! You'll be interested, and perhaps surprised.



Profilometer is a registered trade-mark.

MICROMETRICAL MANUFACTURING COMPANY

345 S. MAIN ST.

ANN ARBOR 4, MICHIGAN

Use postpaid card. Circle No. 408

MACHINE and TOOL BLUE BOOK

Coolant generator is offered in a onegallon size with one or two mist outlets and a four-gallon size with one, two, three or four outlets.

The Kett Tool Co., 5055 Madison Rd., Cincinnati 27, Ohio.

Use postpaid card, Circle No. 128

Automatic Units Feature Long Strokes, Cam Feeds

Quills are shown fully extended on these automatic units to illustrate available strokes—four inches on the No. 4 and No. 5 units, five inches on the No. 16 and No. 17 units. Models 4 and 16 are drilling units, Models 5 and 17 their companion tapping units.

Each unit has a cam feed for accurate repetition of the work cycle. Follower segments make the stroke of the spindle double that of the feed cam.

Each drilling unit may be converted to its companion tapping unit by using a different feed cam, a reversing motor



Models 4 and 16 are drilling units, 5 and 17 their companion tapping units.

and controls to reverse them. The tapping units can have time cycles as short as 3 seconds.

Kingsbury Machine Tool Corp., Keene, N.H.

Use postpaid card. Circle No. 129

Precision Surface Grinder

The Blohm hand operated Model 816 hydraulic surface grinder features high precision ball bearing assemblies running in ground and lapped replaceable





PRECISION GAGES



We can ship 90% of your gage requirements the same day we receive your order. All gages manufactured to AGD standards from highest quality tool steel. In addition to our standard line we can supply your special requirements within the following ranges:

Plain plugs .025 to 7.000 ins.
Plain rings .248 to 3.000 ins.
Thread rings and thread plugs .030—.125 to 12.000 ins.


Active Grinding & Manufacturing Company offers a complete grinding service backed by skilled men with years of experience solving complex grinding problems. Send us your prints for immediate quotation.

Dealer and Mfg. rep. inquiries invited—Attention dealers: No Investment required on our proven sales plan.

Active Grinding & Mfg. Co.

Phone: MOnroe 6-8567 2119-21 W. Hubbard St., Chicago 12, III.

Use postpaid card. Circle No. 410



Hand operated hydraulic grinder Model 816. steel ways for the longitudinal and cross movements of table and carriage; a 2 hp motorized spindle; table cross feed by ratchet lever with travel adjustment for easy and uniform cross movement; fine feed screw on the head elevating wheel with readings of .00004". Capacities are 8" x 16" table surface and 16" under the spindle.

National distributor: Hermes Machine Tool Co., Inc., 48-15 Northern Blvd., Long Island City 1, N.Y.

Use postpaid card. Circle No. 130



1, 1½, 2½ and 5 lb. sizes—order your alloy lead hammer requirements from your mill supply house or direct from:

KITZMAN MFG. CO.

Manufacturers Of Lead Hammer Products
15061 Hartwell Ave. Detroit 27, Mich.

Use postpaid card. Circle No. 411

MACHINE and TOOL BLUE BOOK

Grinding Head's Radial Feed Adjusted in Action

The Grind-A-Matic is said to assure uninterrupted precision grinding because the radial feed can be adjusted without stopping the machine. The air turbine grinding head can be mounted on a jig borer, boring mill, lathe, milling machine, drill press or other comparable machine tool.



Precision internal grinding head.



Use postpaid card. Circle No. 412



Use postpaid card. Circle No. 413

Fine adjustment can be made accurately on close tolerance work. Fine radial adjustments can be made in increments of .0002" over a range of "0" to .70" diameter by means of a graduated collar which is spring loaded to eliminate backlash. Coarse adjustment from "0" through 11/4" grinding radius is made while the spindle is stationary.

Threadwell Tap & Die Co., Springfield. Mass.

Use postpaid card, Cirele No. 131

JIG BORING


to your specification

At your disposal: Our sub-contract fig boring department, one of the best equipped in the East.

A. K. TOOL CO., INC.

Route 22, Mountainside, N. J. Telephone ADams 2-7300

Use postpaid card. Circle No. 414



RICO has a complete line of:

- Quality rotary carbide & HSS tools
- Available for immediate delivery
- Big savings on new tool costs
- Up to 50% savings on regrinds
- Special tools to specifications
- Distributor inquiries invited about better profit margins with RICO TOOLS.



Attach ad to your letterhead for more information.

RICO TOOL CO.


5915 DIXIE HWY. . SAGINAW, MICH.

Tool Detector Prevents Tool Damage, Scrap

For transfer-type production machines, a new tool detector eliminates separate probe and inspection heads and stations, prevents processing of scrap parts and, by signalling the control panel and shutting down the machine when one tool breaks, prevents additional tool damage.

The Protect-O-Tool is an electronic mechanism that "senses" the presence or

absence of a tool—or even a part of a tool in cases where a small piece of a drill or tap breaks off and remains in



Protect-O-Tool detects broken or missing tools.

the workpiece. The device is mounted on bushing plates behind the regular drill bushing hole.

The Cross Co., P.O. Box 3835, Detroit 5. Mich.

Use postpaid card, Circle No. 132

WILSON AIR COLLET CLOSER



STEP UP PRODUCTION 20%+

bar stock capacity

 Hold delicate parts without damage or adjustment


· Iron grip for heavy work

- No adjusting for stock or part variations
- Fingter-tip or foot control eliminates operator fatigue
- Eliminates jarring of head stock

(Ten day FREE TRIAL to reliable firms)

WILSON AIR COLLET CLOSER, INC. 909 40th Ave. NE, Minneapolis 21, Minn.

Use postpaid card. Circle No. 416



Use postpaid card. Circle No. 480

No. 35 T

SHARPENS SAWS Automatically, in Gangs

Just think of it! 100 26 gauge saws sharpened at one time. Takes saws up to $5\frac{1}{2}$ " dia. and $1\frac{3}{4}$ " thick. Saws are automatically indexed and sharpened within a variation of plus or minus .001 of exact diameter of entire lot.

WRITE FOR CIRCULAR 35T

The WARDWELL MFG. CO. 3807 Ridge Rd. Cleveland, O.



Plastic Steel® Makes Jigs, Fixtures, Metal-

Forming Dies, Plastic and Rubber Molds, Foundry Patterns . . . repairs broken or worn machinery. Find out how PLASTIC STEEL and other Devcon products can save time, cut maintenance costs and speed production in your plant - write for FREE Bulletin.

DEVCON CORPORATION

501 ENDICOTT STREET, DANVERS, MASS.


Use postpaid card. Circle No. 418

Bed Type Milling Machines Provide Wide Tables

Available in three standard arrangements to suit special needs, each of the models of the Producto No. 1 bed type milling machine has lever feed for rise and fall of lever head, micrometer cross adjustment of saddle, and pushpull selector switch and starter. Also featured are a 1 hp geared head motor and six spindle speeds in two ranges (111 to 1105 rpm or 247 to 2463 rpm). Unusually wide tables facilitate mounting of large fixtures.

Table work surface 9-13/16" x 27", lever feed, 10" stroke are provided by Model 1A. Model 1B offers choice of two tables (9-13/16" x 27", 10" stroke, hydraulic lever control for rapid approach, feed and return; 9-13/16" x 32" 15" stroke, electrical push-button control). Model 1C provides 9-13/16" x 32" table surface, 15" stroke.

The Producto Machine Co., 990 Housatonic Ave., Bridgeport 1, Conn.



6 spindle speeds—111-1105 rpm or 247-2463 rpm.

Use postpaid card. Circle No. 133



EEL BLUE

at bench; metal surface ready for layout in a few minmaking Dies and utes. The dark blue background makes the scribed lines show up in Templates sharp relief, prevents metal glare. Increases efficiency and accuracy.

> Write for sample on company letterhead THEDYKEMCOMPANY 2301G North 11th St. . St. Louis 6

Popular package 8-oz. can fitted

with Bakelite cap holding soft-hair brush for applying right



ACE

CARBIDE DRILLS

Whatever your carbide drill requirements may be... whether solid carbide or carbide tipped... it always pays to make sure you use an "ACE". Their "ground-from-the-solid", highly polished flutes have keener, stronger cutting edges. And that means finer accuracy, longer tool life, and lower drilling costs for you!

Call your local Ace Drill Distributor today!



ORIGINATORS OF "GROUND-FROM-THE-SOLID" DRILLS Use postpaid card. Circle No. 420 Drill Head Features 2-Bolt Spindle Arm Mounting

A multi-spindle drill head of the universal joint adjustable type, the Cleveland Pneumatic/Johnson, converts any single-spindle drilling machine for profitable single-pass, multi-hole work. It can be used for drilling, tapping, reaming, countersinking and counterboring—in a circle, straight line or random patern and to centers as close as 11/16", standard. Minimum close centers of ½" are also available.

This attachment is claimed to permit handling a greater range of work with



Outer-end Zerk fittings; snap-in universals.

GRAYMILLS Mist Coolant Systems



"The Best in Mist"

Precise air and fluid controls, corrosion proof. Translucent containers let you see the liquid level. Write for new folder.

3721 N. Lincoln Ave. CHICAGO 13. ILLINOIS

Use postpaid card. Circle No. 421

256

MACHINE and TOOL BLUE BOOK

higher precision. Hole pattern changes can be made faster, and maintenance is simplified. Anti-friction bearings are used throughout.

Spindle locating arms are mounted with two precision-milled T-slots on 8" and 10" diameters, providing greater rigidity and maintaining exact settings. Spindle rigidity is reported to be comparable with that of fixed-spindle heads.

To simplify lubrication, Zerk fittings are located on the outer ends of the spindle arms instead of the conventional inner-end position. As a result, they can be reached easier and faster. This design allows lubricating grease to move freely to all needle and ball

The universal joint components which drive the spindles are hexed at each end so as to snap into engagement without using tools. There are no setscrews or pins to remove.

Cleveland Pneumatic Industries, Inc., 64 Old Orchard, Skokie, Ill.

Use nestpaid eard, Circle No. 134

USE THIS NEW KIND OF DIAMOND **CUT-OFF WHEEL**

Gives narrower, smoother cuts on industry's toughest materials

... yet prices start at only \$32.25

Now . . . at production prices . . . DIATRONIC gives you a rim width of .006" that's accurate to a maximum total tolerance of .0005"-or your money back. This accuracy is built in by a new process. No break-in needed. New narrow cut reduces sawdust loss 30%. A must for \$3,000-a-pound silicon or germanium crystal. Cuts tungsten carbide, corundum. aluminum oxide, glass...practically anything. Stock orders shipped in hours; special wheels available. Write for literature, price list.

Another invention marketed by

NAVAN PRODUCTS, INC.

Subsidiary of North American Aviation, Inc.

Dept. BB-131, International Airport, Los Angeles 45, Cal.



Air Line Regulator Features Pressure Valve

Relieving-type air line regulator has a built-in pressure relief valve which allows increases in downstream pressure to bleed harmlessly into the atmosphere when such pressure exceeds the regulator setting. Adjusting the regulator knob to the desired pressure setting is all that is required.

It is not necessary to remove the regulator from the air line for main-



Model BRG-250; gauge and wall bracket optional.

tenance. The replacable poppet valve stem may be quickly removed and a new assembly inserted without disturbing the air line.

Regulator will reduce primary line operating pressures of up to 250 psi and will maintain desired downstream pressures of 0 to 50 psi, 0 to 125 psi, 0 to 250 psi, obtainable from separate units. The ½" and the ¾" models are available for immediate delivery. Other sizes will be announced.

The Bellows Co., Akron 9, Ohio.
Use postpaid eard. Circle No. 135

Heat Treating Furnaces

Two new electric heat treating furnaces for quantity production have a temperature range of 300°F to 2000°F.



STANDARD WOODRUFF KEYS are STANDARD in many plants including the large automotive manufacturers. Why? Because STANDARD Keys are precision made and tested before shipment. Available in all standard sizes for prompt shipment, Sizes range from \(\frac{1}{2} \times 1/16^2 \times 3\frac{1}{2} \times 2 \

. MACHINE RACKS

WRITE TODAY FOR CATALOG

STANDARD STEEL SPECIALTY CO.
BEAVER FALLS • PENNSYLVANIA
Plants: Beaver Falls, Pa.; Hammand, Ind.





Vertically operated plug-type door closes securely.

Chamber dimensions are 10"x7"x18" and 8"x6"x14". The furnaces feature multi-slab type of insulation, with heavy sheet steel body and cast iron end frames.

Embedded heating elements are claimed to give maximum heating efficiency and protection against chemical attacks and other physical damages. Hearth plate is made of cast nickel chromium. A vertically operated counterweighted plug-type door closes securely with brick to brick contact, may be opened to any position.

Cooley Electric Mfg. Corp., Dept. E3, 38 S. Shelby St., Indianapolis 7, Ind.

Use postpaid card, Circle No. 136



For Grinding, Drilling, Milling, Sawing

New Spra-Kool Midget consists of pencil-size brass spray nozzle, durable synthetic plastic tubing, adjustable bell check fitting, removable strainer in suction lube, spring wire attaching clip. Comes packed in mailing container, ready for attaching to airline. Suitable to any type of soluble coolant or oil. Order sample today.

BAR PRODUCTS CO.

4803 White Oaks Ave. • Rockford, III.

Use postpaid card. Circle No. 425



Use postpaid card. Circle No. 426



MUMMERT-DIXON FACING HEADS with Automatic Feed

One-way Tool Feed—8, 9 and 12" sizes.

Two-way Tool Feed—9, 12, 16, 20, 24, 30, 36, 40 and 46" sizes. Save many costly set-ups.

Bulletin Nc. 4141 Gives Full Details

MUMMERT-DIXON CO. 122 Philadelphia St., Hanover, Pa.

HYBCO TAP GRINDER

Sharpens Chamfers, Flutes and Spiral Points



Model 1100

 Capacities No. 0 Machine Screw to 1½" Hand Taps

HENRY P. BOGGIS & CO.
710 E. 163rd St. Cleveland 10, Ohio

Use postpaid card, Circle No. 428

PRECISION INDEXING TO 0.001"

with GEM-17 DIAL INDEX TABLE

True geneva motion gives positive lock, speeds to ½ sec. Rugged 1000 lb. fixture load capacity with solid anvil capacity of 30 tons. Standard 17" dia. (plates to 36" available). Gray's engineering staff will adapt tables to your work problems.

Send for Bulletin DI-17 and full information.



GRAY EQUIPMENT CO.

Use postpaid card. Circle No. 429

End Mill Holders

New type end mill holders may be used in all horizontal and vertical milling machines with No. 50 national



standard taper spindles having Cincinnati Arbor-Loc feature. They serve double or single end mills with shanks from 3/8" to 11/4", inclusive. Changing the holder is a simple operation, yet it holds the end mill securely.

The Weldon Tool Co., 3000 Woodhill Rd., Cleveland, Ohio.

Use postpaid card, Circle No. 137

Chucks Have Swivel Bases

Swivel bases are an important new design feature of O. S. Walker permanent magnetic chucks, increasing the usefulness of this holding device for all kinds of flat or angular machining operations. Chuck and workpiece may now be tilted to 45 degrees right or left of center. Exact position is set directly from an integral graduated dial.

As in other Walker permanent chucks, the new swivel units incorporate ceramic magnets. The bar poles, only ½" wide, give uniform holding over the entire chuck top. Work-holding ability is excellent, even on very thin parts. Secondary external fields are controlled



Complete range of sizes available.

to prevent magnetism from invading the machine table and ways. In the "off" position, the chuck is completely demagnetized.

The model illustrated has 8" x 24" table face. A complete range of sizes is available to suit customer requirements

O. S. Walker Co., Inc., Worcester, Mass.

Use postpaid card. Circle No. 138

Production Boosted 25% Using New Cutting Fluid

Dromus Oil E, water-soluble cutting fluid for use with throwaway carbide inserts, is said to result in a minimum 25% boost in production rates and costs by permitting a full one-third increase in the work feed rate when the proper cutting speed is selected. When used with an improved metalworking technique the fluid promises new efficiency peaks in the aircraft, missile, automotive and heavy machine industries.

Carbide tools are reported to be protected against breakage resulting from thermal shock. The fluid produces cool chips, permits close dimensional tolerances by reason of reduced workpiece heating, produces a brighter surface finish, and is rust-resistant, the manufacturer claims. It is also said to have possibilities for use with ceramic inserts which presently are worked dry at twice the speed of carbide inserts. Shell Oil Co., 50 W. 50th St., New

Use postpaid eard. Circle No. 139





New Roto-Pin type lock is inte-gral part of all Pannier Supreme Holders...eliminates loose, bent, dropped, or lost pins . flip it open to change type . flip it back to securely lock type in clear-marking position.

> Write for complete data.

SUPREME HOLDER WITH ROTO-PIN LOCK

fe, fast type chang-g. Holder in variety ing, Holder in variety of styles. Machined from High-Grade Bar Tool Steel. Hardened anvil maintains type alignment. Striking Head of Tool Steel . . , Replaceable to add long service life to Holder.

MARKING CHANNER DEVICES THE PANNIER CORPORATION

203 Pannier Building . FAirfax 1-5185 . Pittsburgh 12, Pa. Offices: Los Angeles + Chicago + Cleveland + Philadelphia + Birminghant

Use postpoid card, Circle No. 430

For Small Precision Work

You Need The . . .

LINLEY JIG BORER

The Linley will meet the most exacting requirements and save you money by releasing your larger ments and save you larger by releasing your larger borers for heavier jobs. it's a precision teel ... versatile and flexible; casy to set up and fast casy to set up and tast operating. Write to re-ceive complete informa-tion on the many im-provements that are now standard on this borer.

Table Size: 7" x 171/2" Table Travel: 61/2" x 18"



LINLEY BROTHERS CO.

663 State Street Ext.

Bridgeport 1, Conn.

Use postpoid card. Circle No. 431


York 20, N.Y.

Center Column Grinder Has 80" O.D. Work Table

The Blanchard 80-A3 is a center column automatic surface grinder with 48" I.D. x 80" O.D. work table and three grinding wheel spindles. A finger-type feed control caliper maintains each wheel at correct height. Since the work table is nonmagnetic, all parts are held in fixtures during the grinding cycle.

Specifications include: motors-25, 30


SAVE UP TO 40% ORDER DIRECT



Falls Tool Co. IOWA

savings available.

Use postpaid card. Circle No. 432



This model rough grinds both sides of both ends of automotive connecting rods.





THE GRANT MFG. & MACHINE CO. Use postpaid card. Circle No. 433

Bridgeport 5, Conn.

CE Station

or 40 hp each spindle, 3 hp table; floor space—7' 8" x 8' 2"; feed—manual or power.

The Blanchard Machine Co., 64 State St., Cambridge, Mass.

Use postpaid card, Circle No. 140

Stainless Rings and Discs

Stainless steel rings and discs machine-cut to size may be secured at a cost generally less than the price of




Machine-cut stainless steel rings and discs.

material flame-cut, sheared or sawed and then machined to the required size and edge smoothness. Size accuracy is normally held within plus or minus 1/32", although cutting can be done to much closer tolerances when required.

The size accuracy and smooth edges of machine-cut stainless rings and discs make the materials ready for many purposes when received.

Joseph T. Ryerson & Son, Inc., Box 8000-A, Chicago 80, Ill.

Use postpaid card. Circle No. 141



Use postpaid card, Circle No. 435



GEORGE SCHERR CO., Inc.

200 MT LAPAYETTE STREET . NEW YORK 12, H. Y. ...
Use postpaid card. Circle No. 436

STOP... HAND WORK



Use these Handy PORTABLE ELECTRIC RECIPROCATING TOOLS for Greater Production. Better, More Uniform Work-All with less Operator Fatigue. Fixed strokes are ½% or ½% long. Operate on 110 volts AC-DC. Deliver 1000 PUSH-PULL strokes per minute. Try one of these tools on your next job.


Send for Descriptive Literature.

ACME TOOL CORP.

71 W. Broadway . New York 7, N.Y.

Satisfied?

that it's PARALLEL?
. . STRAIGHT?



You will be if you use "Milwaukee" Precision Equipment—Surface Plates, Straight Edges, Angles, Box Parallels, Standard of the industry!



Engineers & Machinists Since 1907
165 S. Barclay St, Milwaukee 4, Wis.
Use postpoid cord. Circle No. 438

7 REASONS WHY FLYNN BORING HEADS ARE MOST USED



LEADING NAME IN
BORING HEADS FOR 40 YEARS
19 MODELS Write for catalog
FLYNN MANUFACTURING CO.

Use postpaid card. Circle No. 439

Drilling Machine Has Unit with 11/2" Stroke

An automatic precision bench type drilling machine is equipped with an



Pulley drive provides wide spindle speed range.

air-hydraulic drill unit with $1\frac{1}{2}$ " total stroke, adjustable for length of quick advance, feed rate, and total depth.

A wide range of spindle speeds is possible through the pulley drive arrangement. The compact 12"x21"x30" unit is mounted on a sliding base with 4" of end adjustment.

Included in the machine are pneu-



Use postpaid card. Circle No. 440

MACHINE and TOOL BLUE BOOK

matic controls and electrical controls with a push-button station,

Hartford Special Machinery Co., 287 Homestead Ave., Hartford, Conn.

Use postpaid card. Circle No. 142

Position Production Tables

A two way production table with plain air feed in both directions and a longitudinal 12" maximum stroke is illustrated. This Model No. 1 has no cross feed. It is equipped with hand control valve, cylinder, and flow control.



#1-air feed, both directions, 12" max. stroke.


The manufacturer has two other models available also. The Model No. 2 production and layout table has air feed in both directions, a maximum longitudinal 12" stroke, and a 2" hand wheel cross feed. It is equipped with hand control valve, cylinder, and flow control. Drilling and layout table, Model No. 3, features hand feed screws in both directions, and longitudinal and cross feed.

Rotex Punch Co., Inc., 2350 Alvarado St., San Leandro, Calif.

Use postpaid card. Circle No. 143

20 TO 200 D.P.

SEND YOUR PRINTS FOR QUOTATION



SPURS • HELICALS • WORM AND WORM GEARS.

STRAIGHT BEVELS • LEAD SCREWS • RATCHETS.

CLUSTER GEARS • RACKS • INTERNALS • ODD SHAPES.



Use postpaid card, Circle No. 441

WATERLESS DEGREASING

"A Free trial sample upon request. Try Q200 in YOUR production and maintenance. Approved by Underwriters' Labs., Inc."



BARCO Chemical Products Co.
701 5, LaSalle St. Chicago 5, Illinois

Use postpaid card. Circle No. 442

You Need an Extra Hand Now to Speed Up Production! HEIMANN TRANSFER SCREW SETS

Here is the faster, more precise way of transferring open and blind screw holes—make savings in "wage-dollars-per hour" of your expensive hands on every job. A die-and-tool maker's tool with many other applications for die makers and machinists. A set of 6 Hardened Screws nested in combination holder and wrench—no other tools needed. Get more work now-save money tool

HEIMANN MFG., CO. . URBANA, OHIO

Use postpaid card. Circle No. 443

IN 11 SIZES-No. 6 to 1"



ACME TAPS From Stock!

HIGH PRODUCTION TYPE

with Exclusive

"Lead Screw Pilot"

Improve Acme Tapping with Single Pass Acme Taps. Eliminate Shaved Threads, Improve Finish, Reduce Machining Time. No Lead Screw Required. Sizes %" to 6" diameter.

Write for stock list and brochure

GAGES? Cost less when ordered with tap

HORSPOOL & ROMINE MANUFACTURING CO., INC. 5850 Marshall St., Oakland 8, Calif.

Use postpaid card. Circle No. 444

.................

How to ENGRAVE **PANELS** and SIGNS to 30" WIDE by any length

Use the LOW COST precision built Preis-Pente 20-4 Engraving Machine. It does the work of larger machines, costing much more.

...............

- · Pantograph is graduated with reductions from 1:1 to 100:1 and will reduce to any size to infinity.
- · Pantagraph and spindle link joints equipped with precision ball bearings throughout.
- · Precision ball bearing cutter spindle.
- · Collet capacity from 1/10" to 1/4" and standard tager shank cutters.
- · Six spindle speeds-5,000 to 14,000 rpm.
- · All feed-screw dials graduated in .001".

Write for complete details and prices. For immediate attention write directly to manufacturer below. Ask for means: representative.

H. P. PREIS ENGRAVING MACHINE CO. 645 U.S. Route 22 Hillside, N. J.

Use postpaid card. Circle No. 445

STAGGERED TOOTH



High speed. Right hand 1/2" shank. Diameter from 1/4" to 11/2". Standard sizes in stock for immediate delivery. Complete set 41 sizes—available in sturdy, hardwood box. Saves time and money, because you always have the size

you need.

WRITE, WIRE OR PHONE Jobbers' inquiries invited

KEO CUTTERS, INC.

25040 Easy St., Warren, Mich. Warehouse: 1300 S. Soto St., Los Angeles 23, Cal.

Use postpaid card, Circle No. 446

Economical! Compact! Durable!

Machine

ROLLS:

Angles . Flats Pipes . Rounds

Squares . Tees

Channels . Beams



TOOL & MACHINE CO. 31st & Ridge • East St. Louis, Ill.

Use postpaid card. Circle No. 447

MACHINE and TOOL BLUE BOOK

Write

Brochure

JEMCO ELECTRIC HAND SHEARS and NIBBLERS

in use by major industries for over 25 years



Nibblers supplied with either standard or with right anale heads to cut corrugated metal.

Nibbler capacties-

18 gauge; 14 gauge and 11 gauge Shear capacities-

7 gauge: 12 gauge: 14 gauge and 16 gauge

Write us for circular

JEMCO TOOL CORPORATION

22-24 State St.

Seneca Falls, N.Y.

Use postpaid card. Circle No. 448



DON'T LET THIS HAPPEN

End Oily Floors with

Reduce Accidents and Costly Time-Offs No Fire Hazard!

Write For Free Sample!

TAMMS INDUSTRIES CO.

228 N. LaSalle St.

Chicago 1, III.

Use postpaid card. Circle No. 449



Hundreds of installations over the past few years have proved the economy of the only hardness tester which combines all scales of Rockwell Test (15 to 150 kg.

The Kentrall cuts costs because it does the job of two conventional testers, requires only half the space and maintenance. Write for more detailed information, plus a list of prominent users who have switched to Kentrall.

THE TORSION BALANCE COMPANY

Main Office and Factory: Clifton, New Jersey Sales Offices: Chicago, San Francisco

Giant Horizontals Provide High Altitude Work

The 80 Series Giddings & Lewis horizontal boring, drilling, and milling machines, with an 8" or 10" diameter spindle, feature vertical headstock travel in excess of 20', heavy-duty welded steel construction, and new operating advantages. These machines are reported capable of boring, turning, or facing over 12' diameters, developing 7½ hp per revolution, and can



So popular with users.


COLLIS Heat Treated Sleeves and Sockets are manufactured by skilled workmen to give long durable service and extra long life. This type of sleeve has less chance of nicks and assures same accuracy with longer runs.

Call at once for our representative to explain about the Complete Collis Line of Lathe centers, Arbors, Drill Drifts, and Magic Type Chucks as well as Sleeves and Sockets and Collets.

"Call Collis for Service"

THE COLLIS CO.

DEPT. A, CLINTON, IOWA Use postpoid card. Circle No. 450



Model 880-FUAR floor-type with an underarm.

be furnished with most types of automatic controls. Any type of programmed controls can be used to initiate and regulate all functions.

Illustrated is the Model 800-FUAR floor -type with an underarm. It has an 8" diameter spindle, 84" spindle underarm travel, 17' headstock travel, and 20' column travel. Other equipment and accessories on this machine include a 3-ton, 4-speed hoist, telescopic sights for viewing all scales and verniers, and a counterbalanced pendant station, to name a few features.

The four basic models in the 80 Series include floor-type, floor-type with underarm, floor-type with cross-sliding column, and planer-type machines.

Giddings & Lewis Machine Tool Co., Fond du Lac. Wis.

the master mechanic's way with oilstones

deburring

whether deburring and honing small knife blades for hand cutters, or chamfering and fitting close tolerance dies . . . hand stoning is the better way for precision work, for better cutting edges, for higher quality finishes, and for longer tool life. Send for your free copy of the Hand Stoning Handbook to Dept. BB-4.

BEHR-MANNING PRODUCTS: Coated Abrasives . Sharpening Stones . Pressure-Sensitive Tapes NORTON PRODUCTS: Abrasives · Grinding Wheels · Grinding Machines · Refractories · Electrochemicals



Use postpoid card. Circle No. 451

Variable Speed Drive

A 1½ hp electric motor drives a variable displacement hydraulic pump, through silent chain and sprocket, which



Speed control from 0 to 750 rpm.

in turn drives a fixed displacement hydraulic motor in a new variable speed drive. Rotation of hand wheel provides infinite speed control from 0 to 750 rpm. A reversing lever provides instantaneous rotational change. Reversing is independent of speed control.

Ball bearing motor, 1½ hp, is available in either three phase 60 cycle 220 volts, or single phase 60 cycle 220 volts capacitor type. Over-all dimensions are 12" long, 7½" wide, and 16½" high. Weight is 90 lb.

The unit is used for lathe heads, reamer drives, pumps, blowers, milling, test benches and many other uses.

Roberts Mfg. Co., 849 West Grand, Chicago 22, Ill.

Use postpaid card, Circle No. 149

Drill Units Have 6" and 10" Stroke

Two new Holomatic drill units, the 6" stroke Model 26 and the 10" stroke



SPELLMACO "SPOTTERS"

A matched set of transfer punches for toolmakers, machinists & tool cribs

Used for transferring location of threaded, drilled and reamed holes, slugs, blanks, etc.

Precision made of finest tool steel—Carefully heat treated and tempered for long life—0025 undersize to facilitate use—Black exide finish Set x3-17, 28 punches with indexed stand—sizes $3/32^{\infty}$ to $1/2^{\infty}$, by $1/64^{\infty}$ — slue handy $17/32^{\infty}$ size, Length $4\%^{\infty}$ ONLY \$17.80 Single sizes available

R. L. SPELLMAN CO. - URBANA, OHIO

NOW . . . SET UP COMPOUND ANGLES INSTANTLY

Save time and money with this Master Multi-Swivel Vise. And you can often save the cost of an expensive jig or fixture! Investigate the money and time saving possibilities by writing today for free illustrated folder.


DONOVAN MFG. CO.

80 Batterymarch St.

Boston 10, Mass



Use postpaid card. Circle No. 453



Drills 1/32" to 56" dia. holes in mild steel.

Model 210, along with the 4" stroke Model 24, are completely self-contained reciprocating quill-type power devices for use on production drilling, reaming, facing and other similar machine applications. They can be used individually or in groups.

Concentric construction of the spindle, quill, hydraulic cylinder, air thrust piston and positive stop is said to assure maximum accuracy and long life.

Six standard drives, incorporating electric motors from ½ to 2 hp, develop spindle speeds from 200 to 8000 rpm. Six standard interchangeable spindles for driving single tools or multiple spindle heads are available for all three models.

Drilling capabilities with 80 psi input air pressures are 1/32'' to 5/8'' dia. holes in mild steel; with 150 psi, extended to 1''.

Hause Machines, Inc., 809 S. Pleasant, Montpelier, Ohio.

Use postpaid card. Circle No. 150



All hinges shown can be furnished with special holes, cutouts and bends to blue-print in metals to suit the job.

THREE-FOURTHS

AUTO MOULDING & MFG. CO. 1110 E. 87TH ST. CHICAGO 19, ILL.

Use postpaid card. Circle No. 454

SPECIFICATIONS
Open width 7/8" to 6"
Gage Material .040 to .125 OP
Pin Diameter .101 to 3/8
Lengths to 120"

SEMI-OFFSET


Multi-Purpose Furnaces

Thermolyne top-loading electric furnace Type 2100 is adaptable for use as salt bath, melting, vertical muffle or crucible unit. Recommended laboratory and shop uses encompass investigative and pilot runs as well as short run production and the heat treating of small parts. The maximum chamber temperature for intermittent operation, 1900° F.

The basic unit includes the hexagonal furnace (115 or 230 volts, chamber 6½"



May be used as salt bath, melting, vertical muffle, or crucible furnace.



Want better milling production? Use Brown & Sharpe arbors, adapters and collets

Production from milling cutters and machines is only as good as the accessories that hold the cutters. It pays you to get high-quality Brown & Sharpe arbors, adapters and collets — made by a company that has also made cutters and machines for 125 years. They get more out of any milling machine. Avail-

able through your nearest B&S industrial distributor. Brown & Sharpe Mfg. Co., Providence 1, R. I.



dia. x 11" deep), stainless steel pot (6½" dia. x 7½" deep) with cover and convenient lifting handle, and thermo-

couple in protective tube.

The furnace case is of heavy-gauge welded and braced steel construction and is finished in corrosion- and heat-resistant enamel. Three separate types of insulation are so utilized as to minimize heat loss and maintain even temperatures. Heavy gauge nickel chromium heating coils held in re-

fractory supports line the chamber uni-

Thermo Electric Mfg. Co., Huff St., Dubuque, Iowa.

Use postpaid card, Circle No. 159

Dividing Head for Indexing Precision

The OW12-OMT optical dividing head is of robust construction, the spindle being mounted in solid bearings, and embodies a non-deflecting clamping

Even without pilots or finger stops .

"RFC" Automatic ROLL FEEDS*

control feeding to utmost accuracy

REVERSES INSTANTLY

Shift Feed Finger spring from one lug hook to opposite side

CAN'T SLIP


Each wedge has 4 points of contact

NO RATCHETS OR PAWLS . . .

to wear down

PATENTED CLUTCH MECHANISM . .

with fewer working parts for less



Write for new brochure containing 39 standard feeds which are applicable to all METALS, FELT, CARDBOARD, PLASTICS, PAPER, WIRE, RUBBER in ALL WIDTHS, LENGTHS and THICKNESSES.

IMPORTANT: Please state make, type and tonnage of press when inquiring.



MANUFACTURERS OF QUALITY FEEDS FOR POWER PRESSES
Use postpoid cord. Circle No. 456



• GRINDERS • DISC GRINDERS and BUFFERS
We know what goes into these Grinders
and Buffers! That's why we can make
this offer.

Point for point — you just can't beat QUEEN CITY Heavy Duty Disc Grinders and Buffers. Built to stand up under hardest use . . . heavy duty motors deliver full horsepower. Wheels, guards, switches, cords, eyeshields are of highest quality . . . selected to deliver long, trouble-free service.

Choose from a complete line of floor or bench types . . . in sizes from ½ to 10 H.P. and buy them for 20 to 30% under competing makes. Try them for 30 days on money-back guarantee!

QUEEN CITY MACHINE TOOL CO write for FREE CATALOG TODAY!

3912KELLOGG AVE. Cincinnati 26, Ohio "Known for Quality for Over 50 Years"

Use postpaid card. Circle No. 457



device. Direct readings to 2 seconds of arc are accomplished by employing a micrometer eyepiece which is illuminated by low voltage bulb. For coarse adjustment, an external scale ring is provided close to the eyepiece.


George Scherr Co., Inc., 200 Lafayette St., New York 12, N.Y.

Use postpaid card. Circle No. 199

Lever Actuated Typewriter Exerts to Two Tons Pressure


Hand operated detail press for low production name plate and small part stamping features automatic spacing and alignment of work. Easy turning character wheel locates each character quickly and easily, with accurate alignment.

The operating lever will deliver up to two tons pressure on the work area, enabling the machine to mark in hard materials such as stainless steel. The marking depth and pressure may be



Use postpaid card. Circle No. 458

MACHINE and TOOL BLUE BOOK



preset and controlled by the operator to assure clearly defined and even characters.

Machine is lightweight and easily transported from one working area to another. It is available in hand operated models and in electric keyboard operated models.

Defiance Machine and Tool Co., 1920 S. Vandeventer Ave., St. Louis 10, Mo. Use postpaid card. Circle No. 153

COOK

Now you can obtain non-marring Lead hammers — Hammer handles — Make 'em yourself — Production and Ladle Molds. Free folder — ask about our Remelt allowance service.

COMPLETE LEAD HAMMER

SERVICE

ALL AT LOW LOCAL PRICES

L. H. COOK, INC. — EAST PROVIDENCE 14, R. I. WESTERN DIVISION — SIMPLEX ENGINEERING & MFG. CO., 4271 STATE ST., POMONA, CALIF.

Use postpaid card. Circle No. 459

"Jorgensen"

Ponu -

CLAMPS



ADJUSTABLE CLAMP CO.

the clamp folks
403 N. Ashland, Chicogo 22, III.

Send for FREE 32-page eatalog showing complete line of styles and sizes.

Ask your Supplier.

Use postpaid card. Circle No. 460

MIST

The NEW KOOLMIST

COOLANT



What KOOLMIST Can do:

STEP-UP PRODUCTION . . . Rapid cooling at cutting point permits increase in speed and feed and longer tool life. Save cost of Chip Spinning and coolant reclamation. Installations can be made in minutes. Readily portable from one machine to another. Operates with only 54 lbs. pressure.

Features of KOOLMIST





Character of spray—course or fine—easily controlled. KOOLMIST CONTROL UNITS can be operated from any container—and 10 or more units can be operated from one container. Many models to choose from.

PRICE only \$19.95 and up.
Used by hundreds of world's largest plants.

Send for FREE Literature-

LLOYD TOOL CORP.

3330 E. Colorado Street
PASADENA, CALIFORNIA



Commander

MULTI-TAPPER

TAP up to

8 HOLES at a TIME . . . in any pattern

. AUTOMATIC TAP REVERSAL

. FITS ANY DRILL PRESS

PRECISE DEPTH CONTROL
ultaneously handles different tap

MULTI-TAPPER simultaneously handles different tap sizes and pitches—can be set up for automatic or semiautomatic operation. Makes any drill press a production tapping tool.

Want a demonstration in your plant? Write us and we'll arrange it with your nearby Commander Distributor. Ask for your copy of the new Commander Production Tool Cataloa.

Commander MFG. CO.

Use postpaid card. Circle No. 462

OMEGA NO. 1

OPTICAL JIG BORER

16" x 24" TABLE

TABLE TRAVEL: 12" x 20"
INFINITELY VARIABLE
SPINDLE SPEEDS
SPINDE NOSE TO
TABLE TOP:
0"—22"



PROJECTION TYPE OPTICAL SCALES READING DIRECTLY IN TENTHS; INFINITELY VARIABLE SPINDLE DRIVE; TACHOMETER; MOTOR AND CONTROLS.






Miniature Toggle Clamps

Knu-Vise tiny toggle clamps in the H-100 series, which features a horizontal handle, have a 100- to 150-lb. clamping force, for a reach of %" and 9/16" respectively in front of base. The H-100 series includes four model designs: H-100 with twin-flange base; HL-100 with left-flange base; HR-100 with right-flange base, and SH-100 with straight base for side mounting.

Lapeer Mfg. Co., 1150 W. Baltimore, Detroit 2.



Series H-100 has horizontal handle.



wear control with the TOOL-GARD

This new super-sensitive "TOOL-GARD" monitors tool wear seven times more effectively than existing load measuring instruments. It reveals the slightest increase or decrease in power consumption, most important for the accurate appraisal of tool wear and efficient operational conditions.

The "TOOL-GARD" has 2 primary functions-

1. When the instrument is set to "TOOL-GARD" position it cancels out the non-cutting load and monitors only the amount of tool wear taking place during the operation. It also controls the <u>safe limits</u> of tool or other pressures, particularly important in "blind machining" or grinding applications.

2. When the instrument is set to "LOADMETER" position it monitors the machine tool's efficient load limits. By permitting the use of maximum horsepower, safely, the machine can be operated at full capacity without the danger of damage to the machine, the tooling or the workpiece.

The "TOOL-GARD" pays a dividend every time you use it

KNOW ____ without stopping the operation—when it's time to change a tool . . . not too soon and not too late.

SAVE ____ unnecessary lost time—checking tool conditions and finished work dimensions.

SAFELY ___ get full measure of tool performance from each grind and more grinds per tool . . .

you will with the "TOOL-GARD".

Some Open Territory . Dealer Inquiries Invited

Write: FUTURMILL, INC.

6360 HIGHLAND ROAD



Advertisements acceptable in THE MARKET PLACE include those for employment, sales services, production facilities, representation and related needs. Rates: \$20 per column inch per insertion. Maximum size advertise-ment accepted in this section is three inches.

Copy should reach us by the first of the month for next month's issue.

MACHINE and TOOL BLUE BOOK

A Hitchcock Publication

Wheaton, III

END MILLS SALVAGED

H. S. and Carbide 50% of new price if held to next standard size.

40% of new price if std. size is not required.

We make them at least as good as new.

CUTTING TOOLS, INC.

134 Seymour Street Stratford, Conn.



-Tested Know-How & Show-How-

MACHINE TOOL RECONDITIONING

Send for free folder describing illustrated book featuring hand scraping methods (3rd printing)

Machine Tool Publications
215 Commerce Bldg.
Street St. Paul I, Minn. East 4th Street

DRILLS-

Special for jobs no other drills will do, at regular drill prices.

DRILLS-

For mongrel size holes. We stock 486 metric sizes .0118" to 1.500"

DRILLS-

Specially made for your job, if our regular types do not meet requirements.

> **ELISHA PENNIMAN** ELMWOOD 10, CONN.

to locate on edge within .0005"!



IUMP EDGE FINDER

Complete satisfaction PRICE \$2.50 or full refund.

Postage free if payment with order

FLISHA PENNIMAN

ELMWOOD 10. CONN.

Exclusive representatives wanted for: ORIGINAL TROUBLE DETECTOR

For machines, motors, vehicles, covered and underground pipe lines. No more operating trouble. Weight 2½ lbs. Excellent references.

RIVERDALE TECHNICAL CORP. 1 East 53 Street New York 22, N.Y.



0003 HOLE LOCATON IN ONE MINUTE Thousands of companies and individuals FINDERS for years Ask for literature with users list and dealer in your area. with users inte and dealer in your area, Hardened and ground on all surfaces in-cluding contours for balance, 590° size \$2.50. Deluxe .200° size \$10.00. Vise stop for holding same hole location in several pieces \$2.95.

Postpaid Except C.O.D. Charges

GLOVER MFG. CO. 423 PARK AVE MEADVILLE, PA

Here's a tool machinist will use KELM T-SLOT CLEANER

Cuts costly "cleanup down-time cuts costly "eleanup dewn-time" speeds set-ups. One end cleans clogged T-slots, the other speens out chips in peckets at end of machine table—quickly and efficiently. Write for literature, \$1.25 ea. \$12.00 per doz.

KELM MANUFACTURING CO. Coloma, Michigan

\$1.25 EACH



NEW PILL

inteRapid GROOVE CHECKING

Comparator Gauge

offers...

- * Precision, range and versatility
- ★ 3 and 2 point checking—3 point tor production, 2 point for short runs
- ★ Quick setting adjustment knob sets scale reading from gage blocks, mikes or ring gauge.
- Locking lever locks arms after setting is made
- ★ Retracting lever allows in and out movement of measuring arms while positioning instrument
- Easily read large meter-type face is graduated in .0005".
- ★ Interchangeable tips offer versatility in application

The new P.D.Q. groove checking comparator gauge offers guaranteed Swiss accuracy and workmanship.

Sets come complete with both short and long groove tips, special "flat bottom" tips, button tips, centering arms, spare screws, special socket wrench and screw driver, all in one compact, sturdy case. Units measure internal grooves from 3/8" to 6"

Representatives in principal cities



comparator gauge

PORTAGE Double-Quick, Inc.


1037 SWEITZER AVENUE . AKRON 11, OHIO

SUPERMILL Milling Machines PLAIN . UNIVERSAL . VERTICAL . TURRET

Whatever your needs, there's a SUPERMILL to give you the highest precision at lowest cost. Complete line of milling machines of all types and substantially built and

designed for strength and versatility ... for greater power, speed, precision

and efficiency. No other milling machines offer today's shops more longrange satisfaction and savings.



SUPERMILL Vertical **Turret Mills EXTRA-HEAVY DUTY**

Increased accuracy and capacity . . . including extra-heavyweight base, more (1½) H.P., longer table. Any angle milling, drilling and boring for both sensitive and heavy duty work.

from \$2,175



Immediate Delivery -

Parts and Service Coast to Coast

SIZES from #1 up to #6 Dual Power

The SUPERMILL features DIAL-TYPE controls, hardened and ground spindle and gears, anti-friction bearings and many other qualities found only in mills of the highest caliber. A complete selection of optional equipment includes motor-driven universal overarm attachments, dividing heads, vertical and slotting attachments as well as tracing equipment.

from \$3,650

EQUIPMENT DIVISION

135-53rd STREET BROOKLYN 32, NEW YORK HYacinth 2 7400

6945 BANDINI BOULEVARD LOS ANGELES 22, CALIF Raymond 3 9231

rite Today for Detailed Specification Brochures

Use postpoid card, Circle No. 466

MACHINE and TOOL BLUE BOOK


YODER

Pipe and Tube Mills—Product dependability—integrity of manufacture—engineering for specific production needs have all contributed to establish Yoder equipment as the industry standard of excellence. Since 1909 Yoder-built machinery, including

Pipe and Tube Mills, Roll Forming Equipment and Rotary Slitters, have earned worldwide customer satisfaction and recognition. Profit from Yoder's years of engineering and service experience. Send today for the illustrated Yoder Pipe and Tube Mills Book.

THE YODER COMPANY . 5509 Walworth Avenue . Cleveland 2, Ohio





ABILITY. Dollar-wise, they're the most economical press you can buy.

Perkins Presses are being profitably operated today in some of the largest metal working plants in the country. There's a model to fit your particular requirements.



Gilman PRECISION SLIDE ASSEMBLIES

...available FROM STOCK

in 132 standard types and sizes



LIGHT DUTY BASIC TYPE



HEAVY DUTY BASIC TYPE



LIGHT DUTY
TYPE WITH
RETURN SPRING




HEAVY DUTY MICROMETER STOP TYPE



LIGHT DUTY LEAD SCREW TYPE



HEAVY DUTY LEAD SCREW TYPE



CYLINDER
POWERED
(in-line
mount)



CYLINDER
POWERED
(lower
mount)

Write for free catalog.



RUSSELL T. GILMAN, Inc.

620 Beech St. . Grafton, Wis.

Use postpoid card. Circle No. 483

and Startling

(in price and performance)

FAMCO'S NEW POWER PRESS LINE

Here's the power press line that gives you all the press economies you need . . . lower maintenance, greater production and lower cost.

Furthermore, Famco Power Presses—6 to 18 tons—are equipped with a pneumatic friction clutch and brake. A high torque, low inertia unit that self-compensates for wear and assures you years of additional press life.

Write today for literature on the new Famco Power Press line.



Pneumatic friction clutch and brake, never needs adjusting, never overheats.



machine company

3118 Sheridan Road . Kenosha 4, Wisconsin

PRESSES . . . AIR, ARBOR, POWER, FOOT SQUARING SHEARS, MILLING MACHINES, BAND SAWS

Use postpaid card. Circle No. 469

Products Index

bue book

Abrasive Cloth, Paper, Discs, Stones, Belts, etc. 22, 38, 269 Abrasives, rubber bonded, 22 Absorption Products, 267 Adapters (See: Tool Holders. adapters) Air-Operated Equipment, 15, 209, 218, 247, 254, 286 Alloys, 13, 104 Aluminum, bars, 43 Aluminum Stock, 43 Angle Plates (See: Plates, angle) Angles, 199, 264 Anti-Friction Compounds, 190 Arbors, 268, 272 Arbors, motor, 64 Bacterial Inhibitors, 121 Balls, master, 193 Bar Machines, automatic, 16-17, 21, 29 Bars, aluminum (See: Aluminum, bars) Bars, steel (See: Steel, bars) Bearings, thrust, 200 Benches, work, 220 Bending Machines & Equipment, 50, 152, 217, 266 Bits, tool, 13 Blades, cut-off (See: Tools, cutting-off, blade) Bolts, eye, 4 Boring Bars and Tools, 94, 194 Boring, Facing Tools, 176, 192, Boring Heads, 176, 192, 221, 264 Boring Machines, 221 jig, 20, 55-56, 261 Boring Mills, 40 Boring Service, 206, 253 Boxes, tote (See: Pans, tote) Brakes, press (See: Press Brakes) Buffing Machines, 228, 274 Burrs, 154 Bushings, 47, 175, 219, 229 Calipers, 86, 258 Cam Milling, 180

Carbide Tools (See: Tools, carbide) Centers, 262 bench, 236 lathe, 268 live. 198, 230, 239 Chilling Machines, 205 Chip Ejectors, 264 Chuck Jaws, 3, 174 Chucking Machines, 16-17, 29 Chucks, 268 lathe, 136 scroll, 136 Clamping Tools, 196 Clamps, 196, 275 air-operated, 247 "C", 4, 196, 275 toggle, 247, 275 Clutches, 286 Coil Cradles, 240 Collet Closers, 254 Collets, 136b, 167, 268, 272, 296 Comparators, dial, 214 optical, 48, 211 surface finish, 242 Control Systems, tool, 277 Coolant Chillers, 205 Coolant Mist Generators, 103, 200, 205, 256 Coolant Pumps, 179 Coolant Systems, 103, 179, 200, 205, 253, 256, 259, 275 Coolants (See: Cutting Fluids, Oils) Counterbores, 156 Couplings, flexible, 200 Cut-off Machines, 52, 54, 152, 165, 187, 202, 290 Cut-off Wheels (See: Grinding Wheels, cut-off) Cutter Grinding Fixtures, 44 Cutters, circle and hole, 229, 254, 259, 263 hydraulic contour, 229 Cutting Fluids, oils, 33, 83, 103 121, 190, 200, 256, 259, 275 Cylinders, hydraulic, pneumatic,

Deburring Machines, Tools, 23 69, 269 Degreasing Compounds, 265 Diamond Wheels, 257 Diamonds, industrial, 137 Die Filing Machines, 31, 183, 224 Die Heads, 172 Die Making Machines, 249 Die Sets. 208 Die Stock, 11, 35, 71, 127 Dies. 201, 234 press brake, 201, 237 Dividing Heads, 232 Dressers, grinding wheel, 137, 147, 169 Drill Drifts, 268 Drill Guides (See: Bushings) Drilling Equipment, 210 Drilling Fixtures, 163 Drilling Heads, 1, 180, 189, 204 Drilling Machines, 26, 39, 87 bench, 39, 87, 226 multiple spindle, 39, 87 precision, 26, 226 radial, Inside Back Cover sensitive, 26, 226 special, 295 Drilling Mules, 270 Drilling & Tapping Heads, 189 Drilling Units, 32 Drills, 18-19, 168 carbide, 256 center, 65 core, 61 high speed, 182 spade, 263 twist, 18-19, 168 Dust Collectors, 197, 243 Dye, layout, 255 End Mills, 148, 227 Engravers, 73, 76, 266 Face Mills, 148, 227 Facing Heads, 176, 259 Facing Tools (See: Tools, facing) Feed Fingers, 222 Feeds, hopper (See: Hopper Feeds) parts, 41, 59

Cams. 150, 181



Stationaire

offers all the better features of air clutches PLUS these exclusive Conway features:

Stationary air housing . . . no rotating union needed . . . no shaft drilling mount anywhere along shaft . . . just slide on . . . can be used as double clutch . . . complete interchanageability . . . one-piece construction . . . available as couplings and many others.

WRITE FOR BULLETIN 858

The CONWAY CLUTCH COMPANY

1105 MARSHALL AVE.

CINCINNATI 25, OHIO

Use postpoid card. Circle No. 470

precision, 74, 219, Back Cover

surface, 25, 60, 74, 161, 219,

tool and cutter, 8-9, 60, 74,

Grinding Wheels, 14, 22, 38, 137

cut-off, 54, 216, 257

Handles, hammer, 252, 275

Holding Tools, 4, 196, 199

Honing Fixtures, 194

Honing Machines, 194

Honing Tools, 137, 194

Hopper Feeds, 41, 59

Hose Assemblies, 253

Index Fixtures & Tools, 232

Hardness Testing Equipment, 267

Holders, tool (See: Tool Holders)

Hole Cutters, 254, 259, 263, 274

Grooving Machines, 246

Guides, band saw, 147 Hammers, 145

lead, 252, 275

Hand Cleaners, 53

machine, 182

Hinges, 271

type, 261

136a, 188, 208, 219, 228, 260,

plain, 8-9

Back Cover

Back Cover

universal, 8-9


wet or dry, 60

tap, 188, 260

roll (See: Roll Feeds) Filers, die, 224 Files, 85 oilstone, 269 rotary, 218 Filing Machines (See: Die Filing Machines) Filters, 70 Finishing Bars, 274 Finishing Machines, 69 Flexible Shaft Equipment, 233 Form Relieving Fixtures, 136a Forming Machines, 50, 152, 165 Furnaces, electrical, 170, 181. gas, 134, 138 heat-treating, 134, 138, 170, 181, 245 Gage Supplies, 42 Gages, bench, 236 carbide, 175 comparator, 211, 214, 242, 279 dial, 86 dial bore, 42 groove, 279 internal, 42 plug, 252 ring, 252 surface finish, 250 thread, 252 Gear Grinding Machines, 80-81 Gear Measuring Equipment, 142 Gear Production Equipment, 142 Gears, 200, 265 Geneva, 150 helical, 265 worm, 265 Grinders, air, 218 Grinding Machine Attachments. 8-9, 44 Grinding Machines, 69 bench, 274 centerless, 8-9 centertype, 8-9

Indexing Machines, 150 Insert Bits, 28, 61, 173 Inspection Instruments, optical, 48, 211 Jig Boring, 206, 253 Jig Feet, double end & screw type, 196 screw & press type, 196 Jigs & Fixtures, 196 Keys, machine, 258 woodruff, 258 Keyseaters, 215, 266 Keyway Cutting Equipment, 215. disc, 274 drill, 208 Knives, circular, 216 Knobs, machine, 182 flute, 188, 260 gear, 80-81 Lapping Machines, 7, 31 hand, 25 Lathe Attachments, 172, 190, heavy duty, 274 229. Inside Back Cover internal, 219 Lathe Dogs, 4 jig, 55-56 Lathes, 2, 55, Inside Back Cover optical projection, 238 armature turning, Inside pedestal, 274 Back Cover

automatic, 2, 55, 92, 203 Inside Back Cover precision, 2, 77, 184, Inside Back Cover speed, 191 tool, gage-makers, 77 turret, 184, 191, 203 Layout Dye, 255 Levers, machine, 182 Lighting Equipment, 248 Lubricants, 33, 83, 103, 121, 190, 200, 259, 275 Lubricators, fog. 103, 200, 205, Machine Keys (See: Keys, machine) Magnifiers, 248 Marking Devices, Stamps, 234, 261 Marking Equipment, 135, 261 Marking Machines, 62, 73, 76, 135, 209, 244, 266 Materials Handling Equipment. Measuring, Checking Equipment, 48, 193, 263 Metal Compounds, 222, 255 Metal Forming Machines, 50, 152, Microscopes, 263 Milling Cutters, 18-19, 148, 227, 229, 288 insert tool, 18-19, 288 Milling Machine Attachments, 199, 272 Milling Machines, 155 horizontal, 24 hydraulic, 66, 155 plain, 280 thread, 88 tool room, 24, 27, 66 tracer controlled, 66 turret, 24, 280 vertical, 24, 68, 280 engine, toolroom, 92, 191 Mist Generators, 103, 200, 259, Molds, hammer, 252, 275 Monitors, 277 Motor Arbors, 64 Motors, air turbine, 15 Mounting Pads, 78, 241 Nibblers, portable, 267 Notching Equipment, 152, 212



We happen to know it is-on this specific job!

But frequently operators will rely on "pet cutters" for milling a variety of parts and materials. Result: Either higher costs or inferior finish... and usually both.

The problem has always been to match the cutter exactly to work and machine on every job.

Solutions to problems like these are our main product. And only after a

penetrating study of machine, work, depth of cut, speed, feed rates and finish requirements do we recommend any cutter.

The inserted blade cutter pictured above is an example. On the work and the machine for which it was designed it is "the one best cutter for low cost milling."

We would welcome the opportunity to tell you more about this unique cutter selection service. Write:

Use postpoid card. Circle No. 471



This helpful new booklet tells you how to reduce the cost of chips and improve your milling and boring performance. Ask for a free copy of booklet No. 68E.

THE

INGERSOLL

CUTTER DIVISION

303 FOLION AVENUE + NOCKFORD, ILLINOIS

MACHINE and TOOL BLUE BOOK

PRODUCTS INDEX

Nozzles, coolant, 253 Oil Groovers, 246 Oilstones, 269 Optical Inspection Devices (See: Inspection Instruments. optical) Pans, tote, 226 Pantographs, 73 Parallels, box, 264 Piercing Machines, 165 Pins, taper, 258 Pipe & Tube Mills, 281 Plates, angle, 199, 264 surface, 264 Polishing Machines, 69, 183 Portable Air Tools, 32, 218 Portable Electric Tools, 32, 263 Power Units, air-hydraulic, 15, 51 Press Brakes, 152 Press Room Equipment, 53 Presses, air clutch, 282, 284 arbor, 231, 284 bench, 46 deep throat, 177 foot, 284 forcing, 10 gap type, 262 hand, 53, 225 high speed, 177 hydraulic, 10, 46, 53, 75, 225, mechanical, 282 OBI, 141, 262, 282 power (punch), 141, 152, 177, 262, 284 punch, turret, 34 straight side, 262 Pulleys, 200 Pumps, coolant & lubricant, 179 Punches, & Dies, 201 Punching Equipment, 270 Pushers, 136b, 293 Racks, machine, 258 Reamers, 18-19, 156 Rivet Spinners, 262 Riveting Machines, 262 Rod Parters, 152 Roll Feeds, 273 Roll Forming Machines, 152, 266,

Safety Products, 267, 277

Saw Blades, band, 145

circular, 45, 145


hack, Inside Front Cover, 145 hole, 145 Saw Sharpeners, 254 Sawing Machine Guides, 147 Sawing Machines, band, 183, 202, 207, 249 contour, 31, 249 cut-off (See: Cut-off Machines) friction, 58, 249 hack, Inside Front Cover Screw Machines (See: Bar Machines, automatic) Screw Sets, transfer, 265 Services: Boring, Grinding, Lapping, Milling, Repairing, etc., 180, 206, 253 Setup Tools, 270 Shafts, 233 Shapers, 63 Shearing Machines, 36-37, 152, Shearing Tools, 253, 267 Shears, hand, 267 lever, 253 Sheet Metal Machinery, 187, 202 Sleeves, 268 Slide Assemblies, 283 Slitting Cutters, 45 Slitting Machinery, 281 Sockets, 268 Solders, cold, 222 Special Machinery, 295 Speed Reducers, 200, 244 Spindles, boring, 151 grinding, 30, 151 milling, 30 Spotters, 270 Spring Coilers, 152 Sprockets, 200 Stamps, steel, 234 Steel, 11, 35, 71, 127, 145, 195 bars, 104, 127, 145, 195 plastic, 222, 255 tool, 71, 104, 127, 195 Step Blocks, 196 adjustable, 196 Stones, oil or sharpening, 269 Straight Edges, 264 Surface Finish Indicators, 250 Surface Plates (See: Plates,

rotary, index, 15, 150, 199, 210, 260 Tap Guides, 229 Tap Holders, 132 Tapping Heads, 1, 189, 204, 251 Tapping Machines, 88, 91 Taps, 18-19, 266, 293 Templates, 196 Thread Millers (See: Milling Machines, thread) Thread Rolling Machines, 88 Threading Machines, 88 Threading Tools, 88, 172 Tool Bits (See: Bits, tool) Tool Blanks, 72 Tool Holders, 4, 132, 173 adapters, 272 Tool Steel (See: Steel, tool) Tool Tips, carbide, 28, 61, 173 Tools, carbide, 28, 154, 173, 175, 229, 253 chamfering, 61 cutting-off, blade, 13, 18-19, 45, 61 deburring, 23 deburring, 23 diamond, 137 facing, 61, 227 form, circular, 18-19, 72, 136a, 229 hand, 32, 218, 263 hole cutters, 254, 259, 263, 274 setting-up, 4 thread grinding, 137 Tote Pans, 226 Transfer Machines, 223 Tube Cutting Equipment, 152, 212, 216, 290 Tube & Pipe Mills, 281 Tubing, 104, 296 Turret Attachments, 189 Turrets, lathe, 190 Valves, 84 air, 84 Vibration Control, 78, 241 Vises, bench and machine, 199, 224, 271 Wheel Dressers (See Dressers, grinding wheel) Wheels, cut-off, 54, 216, 257 machine, 182 Wire Forming Machines, 165 Wrenches, 4 impact, 4 torque, 4, 244

surface)

Swaging Machines, 49

Tables, elevating, adjustable, 67,



Fast cut-off in lengths from a fraction of an inch to several feet with micrometer accuracy. Handles any length of stock and cuts any material that can be turned-bar stock up to 3" O.D.—tubing up to 8" O.D. Will cut-off, form, groove, flange and chamfer in a single operation—at a high rate of speed.

CUTS TUBING, PIPE AND BAR STOCK FAST



WRITE for CATALOG

Describes all models. Complete specifications. Shows automatic bar feeder that handles entire load of stock with no operator attention, even with random lengths. Also, hot spinning machines and Safety Drill Tables.



MODERN MACHINE TOOL COMPANY JACKSON, MICHIGAN

Use postpaid card. Circle No. 472

Index to Advertisers

blue book

A	С
A. K. Tool Company, Inc25	3 Capewell Manufacturing Company
Aaron Machinery Company12-2	4 Carter Products Company
Abart Gear & Machine Company24	4 Chandler Tool Company
Accurate Bushing Company	3 Chicago Gear Works 200
Ace Drill Bushing Company	7 Chicago Quadrill Company
Ace Drill Corporation 25	6 Chicago Tool & Engineering Company 199
Acme-Danneman Company, Inc. 20 (Danneman Die Set Division)	8 Cincinnati Gilbert Machine
(Danneman Die Set Division)	Tool Company 40
Acme Tool Corp. 26	3 Cincinnati Lathe & Tool Company
Acromark Company 13 Active Grinding & Mig. Company 25	5 Cincinnati Milling Machine Company 8-9
Active Grinding & Mfg. Company25	2 (Grinding Machine Division)
Adjustable Clamp Company27	5 Cincinnati Milling Machine Company 33
Adjustable Clamp Company 27 Advance Products Corporation 21	0 (Products Division)
Aetna Manufacturing Company	3 Cincinnati Shaper Company
Aget Manufacturing Company 24	3 Circular 1001 Company
Alina Corporation 21 Allegheny-Ludium Steel Corporation 19	4 Clark Company, Robt. H254-259-263-274
Allegheny-Ludium Steel Corporation19	15 Clark-Cutler-McDermott Company /8
Allen Collet Manufacturing Company 29 Allen Industries, Alva 14 Allison-Campbell Division	Cleveland Automatic Machine Company 25 Cleveland Crane & Engineering Company 155
Allen Industries, Alva 14	11 Cleveland Crane & Engineering Company 158
Allison-Campbell Division	4 Cleveland Grinding Machine Company230
(American Chain & Cable Company)	Clipper Diamond Tool Company
Alvin Products, Inc. 22	22 Cogsdill Twist Drill Company, Inc
American Chain & Cable Company	64 Collis Company 26
(Allison Campbell Division) American Pullmax, Inc.	Commander Manufacturing Company 270 Commercial Filters Corporation 70
American Pullmax, Inc.	7 Commercial Filters Corporation
American Tool Works Inside Back Cove	Concentric Tool Corporation 23
Amitool Company, Inc. 2' Anderson Brothers Manufacturing Company 2' Armstrong Blum Manufacturing	76 Continental Machine Company
Anderson Brothers Manufacturing	Conway Clutch Company
Company 2:	25 Cook, Incorporated, Lawrence H
Armstrong Blum Manufacturing	Cosa Corporation 14
CompanyInside Front Cov	er Covel Manufacturing Company
Company Inside Front Cove	Cook
(Clausing Division)	91 D
Auto Moulding &	Danneman Die Set Division 20
Manufacturing Company 2	(Acmo Dannoman Company)
	Davis Keyseater Company 21
B	Denison Engineering Company
n-t- n-a	Desmond-Stephan Manufacturing
Baker Brothers, Inc. Balas Collet Manufacturing Company136	-B Company 14
Balds Collet Manufacturing Company 136	
Baldor Electric Company	
Bar Products Company 2 Barco Chemical Products Company 2	DeVlier Microbore
Barco Chemical Products Company	(Div. DeVlieg Machine Company)
Barnes Drill Company	20 Dixie Tool Industries 15
Bay Products, Inc. 2 Beaver Gear Works, Inc. 2	Donovan Manufacturing Company 27
Bedver Gedr Works, Inc. 2	
Bedford Gear & Machine	
Products, Inc.	74 27 2011
Behr-Manning Company 2 Bellows Company	69 E
Bellows Company	Eastern Machine Screw Corporation
Benchmaster Manufacturing Company 2	Eclipse Counterbore Company
Black Diamond Saw &	88 Economy Engineering Company
Plake Company Edward	83 Eisler Engineering Company
Planchard Machine Company	Electro Mechano Company 22
Blanchard Machine Company	60 Empire Tool Company
Machine Works 1 Blake Company, Edward 1 Blanchard Machine Company Boggis & Company, Henry P. 2 Reice Crane Company	26 Enco Manufacturing Company
Boice-Crane Company Boyar-Schultz Corporation	Enterprise Company
Bramil Manufacturing Company	26
Brighther Industrial Division	Ex-Cell-O Corporation 51-15
Bremil Manufacturing Company 2 Brightboy Industrial Division (Weldon Roberts Rubber Company)	Excelsior Tool & Machine Company 26
Promp & Sharpe Manufacturing	
Brown & Sharpe Manufacturing	720 F
Company 2	43 Fairfield Development Laboratories, Inc24
Busch Company, J. C.	Falls Tool Company
Byco Industries	29 Famco Machine Company 28

Manual
mpony, Jos. H. 209 tries, Inc. 173 mufacturing Company 208 Manufacturing Company 250 is Engineering Company 206 ie Tool Company 290 poration 235 Tool Company 56-57 ill & Machine Company 18-19 weather Machinery 45 Company 259 N is, Inc. 257 th American Aviation, Inc.) ingraving reporation 76 ingraving reporation 76
mpony, Jas. H. 209 tries, Inc. 173 mufacturing Company 208 Manufacturing Company 206 is Engineering Company 206 is Tool Company 290 poration 235 Tool Company 56-57 ill & Machine Company 18-19 weather Machinery 45 Company 259 N is, Inc. 257 th American Aviation, Inc.) ingraving reporation 76 ingraving reporation 76
mpony, Jas. H. 209 tries, Inc. 173 mufacturing Company 208 Manufacturing Company 250 is Engineering Company 290 poration 235 Tool Company 56-57 ill & Machine Company 18-19 weather Machinery 45 Company 259 N is, Inc. 257 th American Aviation, Inc.) ingraving reporation 76 ingraving reporation 76 ingraving reporation 76 ingraving reporation 76
mpony, Jas. H. 209 tries, Inc. 173 mufacturing Company 208 Manufacturing Company 250 is Engineering Company 290 poration 235 Tool Company 56-57 ill & Machine Company 18-19 weather Machinery 45 Company 259 N is, Inc. 257 th American Aviation, Inc.) ingraving reporation 76 ingraving reporation 76 ingraving reporation 76 ingraving reporation 76
mpony, Jas. H. 209 tries, Inc. 173 mufacturing Company 208 Manufacturing Company 250 is Engineering Company 290 poration 235 Tool Company 56-57 ill & Machine Company 18-19 weather Machinery 45 Company 259 N is, Inc. 257 th American Aviation, Inc.) ingraving reporation 76 ingraving reporation 76 ingraving reporation 76 ingraving reporation 76
mpony, Jas. H. 209 tries, Inc. 173 mufacturing Company 208 Manufacturing Company 206 is Engineering Company 206 is Tool Company 290 poration 235 Tool Company 56-57 ill & Machine Company 18-19 weather Machinery 45 Company 259 N is, Inc. 257 th American Aviation, Inc.) ingraving reporation 76 ingraving reporation 76
mpony, Jas. H. 209 tries, Inc. 173 mufacturing Company 208 Manufacturing Company 250 is Engineering Company 290 is Engineering Company 290 poration 235 Tool Company 56-57 ill & Machine Company 18-19 weather Machinery 45 Company 259 N is, Inc. 257 th American Aviation, Inc.) ingraving reporation 76 ingraving reporation 76 ingraving reporation 76
ill & Machine Company
A5 Company A5
Company 45 N is, Inc. 257 th American Aviation, Inc.) 86, 176 ingraving reporation 76 total Stamps Inc. 234
Is, Inc. 257 th American Aviation, Inc.) 86, 176 ingraving reportation 76 total Strong Inc. 234
Is, Inc. 257 th American Aviation, Inc.) 86, 176 ingraving reportation 76 total Stemps Inc. 234
Is, Inc. 257 th American Aviation, Inc.) 96, 176 ingraving rporation 76 teel Stamps, Inc. 234 Company 85
ts, Inc. 257 th American Aviation, Inc.) 86, 176 ingraving 76 teel Stamps, Inc. 234 Company 85
th American Aviation, Inc.) 96, 176 Ingraving reportation 76 teel Stamps, Inc. 234 Company 85
86, 176 176
Ingraving
rporation 76 teel Stamps, Inc. 234 Company 85
teel Stamps, Inc. 234 Company 85
Company 85
Company A H 165
Company, A. H100
rook Manufacturing
Tools, Inc
•
0
ient Company31
ery Company 202
lanufacturing Company152
nent Company 31 ery Company 202 fanufacturing Company 152 ols, Inc. 211
oration 261
n Corporation 46
o Machinery Division)
& Machine Company 50
shor 278
Poration 261 n Corporation 46 n Compony 50 sha 278 sine Company 20 ring Company 217 ry Corporation 30 te-Quick, Inc. 279 cts Corporation 205 ng Machine H. P. 266 ety Chuck Company 251
ring Company 217
ry Corporation 30
le-Ouick Inc 279
cts Corporation 205
og Machine
4 P 266
aty Chuck Company 251
ry onuck company
Machine Tool Company274
_
R
nhattan Division
Manhattan Hubber Company)
ms Company, Inc 32
pany, J. A294
mpany 253
mpany J. A. 294 mpany 253 hnical Corporation 278
pany, J. A
pany, J. A. 294 mpany 255 chnical Corporation 278 chical Corporation 278 chical Corporation 219 ol & Die Company 44
pany, J. A. 294 mpany 255 hnical Corporation 276 & Grinder, Inc. 211 ol & Die Company 44 hine Tool Company 66
pany, J. A. 294 mpany 253 innical Corporation 278 6 Grinder, Inc. 219 ol 6 Die Company 44 hine Tool Company 66 raulic, Inc. 16
Apany, J. A. 294 mpany 255 chnical Corporation 276 6 Grinder, Inc. 216 ol 6 Die Company 44 chine Tool Company 66 raulic, Inc. 11 orporation 27
1
10 10 10 10 10 10 10 10
10 10 10 10 10 10 10 10
10 10 10 10 10 10 10 10
10 10 10 10 10 10 10 10
Manhattan Rubber Company ms Company Inc. 32 32 32 32 32 33 34 34
10 10 10 10 10 10 10 10
m



WHY WAIT FOR SPECIAL TAPS?

Has them IN STOCK
for IMMEDIATE DELIVERY!

HIGH SPEED

SPECIAL

RIGHT HAND TAPS

SIZE	THREAD	SIZE	THREAD	SIZE	THREAD
00	96	15/32	32	1-3/4	5-8-10-12-14-
9	70-72-76-80	1/2	12-13-14-16-18-20-24-27-		16-18-20-24
	48-56-64-72-80-90		28-32-36-40	1-13/16	8-10-12-14-
	48-52-54-56-64-72-80	9/16	12-14-16-18-20-24-27-28-		16-18-20-24-32
3	40-44-46-48-56-60-64		32-36-40	1-7/8	5-8-10-12-14-16-18-20-20
	32-36-40-48-56-60-64-	5/8	10-11-12-14-16-18-20-24-	1-15/16	5-6-8-10-12-
	72-80	44.44	27-28-32-36-40		14-16-18-20
5	30-32-36-40-44-48-56-	11/16	10-11-12-14-16-18-20-24-	4-1/2	8-10-12-14-16-18-20
	64-80	3/4	27-28-32-40 10-11-12-14-16-18-20-24-	2-1/16	12-14-16
,	30-32-36-40-48-56-60-64- 72-80	3/4	27-28-30-32-36-40	2-1/8	8-10-12-14-
,	30-32-36-40-48-64	13/16	10-12-14-16-18-20-24-27-	2-3/16	16-18-20
	24-30-36-40-44-48-56-60-	13/19	32	2-3/16	10-12-14-
•	64-80	7/8	9-10-12-14-16-18-20-24-	2-1/4	41/2-8-10-
	24-28-32-36-40	7/0	27-28-32-40	2-1/4	12-14-16-18
0	28-30-36-40-48-56-60-64	15/16	8-9-10-12-14-16-18-20-	2-5/16	12-14-16-
2	20-22-24-28-30-32-36-40-	10,10	24-27-32-40	8-0/10	18
-	56-60	1	8-10-12-14-16-18-20-24-	2-3/8	10-12-14-
4	20-24-28-32-40		27-32-36-40		16-18
1/16	60-64-72	1-1/16	10-12-14-16-18-20-24-27-	2-1/2	4-8-10-12-
5/64	72		32		14-16-18
3/32	36-48	1-1/8	7-8-10-12-14-16-18-20-	2-9/16	12-14
/8	32-36-40-44-48		24-27-32-36	2-5/8	8-10-12-
5/32	32-36-38-40-44-48	1-3/16	8-10-12-14-16-18-20-24-		14-16-18
3/16	20-24-28-32-36-40-48		27-32	2-3/4	4-8-10-
7/32	20-24-28-32-36-40	1-1/4	7-8-10-12-14-16-18-20-		12-14-16
1/4	14-16-18-22-24-26-27-28-		24-27-32	2-7/8	8-10-12-
	30-32-36-40-48-56-64	1-5/16	6-8-10-12-14-16-18-20-		14-16
0/32	18-20-24-27-28-32-40-64	1-3/8	24-27-32 6-8-10-12-14-16-18-20-	3	4-8-10-
5/10	16-18-20-22-24-26-27-28-	1-3/8	24-27-32	39/4	8-10-12-
11/32	30-32-36-40-48-64 20-28-32-40-48	1-7/16	8-10-12-14-16-18-20-24-	3/4	14-16
3/8	12-13-14-18-20-22-27-28-	1-1/2	6-8-10-12-14-16-18-20-24	31/2	8-10-12-
3/6	30-32-36-40-48	1-9/16	12-14-16-18-20-24	3/2	14-16
13/32	16-20-24-32	1-5/8	51/2-6-8-10-12-14-	33/4	
7/16	12-14-16-18-20-24-27-28-	1.0/0	16-18-20-24	974	12-14
2/10	32-36-40	1-11/16	6-8-10-12-14-16-18-20-24	4	4-8-10- 12-14 8-10-12
	31-30-40	1 1-11/10	0-0-10-12-14-10-10-20-24	1 4	0.10.12
	HIGH SP	EED	LEET HAN	ID T	APS

		O			ID INIO
SIZE	THREAD	SIZE	THREAD	SIZE	THREAD
	80	3/8	16-24-32	1-3/8	6-8-10-12-16-18-20-24
i	56-64-72	7/18	14-20-28	1-7/16	8-10-12-14-16-18-20
2	56-64	1/2	12-13-20-28	1-1/2	6-8-10-12-16-18-20
3	56	9/16	12-18-20-24	1-9/16	8-10-12-16-18-20
4	32-36-40-48	5/8	11-12-18-20-24	1-5/8	8-10-12-14-16-18-20
5	40-44	11/16	11-16-24	1-11/16	8-10-12-14-16-18-20
6	32-36-40	3/4	10-16-18-20	1-3/4	8-10-12-14-16-18-20
8	32-36-40	13/16	16	1-13/16	8-10-12-14-16-18-20
10	24-30-32-40	7/8	9-12-14-18-20	1-7/8	8-10-12-14-16-18-20
12	24-28-32	1	8-12-14-16-18-20	1-15/18	
1/4	20-28-32	1-1/8	7-12	2	41/2-10-12
5/16	18-20-24-28-32	1-1/4	7-12-16-18		

SPECIAL AND LEFT HAND DIES IN STOCK

NOTE: Oversize, Undersize, Metric, 64th and 32nd Size Taps Available for Quick Delivery. We stock Special Sizes in High Speed Milling Cutters, Slitting Saws, End Mills and Reamers.

DEALER INQUIRIES INVITED

If you are a user of cutting tools it will pay you to be on our mailing list. Write for circular now to Dept. B.

SID TOOL COMPANY, INC.

Cutting Tool Specialists
158 LAFAYETTE ST., NEW YORK 13, N. Y.
Telephone: BEekman 3-4270

Use postpoid card. Circle No. 473

Sales Service Manufacturing Company22 Sanford Manufacturing Corporation	
Scherr Company, Inc., Geo	3
Schmidt, Inc., Geo. T24	4
Schupack Supply Company29	
Scientific Lubricants Company	0
Sealol Corporation	4
Sheldon Machine Company	4
Sid Tool Company29	3
Somma Tool Company 7	2
Simonds Saw & Steel Company	7
Sonnet Tool & Manufacturing Company22	э
Special Cutter & Tool Company	8

144 ABRASIVE WHEELS & POINTS



72 Abrasive Wheels & Points on 1/4 in. steel mandrels \$26.50

COMPLETE IN HANDY, STURDY CONTAINER AT NO EXTRA COST

If after 10 days you are not fully convinced that this is the greatest wheel and point value in the industry, return the set at no cost or obligation on your part. Illustrated Free Catalog on Request.

SCHUPACK SUPPLY CO. DEPT. MB-16 7331 Cottage Grove Ave.

Chicago 19, Illinois Use postpaid card. Circle No. 474

Spellman Company, R. L. Spittire Tool & Machine Company Standard Steel Specialty Company Stone Machinery Company Stow Manufacturing Company	258			
Stow Manufacturing Company	244			
Sturtevant Company, P. A. Sunnen Products Company	194			
Sunnen Products Company	167			
Sutton Tool Company Syntron Company	41			
Т				
Taft-Peirce, Inc.	.236			
Tamms Industries, Inc. Tannewitz Works, Inc.	267			
Tannewitz Works, Inc.	249			
Thermo-Electric Manufacturing Company Thompson Grinder Company	170			
Thompson Grinder Company	161			
Thrittmaster Products Corporation	180			
Titan Tool Company	.194			
Tomkins-Johnson Company	.227			
Torit Manufacturing Company	.197			
Torsion Balance Company Trico Fuse Manufacturing Company	267			
Trico Fuse Manufacturing Company	.200			
Twentieth Century Monutocturing				
Company	156			
Company Ty-Sa-Man Machine Company	. 58			
U				
United Instrument Company	250			
United Instrument Company	71			
Universal Cyclops Steel Corporation	23			
Universal Cyclops Steel Corporation Universal Engineering Company Universal Metal Hose Company	253			
Universal Metal Rose Company	,200			
V				
Vascoloy-Ramet Corporation	. 13			
Vac-are Cornoration	1.9926			
Versa Products Company, Inc.	84			
Victor Machinery Exchange, Inc.	182			
Versa Products Company, Inc. Victor Machinery Exchange, Inc. Vogel Tool & Die Corporation	.212			
w				
Wade Tool Company	20			
Walker-Turner Division	. 33			
(Rockwell Manufacturing Company) Wardwell Manufacturing Company	254			
Wardwell Manufacturing Company	C 17			
Warner & Swasey Company	0-17			
Watts Brothers Tool Works	210			
Weldon Roberts Rubber Company	. 44			
(Brightboy Industrial Division) Wells Manufacturing Company	207			
Wells Manufacturing Company	207			
West Chemical Products Company	201			
Whistler & Sons, Inc., S. B.	24			
Wiedemann Machine Company Wilson Air Collet Closer, Inc. Woods Machine Company, S. A.	254			
Woods Machine Company S. A.	64			
woods radenine Company, S. A.	. 04			
Y				
Yoder Company	281			
Z				
	. 1			
Zagar, Inc.	. 1			




BENDER

CUTS, BENDS, PUNCHES

Available in hand, air and hydraulic models, the MULTIFORM is shipped complete with full assortment of dies and mandrels to punch, bend, and cut round or flat brass, bronse, aluminum, steel, etc., up to ½"x1½" as illustrated, other models up to ½"x8".

J. A. RICHARDS CO. KALAMAZOO, MICH.



Designed for maximum utilization —

It goes without saying that Leland-Gifford special drilling machines deliver the production you want to the precision standards you set. But Leland-Gifford also has in mind the importance of design for maximum utilization to make your purchase of a Leland-Gifford machine a gilt-edge, quick return investment.

For Automatic Drilling at its best . . . be sure to see Leland-Gifford

CALL THE OFFICE NEAR YOU

THE JOB: Drill and ream a complete line of screw machine master collets and feed fingers ranging from 1/4" to 11/4" diameter.

THE MACHINE: A dual operating Leland-Gifford special with two work-holding fixtures and four standard self-contained drilling units equipped for either plain or step feed. Workpieces are drilled in one location, indexed to second location and reamed. Spindle speeds are precisely controlled through variable frequency input to ac spindle motors. Hydraulic feed is infinitely adjustable with separate motors driving hydraulic pumps at constant speed regardless of spindle speed.

LELAND-GIFFORD SPECIAL

DRILLING MACHINES

WORCESTER 1, MASSACHUSETTS

Chicago 5 2515 W. Puterson Ave. Detroit 10429 W. McNichole Rd.

Ave. New York Office Se. Orange Ave. South Orange, N.J. Los Angeles Office 2820 Leonis Blvd. Vernon 58, Cal.

Rochester 12, P. O. Box 24, Charlotte Statio



accuracy is our

Standard




TAPER LOCK
PUSHERS

Automatic Adjustment Positive Feed Minimum Scratch When Specified SPECIAL DETAILS TO PRINT

Let Us Quote Your Details

We Will Duplicate COLLETS, COLLET TUBES, PUSHERS and PUSHER TUBES




ALLEN COLLET MFG. CO., INC.


17720 CLARANN AVE. . MELVINDALE, MICHIGAN

MIRROR FINISH

LIGHT... but

QUALITY





All "AMERICAN" Hole Wizard Radial Drill Column Sleeves are now super-finished to a beautiful "mirror" finish.

Not only does this vastly improve the appearance of the machine but which is far more important it minimizes the danger of column cutting and scratching.

This operation is done in our own plant on a brand new 40" "AMERICAN" Pacemaker Lathe equipped with a new No. 4 Gisholt Super-finishing attachment.

This represents just another step along the path of continuous modernization to improve the quality and also the inherent value of "AMERICAN" Lathes and Radial Drills.

Descriptive bulletin No. 328 will be of interest to you. It illustrates and describes many new and exclusive features.

THE AMERICAN TOOL WORKS CO. Cincinnati 2, Ohlo, U.S.A.

LATHES AND RADIAL DRILLS

From GRAND RAPIDS

and just look at all these features:

- Powered vertical movement of wheel head*
- Instantly variable hydraulic table speed
- Greased-for-life precision ball bearing spindle with two speeds for long wheel life
- Head carried on protected pre-loaded ball bearing ways
- Equipped with Vickers vane type pump and our own control valve for infinite longitudinal table speeds from 5" to 120' per minute
- Variable speeds hydraulic cross feed and continuous cross feed
- Rugged, one-piece casting column and base for permanent rigid alignment
- Ultimate in accuracy with micro inch finish at production speeds

*Automatic downfeed available as




No. 350 PRECISION

TOOL ROOM TYPE

SURFACE GRINDER

FEED

HYDRAULIC





For full details, just send a note on your letterhead.

GALLMEYER & LIVINGSTON CO.

405 Straight Ave., S.W., Grand Rapids, Mich.